



1 STAIR 1 - Removals Plan
1/4" = 1'-0" BY ADD ALTERNATE #1

2 STAIR 2 - Removals Plan
1/4" = 1'-0"

3 STAIR 2 - New Ramp Plan
1/4" = 1'-0"

8 STAIR 3 - Removals Plan
1/4" = 1'-0"

9 STAIR 3 - New Work Plan
1/4" = 1'-0"

4 STAIR 1 - New Work Plan
1/4" = 1'-0" BY ADD ALTERNATE #1

10 STAIR 3 - New Work Elevation
1/4" = 1'-0"

11 STAIR 3 - New Work Elevation
1/4" = 1'-0"

5 STAIR 1 - New Work Elevation
1/4" = 1'-0" BY ADD ALTERNATE #1

6 STAIR 2 - New Ramp Elevation
1/4" = 1'-0"

7 STAIR 2 - New Ramp Elevation
1/4" = 1'-0"

ADD ALTERNATE #2 (STAIR 3):
ALL WORK RELATED TO STAIR 3 INCLUDING BUT NOT LIMITED TO REMOVALS, NEW WORK AND SITE WORK AS SHOWN ON A0, 8/A1, 9/A1, 10/A1, & 11/A1.

ALL GALVANIZED STEEL INCLUDING BUT NOT LIMITED TO RAILS, STRINGERS, POSTS, BALUSTERS, BRACKETS, TREADS, ANGLES, HSS, ETC. SHALL BE TREATED WITH COLORGALV SYSTEM BY DUNCAN GALVANIZING.

ADD ALTERNATE #1 (STAIR 1):
ALL WORK RELATED TO STAIR 1 INCLUDING BUT NOT LIMITED TO REMOVALS, NEW WORK AND SITE WORK AS SHOWN ON A0, 1/A1, 4/A1 & 5/A1.

TYPICAL FOUNDATION WALL:
8" C.I.P. FOUND. WALL W/ #5 VERTS @ 24" O.C. #4 CONT. @ 16" O.C. (2) #4 CONT. AT TOP & BOT OF WALL #4 HOOKED DOWELS INTO FTG @ 32" O.C.
TYP. FOOTING:
16" WIDE X 8" DEEP W/ (2) #4 CONT.