Inspections Division
Date: 07/13/17

INTERIOR FINISHES: REPLACE DRYWALL ON WALLS AND CEILING OF BUMPOUT - USE MOISTURE RESISTANT DRYWALL IN BATHROOM.

EXISTING WINDOWS, FLOORING, AND INSULATION TO REMAIN.

PROVIDE A 2'-8" POCKET DOOR INTO BATHROOM WITH A PRIVACY LOCKSET.

PLUMBING FIXTURES TO BE SELECTED BY OWNER. SUPPLY LINES FOR PLUMBING FIXTURES TO RUN WITHIN WALLS OF HEATED ROOM. PROVIDE ADDITIONAL INSULATION AT DRAIN LINES AS REQUIRED.

INSTALL AN ELECTRIC HEATER IN BATHROOM - OWNER TO SELECT

Plan Notes

W1 2x4 WOOD STUD, 1/2" DRYWALL BOTH SIDES

W2 2x6 WOOD STUD, 1/2" DRYWALL BOTH SIDES

Wall Types

$ SINGLE WALL SWITCH

GFCI COUNTER HEIGHT GFI DUPLEX WALL OUTLET

CEILING LIGHT

WALL SCONCE

F FAN

Ceiling Legend

2 Reflected Ceiling Plan
1/4" = 1'-0"

1 First Floor - New Work Plan
1/4" = 1'-0"

PERMIT DRAWINGS

38 Lower A Peaks Island, Maine 04108	DATE: JUNE 29, 2017	SCALE: As indicated	TITLE First Floor Plan and Reflected Ceiling Plan	A3