























Coastal Forest Products/ 34 Dunklee Rd Bow, NH 03304 603-623-4100

Layout Name 6489 Description

Sales Rep

Builder's Project

Framing Plan Revisions

Live Dead Deflection Joist LL Span
TL Span
LL Cant
TL Cant **Decking**Deck
Fastener SPF Plywood Nailed & Glued

Client Site Address Created

11/7/2011 12:00:00 AM **Designer** Frank Gonyea

Engineer

Project 6489

First Floor 2/14" LVL@ 1223/8 24'4" Start Joist Run (Level) G13 2 ply G12 2 ply H1 (HHUS410) H1 (HHUS410) __H1 (HHUS410)_

Web stiffeners are required for high reactions at supports. Refer to ESR-1225. 2. Web stiffeners are required under concentrated loads applied to the tops of joists between supports, or along cantilevers beyond the support, when the concentrated load exceeds 1500 pounds. 1. Plan Design Notes:

2.	Warning: Failure to follow these notes could cause property damage or personal injury.
3.	The components represented on this drawing, are designed at the request and specification of the customer as an individual building
	component, in a vertical plane, to be incorporated into the building design at the specification of the building designer.
4	Provide copies of placement drawings and designs to the structures designer and construction supervisor.

4. Provide copies of placement drawings and designs to the structures designer and construction supervisor.5. This drawing reflects our best interpretation of the plans and specifications provided to us. These drawings supplement, but do not supercede the structural design drawings for the building. The structural designer shall coordinate the placement plans with the Project Plans.

6. Please check all dimensions and materials prior to ordering. Ordering of materials based on the attached materials list constitutes review and acceptance of the placement plans. '. Handle and install products in accordance with APA Installation Guide, and Simpson Hangers Installation Guide. 8. Building Designer is responsible to insure that the loading shown on drawings is applicable to building and use.

9. The Engineered Wood Product designs are designed for gravity loads only. The Structural designer is responsible for lateral load accommodations, as required, from framing to building foundation. 10. The contractor or structural designer is responsible to insure that load bearing walls and foundations are adequate to support the loads

imposed by the framing. Design of columns, walls, and fastening is by the structures designer. 1. All roof loads assumed to be supported by exterior walls only. I-Joist are not stable until completely installed, and will not carry any load until braced and sheathed. 12. Do not stack construction materials on the floor or roof that induce loading on components greater than designated loads.

13. All flush beams noted as G, all drop beams noted as B.

14. Except for cutting to length, do not cut, drill, or notch I-Joist flanges.

15. Never install Engineered Wood products where they will be permanently exposed to weather, masonry, or concrete.

16. As an aid to the framer, this drawing may identify framing, headers, and hangers that have been specified by others.

17. This drawing is to be used only with the products specified on it.

	First Floor			
	LVL	Wistel	Donth	Length
	Qty Label Description	Width	Depth	• .
* .	2 G9 2.0E CP-LAM	1.75	14	4
	2 G10 2.0E CP-LAM	1.75	14	8
	2 G11 2.0E CP-LAM	1.75	14	10
	2 G12 2.0E CP-LAM	1.75	14	12
	4 G13 2.0E CP-LAM	1.75	14	26
	I Joist			
	Qty Label Description	Width	Depth	Length
	3 J1 NI-90X	3.5	14	6
	7 J2 NI-90X	3.5	14	10
	4 J3 NI-90X	3.5	14	12
	13 J4 NI-90X	3.5	14	26
	Rim Board			
	Qty Description	Thickness	Depth	Length
	7 APA EWS Rim Board P	lus 1.125	11.875	16
٠,٠,٠	Blocking			
<u>رو</u> نسون د	Description	Width	Width Depth Tot. Lengt	
	Hanger			
	-Qty Label Description	Girder	Supported Mbr.	
	5 H1 HHUS410	30 16d	10 16d	

Partition Wall (Non-Load-Bearing)
NI-90X 14"
2.0E CP-LAM 1.75" X 14"
APA EWS Rim Board Plus 1.125" X 11.875"

pth. city mareyor

£7788 ← of 5/01/27