SINGLE / DOUBLE HUNG

Andersen

	GLASS SIZE	LIGHT	CLEAR OPENING SIZE	VENT	MAX. RM.(SF).	EGRESS SIZE	U-VALUE
TW2832	2'-3" x 2'-7 7/8"	5.98	2'-5 7/8" x 1'-4 1/4"	3.39	75		.35
TW28310	2'-3" x 3'-3 7/8"	7.48	2'-5 7/8" x 1'-8 1/4"	4.22	94		.35
TW3052	2'-7" x 4'-7 7/8"	12.03	2'-9 7/8" x 2'-4 1/4"	6.67	150	YES	.35
244DH3030	2'-5 1/2" x 2'-11 1/2"	5.60	2'-8 9/16" x 1'-2 15/16"	3.38	84.5		.36
244DH3050	2'-5 1/2" x 4'-11 1/2"	10.52	2'-8 9/16" x 2'-2 15/16"	6.09	152.25	YES	.36
3052 *	2'-8 7/16" x 4'-7 7/8"	12.60	2'-10 11/16" x 2'-4 1/2"	6.91	158	YES	.36

* Denotes Andersen Narroline Windows

Certainteed

#	GLASS SIZE	LIGHT	CLEAR OPENING SIZE	VENT	MAX. RM.(SF).	EGRESS SIZE	U-VALUE
3236	2'-1" x 2'-4 3/8"	4.93	2'-3 1/8" x 1'-0 3/4"	2.40	60		.35
3244	2'-1" x 3'-0 3/8"	6.32	2'-3 1/8" x 1'-3 3/4"	2.97	74		.35
3766	2'-5 1/4" x 4'-9 1/8"	11.55	2'-7 1/4" x 2'-2 13/16"	5.82	144	YES	.35

Harvey

#	GLASS SIZE	LIGHT	CLEAR OPENING SIZE	VENT	MAX. RM.(SF).	EGRESS SIZE	U-VALUE
28210	Not Provided	5.77	2'-4 1/4" x 1'-2 1/16"	2.80	70		.30
2832	Not Provided	6.53	2'-4 1/4" x 1'-4 1/16"	3.20	80		.30
30410	Not Provided	11.75	2'-8 1/4" x 2'-2 1/16"	5.80	145	YES	.30
3052	Not Provided	12.70	2'-8 1/4" x 2'-4 1/16"	6.30	157	YES	.30

CASEMENTS

Andersen

#	GLASS SIZE	LIGHT	CLEAR OPENING SIZE	VENT	MAX. RM.(SF).	EGRESS SIZE	U-VALUE
C13	1'-7 3/4" x 2'-7 1/8"	4.30	1'-2 7/16" x 2'-7 1/16"	3.90	54		.28
C23	3'-3 1/2" x 2'-7 1/8"	8.50	2'-4 7/8" x 2'-7 1/16"	7.80	106		.28
CW15	2'-0" x 4'-7 1/16"	9.20	1'-8" x 4'-7"	8.40	115	YES	.28
CW25	4'-0" x 4'-7 1/16"	18.3	3'-4" x 4'-7"	16.70	229	YES	.28

Certainteed

#	GLASS SIZE	LIGHT	CLEAR OPENING SIZE	VENT	MAX. RM.(SF).	EGRESS SIZE	U-VALUE
CS2436	1'-5 1/2" x 2'-5 1/2"	3.59	11 3/16" x 2'-5 7/8"	2.32	45		.34
TCS4836	3'-0 1/2" x 2'-5 1/2"	7.48	1'-11 3/4" x 2'-5 7/8"	4.93	94		.34
CS3036	1'-11 1/2" x 2'-5 1/2"	4.81	1'-9 9/16" x 2'-5 7/8"	4.47	60		.34
CS3060	1'-11 1/2" x 4'-5 1/2"	8.73	1'-9 9/16" x 4'-5 7/8"	8.07	109	YES W EGRESS HINGE	.34
CS3660	2'-5 1/2" x 4'-5 1/2"	10.96	1'-11 3/16" x 4'-5 7/8"	8.68	137	YES	.34
TCS3636	2'-0 1/2" x 2'-5 1/2"	5.02	11 3/4" x 2'-5 7/8"	2.44	61		.34

Harvey

#	GLASS SIZE	LIGHT	CLEAR OPENING SIZE	VENT	MAX. RM.(SF).	EGRESS SIZE	U-VALUE
303-2	4.4 sq.ft.	4.4	5 1/2" x 29 3/4"	2.2	55		.30
3636-2	7.3 sq.ft.	7.3	9 1/2" x 2'-11 3/4"	4.8	91		.30

EXTERIOR DOORS

Therma-Tru

#	GLASS SIZE	LIGHT	UNIT SIZE (*NOT* R.O.)	VENT	MAX. RM.(SF).	EGRESS SIZE	U-VALUE
2'-8" (S210)		—	33 5/8" x 82"	19.14			.16
2'-8" (S262)	23 7/8 x 37 7/8"	6.28	33 5/8" x 82"	19.14	78.5 (LT only)		.28
3'-0" (S210)		—	37 5/8" x 82"	21.43			.16
3'-0" (S262)	23 7/8 x 37 7/8"	6.28	37 5/8" x 82"	21.43	78.5 (LT only)		.28
3'-0" (1 S.L.) **	9 7/8" x 37 7/8" (SL only)	2.60	52 21/32" x 82"	21.43	32.5 (LT only)		.28
3'-0" (2 S.L.) **	9 7/8" x 37 7/8" (SL only)	5.20	67 21/32" x 82"	21.43	65.0 (LT only)		.28

** Sidelights are calculated as ½ lights only

Andersen

#	GLASS SIZE	LIGHT	CLEAR OPENING SIZE	VENT	MAX. RM.(SF).		U-VALUE
FWG6068	54 1/4" x 63 1/8"	23.78	5'-11 1/4" x 6'-7 1/2"	14.72	297.25		.28
FWH6068	49 3/4" x 63 1/2"	21.92	5'-11 1/4" x 6'-7 1/2"	16.11	274.0		.28

Certainteed

#	GLASS SIZE	LIGHT	CLEAR OPENING SIZE	VENT	MAX. RM.(SF).		U-VALUE
PD7280	59" x 73 1/4"	30.01	35 3/4" x 81 1/2"	20.23	375.13		.32
FPD7280	59" x 73 1/4"	30.01	35 3/4" x 81 1/2"	20.23	375.13		.32

Harvey

#	GLASS SIZE	LIGHT	CLEAR OPENING SIZE	VENT	MAX. RM.(SF).		U-VALUE
PD6068	26 1/8 " x 73"	26.4	29 1/4 " x 76 1/8"	15.5	330.0		.34
FPD6068	26 1/8 " x 73"	26.4	29 1/4 " x 76 1/8"	15.5	330.0		.34

NON-STANDARD CUSTOM DOORS & WINDOWS

Miscellaneous

#	GLASS SIZE	LIGHT	UNIT SIZE SIZE (NOT R.O.)	VENT	MAX. RM.(SF).	EGRESS SIZE	U-VALUE
2'-8" S118	NOT PROVIDED	8.7	33 5/8" x 82"	19.1	217 LT ONLY	YES	.34
20210	4.08 sq.ft.	4.08	1.9	1.9	47.5	NA	.30

T.R. ARNOLD & ASSOCIATES, INC. PO Box 1081 Elkhart, IN 46515
State(s) MAINE
Accredited Evaluation and Inspection Agency
This document is certified as being in conformance with LISTED CODES
Jul 5, 2016
Approved By Kevin Kilute
Approval of this document does not authorize or approve any omission or deviation from the requirements of applicable State Laws.
TRA APPROVAL LIMITED TO FACTORY-BUILT MODULES ONLY.

NOTES:

1. WINDOWS, DOORS AND SKYLIGHTS OF EQUAL OR BETTER PERFORMANCE AND MANUFACTURED BY OTHER THAN SHOWN MAY BE SUBSTITUTED
2. WINDOW AREA OF HABITABLE SPACE (LIVING, DINING, INCLUDING KITCHEN/DINING IF NO OTHER DINING OR SLEEPING SPACE) SHALL BE 8 % OF FLOOR AREA FOR NATURAL LIGHT, AND 4 % OF FLOOR AREA FOR NATURAL VENTILATION. IF NOT VENTED TO EXTERIOR BATHROOMS AND TOILET ROOMS SHALL HAVE A MIN. OPENABLE AREA OF 1 1/2 . FT. FOR 3 SQ.FT OF AREA
3. WINDOWS, SKYLIGHTS AND GLASS DOORS USED SHALL BE NFRC RATED
4. EACH PLAN DESIGNED FROM BUILDING SYSTEMS WILL COMPLY WITH ENERGY REQUIREMENTS OF BUILDING ENVELOPE OF EACH COUNTY OF SPECIFIC STATE (RES CHECK WILL BE DONE FOR EACH)
5. MINIMUM WINDOW DP RATING USED IN THIS HOME IS "DP 35"

JOB NAME	BUILDER	HOUSE TYPE	WINDOW/DOOR SCHEDULE	REVISIONS	KBS BUILDERS, INC.
Purtell Peaks Island, ME 04108 50# GSL / 90 MPH WIND	Hallmark Homes Corp 619 Lewiston Road Topsham, ME 04086	4-Box Cape FILE NAME: Q-16-0117-JML SERIAL #: KBS-2735	SHEET # P10 SCALE: NONE DWN BY: SAT/ETW DATE: 06/22/16		KBS BUILDERS, INC. 300 PARK STREET, SOUTH PARIS, ME 04281 PHONE: 207-739-2400 FAX: 207-739-2223