## 088 01.9

## **REPLACEMENT SYSTEM VARIANCE REQUEST**

THE LIMITATIONS OF THE REPI ACEMENT SYSTEM VARIANCE REQUEST This form shall be attached to an application (HHE-200) for. the proposed replacement system which requires a variance to the Rules. The LPI shall review the Replacement System Variance Request an HHE-200 rnd may approve the Request if ail of the following requirements can be met, and the variance(s) requested fail within the limits of LPI's authority.

1. The proposed design meets the definition of a Replacement System as defined in the Rules (Sec. 1903)

2. There will be no change in use of the structure except as authorized for one-time exempted expansions outside the shoreland zone of major waterbodies/courses.

3. The replacement system is determined by the Site Evaluator and LPI to be the most practical method to treat and dispose of the wastewater.

4. The BODs plus S.S. content of the wastewater is no greater than that of normal domestic effluent.

| GENERAL INFORMATION   | TOWN OF PEAKS ISLAND  |
|---|---|
| Permit No   | Date Permit Issued  |
| Property Owner's Name: WALTER_SCHNELLER_  | Tel. No.: <b>766-209</b> 1  |
| System's Location: 123 UPPER A STREET   |   |
| Property Owner's Address:   |   |
| (if different from above)   |   |
| SPECIFIC INSTRUCTIONS TO THE:   |   |
| LOCAL PLUMBING INSPECTOR (LPI):<br>If any of the variances exceed your approval authority and/or do not r<br>Section above, then you are to send this Replacement System Varian<br>Department for review and approval considemtion before issuing a Per-<br>signature.)<br><u>SITE EVALUATOR:</u><br>If after completing the Application, you find that a variance for the pro-<br>Replacement Variance Request with your signature on reverse side of<br><u>PROPERTY OWNER:</u><br>If has been determined by the Site Evaluator that a variance to the Ru<br>This variance request is due to physical limitations of the site and/or a<br>considered the site/soil restrictions and have concluded that a replace<br>possible. | nce Request, along with the <b>Application</b> , to the<br>ermit. (See reverse <b>side</b> for Comments Section and your<br>sposed replacement system is needed, complete the<br>of form.<br>ules is required for the proposed replacement system.<br>soli conditions. Both the Site Evaluator and the LPI have |
| PROPERTY OWNER  |   |
| I understand that the <b>proposed system requires</b> a variance to the Rule<br>all. concerned provided they have performed their duties in a reasonabl<br>Local <b>Plumbing inspector</b> and make any corrections <b>required</b> by the <b>R</b><br><b>acknowledge permission for representatives</b> of the Department to enter<br>necessary to evaluate the <b>variance</b> request.   | le and proper manner, and i will promptiy *notify the Rules. By signing the variance request form, I  |
| SIGNATURE <b>OF</b> OWNER   | DATE  |
|   |   |
| LOCAL PLUMBING INSPECTOR<br>I. MIKE A GEA<br>best of my knowledge that it cannot be installed in compliance with th<br>Variance Request, the Application, and my on-site investigation, I (ch<br>E a. (Capprove, I disapprove) the variance request based on my at<br>give his approval, he shall list his reasons for denial in Comments Se<br>I b. find that one or more of the requested Variances exceeds my a<br>recommend) the Department's approval of the variances. Note: If the<br>she shall state his reasons in Comments Section below as to why the<br>recommended.  | The Rules. As a result of my review of the Replacement<br>teck and complete either <u>a</u> or <u>b</u> ):<br>uthority to grant this variance. Note: if the LPI does not<br>section below and return to the applicantOR   |
|   |   |

DATE HHE-204 Rev 3/97 Replacement System Variance Request

.

المراجعة والمحاد

Ę.

| VARIANCE CATEGORY  | VARIANCE REQUESTED<br>Ground Water Table<br>Restrictlys Layer              |   | LIMIT OF LPI'S<br>APPROVAL<br>AUTHORITY          |   | VARIANCE REQUESTED TO   |   |  |  |
|--|--|---|--|---|---|---|--|--|
| OILS   |  |   |  |   | <u> </u>  |   |  |  |
| oil Profile  |  |   | to   | 7.  | <u> </u>  | Inches                                      |  |  |
| oil Condition  |  |   | to   |   | inches<br>inches  |   |  |  |
| om HHE-200   | Bedrock  |   |  | to 12"  |   | inches<br>Inches                            |  |  |
| SETEACH DISTANCES (MUMU  |  |   |  |   | 88 - 1 Marco 2000 8 - 1 10 7 1  |   |  |  |
| - Fren   |  | 1000.16<br>2000.ppd   |  |   | To  | Te  |  |  |
| ells with water usage of 2000 or more gpd  | 300 ft   | 300 8   | 100 ft   | 100° ft   |   |   |  |  |
| wher's wells   | 100 down to 50 ft  | 200 down to<br>100 ft   | 100 <sup>b</sup> down<br>to 50 ft                | 100 down<br>to 50 ft  | 4 90'+  | 2512  |  |  |
| eighbor's wells  | 100 down   | 200 <sup>0</sup> down   | 100 <sup>0</sup> down                            | 1000  | <u> </u>  | 2.5   |  |  |
|  | to 60 ft   | to 120 ft   | to 50 ft   | down to   |   |   |  |  |
| /ster supply line  | 10 🕅   | 20 ft <sup>a</sup>  | 10 1   | 10 1  |   |   |  |  |
| ster course, major - for replacements only, see  | 100 down to  | 200 down to   | 100 down to                                      | 100 down  |   |   |  |  |
| able 400.4 for exempted expansions   | 60 ft  | 120 down to   | 50 ft  | to 50 ft  | · ·   |   |  |  |
| ater course, minor   | 50 down to   | 100 down to   | 50 down to                                       | 50 down   |   |   |  |  |
|  | 25 ft  | 50 ft   | 25 ft  | to 25 ft  | 1 -   | 1.  |  |  |
| rainage ditches  | 25 n<br>25 down to   | 50 down to  |  |   |   |   |  |  |
|  | 23 down to<br>12 ft  | 50 down to<br>25 ft   | 25 down to                                       | 25 down   |   |   |  |  |
| cestal wetlands, special freshwater wetlands,<br>eat ponds, rivers, streams (edge of fill  | 25 ft <sup>d</sup>   | 25 ft <sup>d</sup>  | <u>12 ft</u><br>25 ft <sup>d</sup>               | <u>to 12 ft</u><br>25 ft <sup>d</sup>                             |   |   |  |  |
| tension)<br>opes greater than 3:1  | 10 ft  | 18 R  | 20 m   | 20 II<br>N/A  |   | ·   |  |  |
| o full besement (e.g. sleb, frost well, columns)   | 15 down to   | 30 down to  | 8 down to 5                                      | 14 down   |   | +   |  |  |
| If besement (below grade foundation)   | 7 ft 20 down to  | 15 ft   | n  | 10711   |   |   |  |  |
|  | 20 down to<br>10 ft  | 30 down to<br>15 ft   | 8 down to 5<br>ft                                | 14 down<br>to 7 ft  |   |   |  |  |
| operty lines   | 10 dgwn to<br>5° ft  | 18 ft down<br>to 9 <sup>0</sup> ft  | 10 ft down<br>to 4 <sup>C</sup> ft               | 15 ft<br>down to<br>7 <sup>c</sup> ft                             |   |   |  |  |
| rial sites or graveyards, measured from the<br>win toe of the fill extension   | 25 ft  | 25 ft   | 25 ft  | 25 ft   | ······································  |   |  |  |
| THER<br>Fill extension Grade - to 3:1<br>* PROPOSED DISPOSAL AREA  | EVRTHE   | R AWAY F  | ROM WEL  |   | / EXISTING  | LESS POOL                                   |  |  |
| <ul> <li>a. This setback distance cannot b</li> <li>b. Written Permission from the ov<br/>(or 200 ft. for 1000-2000 gpd) ft</li> <li>c. Sufficient distance shall be main<br/>line.</li> <li>d. Natural Resources Protection A<br/>disturbance and 100 feet on side</li> </ul> | wher of a well i<br>bet and closer<br>Intained to assu<br>act requires a 2 | is <b>required wh</b><br>to that wail th<br>ure that <b>the to</b><br>5 foot <b>setbaci</b> | on a replacer<br>an the system<br>of the fill do | ment system<br>n it is repla-<br>bes not extended<br>th less that | <b>n will be</b> bated<br><b>cing.</b><br>and to <b>the 3:1</b> sl<br>n 20% from <b>the</b> | less than 100<br>ope or property<br>edge of |  |  |
| when no practical alternative ex   | dists.<br>Albert   | mich  | •  |   |   | /16/200,                                    |  |  |
|  | SITE EVALL   | JATOR'S SIG   | NATURE   |   |   | DATE  |  |  |

SIGNATURE OF THE DEPARTMENT

DATE

.

| SUBSURF   | ACE WAST                                   | EWATER DISPOSAL   | SYST                         | EM APPLICATIO   | N                                       | Moine Department of Human Services<br>Division of Health Engineering, Station 10<br>(207) 287-5672 FAX (207) 287-41 |  |
|---|--|---|------------------------------|---|---|---|--|
|   | ///PROPERTY I                              | OCATION////////////////////////////////////                                     | 7                            | >> Caution: Permit  |   | Attach in Space Below <<  |  |
| City, Town,<br>or Plantation                    |  | AND, PORTLAND   | V///                         |   |   |   |  |
| Street or Rood                                  | 12.8 ()0000                                | . CTDCCT  |                              |   | /////////////////////////////////////// |   |  |
| Subdivision, Lot •                              | 123 UPPER                                  | A JIKEEI  | p                            | ORTLAND   | <b>`</b>                                | 9590 TOWN COPY  |  |
|   | LOT 18<br>WINERAPPLICANT                   |   | P+                           | Permit CLAR   | 1031                                    | \$ 1000010 FEE  |  |
| Nome (last, first, MI)                          |  | Owner   | wi (                         | In la   |   | LPI # DIGILIZI  |  |
| SCINELLER<br>Mailing Address                    | · · ·                                      | WALTER Applican   | ·7//                         | Local Planding Insecto  | r Signatur                              |   |  |
| of<br>Owner                                     |  |   | -\///                        |   | ///////                                 |   |  |
| Daytime Tel. •                                  |  | ·····   |                              |   |   |   |  |
|   | 766-209                                    | ·   | Munic                        | ipal Tax Map • 885  | Lot                                     | .012  |  |
| <u> </u>  | wher or Applic                             | ant Statement   |                              | Caution   | inspecti                                | ons_Required  |  |
| I state and ocknowledge<br>my knowledge and und | that the information<br>erstand that my fa | submitted is correct to the best of<br>Isification is reason far the Deportment | t with the                   | nsp• cted the installation<br>Subsurface Wastewater Disp                          | authorized (<br>posol Rules Ap          | bove and found it to be in compliance oplication.   |  |
| and/or Local Plumbing In:                       | spector to deny a p                        | permit.   |                              |   |   | (1st) Dote Appro  |  |
|   |  |   | -                            |   | · · · · · · · · · · · · · · · · · · ·   |   |  |
| Signature of                                    | Owner/Applicant                            | Date  |                              | Local Plumbing Inspector Sign   | ature                                   | (2nd) Date Appro  |  |
|   |  |   | MI/NFC                       | FMATION ////////////////////////////////////                                      |   |   |  |
| TYPE OF A                                       | PPLICATION                                 | THIS APPLI  | CATION                       | REQUIRES  | DIS                                     | POSAL SYSTEM COMPONENTS   |  |
| 1. 🗍 First Tim<br>2. ■ Reploca                  | -  | 1. INO Rule Voriono   |                              |   | 1.                                      | Complete Non-Engineered Sys   |  |
| Type Replaced:                                  | ment System                                | 2. 🗍 First Time Syste<br>o. 🗌 Local Plumbin                                     |                              |   |   | nitive Systemfqraywoter & olt<br>rnotive Toilet, specify:   |  |
| Year Instal                                     |  |   |                              | lumbing Inspector Approval 4. 🗌 Non-  |   | -Engineered Treatment Tank (  |  |
| 3. 🗍 Expanded                                   | •  | 3. Replocement System   |                              |   |   |   |  |
| o. Cl Minor E<br>b. Cl Major E                  |  | o. 📕 Local Plumbing   |                              |   |   |   |  |
| 4. 🖸 Experimen                                  |  | 4. A Minimum Lot Siz  | -                            |   |   | omplete Engineered System(200   |  |
| 5. Saotonot                                     | -  | 5. Seosonol Convers   |                              |   |   | ngineered Treatment Tonk (only)   |  |
| SIZE OF I                                       |  | DISPOSAL  |                              |   | 10.0 Engi                               | neered Disposol Field (only)  |  |
|   | sq. 1                                      | £4  |                              | , No. of Bedrooms:_3  |   | e treatment. specify:<br>ellaneous components   |  |
| - ACRES   | > +- 📕 acre                                | 2. 🗍 Multiple Fomily Dw   | -                            |   | 1210 0000                               |   |  |
| SHORELAN  | DZONING                                    | 3. 🖸 Other:   | SPECI                        | TYPE OF WATER SUPPLY           SPECIFY         1. ■ Drilled Well 2. □ Dug Well 3. |   | ed Well 2. 🗍 Dug Well 3. 🗍 Priv   |  |
| C Yes   | • 20                                       | Current Use 🖾 Seasonal  | Year                         | Round [] Undeveloped  | 4. 🖸 Publi                              |   |  |
|   |  | /////DESIGN DETALS (SYS   | TEM LAY                      | OUT SHOWN ON PAGE   | \$//////                                |   |  |
| OR USE MON-                                     | LITTIC TAN                                 | DISPOSAL FIELD TYPE &   | SIZE                         | GARBAGE DISPOSA   | L UNIT                                  | DESIGN FLOW   |  |
| 1. Concrete                                     |  |   | rench                        | 1. 🖿 No 🛛 3. 🗖 Moyl   |   | 270 gallons per d   |  |
| 0.∎ Regular<br>b.□ Low Pr                       |  | 3. Proprietory Device   |                              | 2. Yes >> Specify   |   | BASED ON:<br>1. Toble 501.1 (dwelling unit(s  |  |
| 2. D Plastic                                    |  | a.□Cluster array c.■Linea<br>b.■Regular d.□H-2(                                 | or<br>Dilooded               | 0. Multi-compartme  |   | 2. Toble 501.2 (other facilitie   |  |
| 3. 🗋 Other:                                     | F  | 4. Other:   | 000000                       | b.[]tonks in<br>C.[] Increase in tank   |   | SHOW CALCULATIONS   |  |
| CAPACITY  | <mark>00</mark> 1 <u>o</u> ns              | SIZE  |                              | lin. ft. d. Filter on tank outlet   |   | - for other f <b>acilities -</b>  |  |
| SOIL DATA & DE                                  | SIGN CLASS                                 | 20 ELJEN IN DRAIN   |                              |   |   |   |  |
| PROFILE CONDITI                                 | on design                                  | DISPOSAL FIELD SIZING   |                              | PUMPING   |   | 3 BEDROOMS AT   |  |
| <u>2/A</u>                                      |  | 1. Small - 2.0 sq.ft./gpd   | .                            | 1. 🔲 Not required   |   | 90 GALLONS PER  |  |
| T Observotion H                                 | ole <u>'TB</u> B                           | 2. ☐ Medium - 2.6 sq.ft./gp<br>3.   |                              | 2. ■ May be required<br>3. □ Required >>Specif                                    | fy only for                             | DAY EACH  |  |
| epth <b>17</b> ''                               | 1  | 4. Large - 4.1 sq.ft./gpd   |                              | engineered or experiment  | tol systems:                            | う.ロ Section 503.0 (meter read   |  |
| F MOST LIMITING                                 | SUIL FACTOR                                | 5. 🗆 Extra-Large - 5.0 sq.f   |                              | DOSE: Gollons   |   | ATTACH WATER-METER DA   |  |
| Certify that an 19                              | 1/////////////////////////////////////     | //////////////////////SITE_EV/  | ALLIATOR                     | STATEMENT//////////////////////////////////                                       |   |   |  |
| proposed sytem                                  | in compliance v                            | i completed a site evaluation<br>with the Subsurface Wostewot                   | on this<br>ter Di <b>spo</b> | sol Rules (10-144A CMR  | t the dota<br>241) 2                    | reported is occurote and that   |  |
| M   | hat  | mich_   |                              |   |   | 003   |  |
|   |  |   |                              | X   | 1116                                    |   |  |



ALBERT FRICK ASSOCIATES - 95A CODINTY ROAD ROAD GORHAM, MAINE 04058 - (207) 859-5555





| Peaks Island | 123 Voper A Street | Walter Schneller |
|--------------|--------------------|------------------|
| TOWN         | LOCATION           | APPLICANT'S NAME |

1) The Plumbing and Subsurface Wastewater Disposal Rules adopted by the State of Maine, Department of Human Services pursuant to 22 M.R.S.A. § 42 (the "Rules") are incorporated herein by reference end made a part of this application and shall be consulted by the owner/applicant, the system Installer and/or building contractor for further construction details and material specifications. The system Installer should contact Albert Frick Associates, Inc. 839-5563, if there are any questions concerning materials, procedures or designs. The system installer and/or building contractor installing the system shell be solely responsible for compliance with the Rules and with all state and municipal laws and ordinances pertaining to the permitting, Inspection nnd construction of subsurface wastewater disposal systems.

2) This application is intended to represent facts pertinent to the Rules only. It shall be the responsibility of the owner/applicant, system installer and/or building contractor to determine compliance with nnd to obtain permits under all applicable local, state and/or federal laws and regulations (including, without limitation, Natural Resources Protection Act, wetland regulations, zoning ordinances, subdivision regulations, Site Location of Development Act and minimum lot size invs) before installing this system or considering the property on which the system is to be installed a "buildiable" lot. It is recommended that a wetland scientist be consulted regarding wetland regulations.

Prior to the commencement of construction/installation, the local plumbing inspector shall Inform the owner/Applicant and Albert Frick Associates, Inc. of any local ordinances which are more restrictive than the Rules in order that the deign may be amended, Ali designs ace subject to review by local, state and/or federal authorities. Albert Frick Associates, Inc.'s ilrbility shall be limited to revisions required by regulatory agencies pursuant to laws or regulations in effect at the time of preparation of this a p p lic ation.

3) All information shown on this application relating to property lines, well locations, subsurface swuctures and underground facilities (such as, utility lines, drains, septic systems, water tints, etc.) are based solely upon information provided by the owner/applicant and has been relied upon by Albert Frick Associates, Inc. in preparing this application. The ownedapplicant shall review this application prior lo the start of construction and confirm this information.

4) Installation of a garbage (grinder) disposal is not recommended. If one is installed, an additional 1000 gallon septic tank or a septic tank filter should be connected in series to the proposed septic tank.

5) The system user shall avoid introducing kitchen grease or fats into this system. Chemicals such as septic tank cleaners and/or chlorine (such AS from water treatment) and controlled or hazardous substances shall not be disposed of in this system.

## ATTACHMENT TO SUBSURFACE WASTEWATER DISPOSAL APPLICATION

| Peaks Island | 123 Upper A street | Walter Schoeller |
|--------------|--------------------|------------------|
| TOWN         | LOCATION           | APPLICANT'S NAME |

6) The septic tank should be pumped within two years of installation and subsequently as recommended by the pump service, but in no event should the septic tank be pumped less often than once every three years.

7) The actual water flow or number of bedrooms shall not exceed the design criteria indicated on this application without a re-evaluation of the system as proposed. If the system is Supplied by public water or a private! service with a water meter, the water consumption per period should be divided by the number Of days to calculate the average daily water consumption (water usage (cu.ft.) x 7.48 cu.ft.(gallons per cu.ft.) + # of daysill period).

8) The general minimum setbacks between a well and septic system serving a single family residence is 100-300 feet, unless the local municipality has a more stringent requirement. A well installed by an abutter within the minimum setback distances prior to the issuance of a permit for the proposed disposal system may void this design.

9) When a gravity system is proposed: **BEFORE CONSTRUCTION/INSTALLATION BEGINS**, the system installer or building contractor shall review the elevations of all points given in this application and the elevation of the existing and/or proposed building drain and septic tank inverts for compatibility to minimum slope requirements. In gravity systems, the invert of the septic tank(s) outlet(s) shall be at least 4 inches above the invert of the distribution box outlet at the disposal area. When an effluent pump is required, provisions shall be made to make certain that surface ground water does hot enter the septic tank or pump station. An alarm device warning of a pump failure shall be installed. Also, when pumping is required to a chamber system, install a "T" connection in the distribution box and place 3 inches of stone or a splash plate in the first chamber. Insulate gravity pipes, pump line8 and the distribution box as necessary to prevent freezing.

10) On all systems, remove the vegetation, organic duff and Old fill material from under the disposal area and any fill extension. On sites where the proposed system is to be installed in natural soil, scarify the bottom and sides of the excavated disposal area with a take, bo not we wheeled equipment on the scarified soil surface. For systems installed in fill, scarify the native soil by roto-tilling to a depth of at least 8 inches over the entire disposal and fill extension area to prevent glazing and to promote fill bonding. Place fill in loose layers no deeper than 8 inches and compact thoroughly before placing more fill (this ensures that voids and loose pockets all eliminated to minimize the chance of leakage). Do not use wheeled equipment on the scarified soil area until after 12 inches of fill is in place. Keep equipment off the chambers. Divert the mu-face water aWay from the disposal area by ditching or shallow swales.

11) Unless noke otherwise, fill shall be gravely coarse sand which contains no more than 5% fines (Silt and day).

12) Do not install systems on loamy, silty, or clayey soils during wet periods since soil smearing/glazing may seal off the soil interface.

13) Seed all filled and disturbed surfaces with perennial grass seed, then mulch with hay or equivalent material to prevent erosion.

