

SUBSURFACE WASTEWATER DISPOSAL SYSTEM APPLICATION

| | | | |
|---|--|--|--|
| PROPERTY LOCATION | | City, Town, or Plantation: PORTLAND PEAKS ISLAND | |
| Street or Road: MUSSEY ROAD BATTERY CRAVEN | | City, Town, or Plantation: PORTLAND | |
| Subdivision, Lot #: PROPOSED LOT B | | Date Permit Issued: 4/24/01 | |
| Name (last, first, MI): _____ Owner/Applicant | | 7675 TOWN COPY | |
| | | \$ 110.00 FEE (Double Fee Charged) | |
| Mailing Address of: RJC WEINSCHEK | | LPI # 01, 2, 4 | |
| <input type="checkbox"/> Owner <input checked="" type="checkbox"/> Applicant 33 ISLAND AVE. PEAKS IS, ME | | Municipal Tax Map # 89E Lot # 22 | |
| Daytime Tel. # 828-2900 | | | |
| Owner or Applicant Statement I state that the information submitted is correct to the best of my knowledge and understand that any falsification is reason for the Department and/or Local Plumbing Inspector to deny a permit. | | Caution: Inspections Required I have inspected the installation authorized above and found it to be in compliance with the Subsurface Wastewater Disposal Rules Application. | |
| Signature of Owner/Applicant: <i>[Signature]</i> 4/24/01 Date | | Local Plumbing Inspector Signature: _____ Date Approved: _____ | |


| PERMIT INFORMATION | | | |
|--|--|--|--|
| TYPE OF APPLICATION <input checked="" type="checkbox"/> First Time System <input type="checkbox"/> Replacement System Age Replaced: _____ Year installed: _____ <input type="checkbox"/> Expanded System <input type="checkbox"/> One-time exemption <input type="checkbox"/> Non-exempted <input type="checkbox"/> Experimental System <input type="checkbox"/> Seasonal Conversion | THIS APPLICATION REQUIRES <input checked="" type="checkbox"/> No Rule Variance <input type="checkbox"/> First Time System Variance <input type="checkbox"/> Local Plumbing Inspector Approval <input type="checkbox"/> State & Local Plumbing Inspector Approval <input type="checkbox"/> Replacement System Variance <input type="checkbox"/> Local Plumbing Inspector Approval <input type="checkbox"/> State & Local Plumbing Inspector Approval <input type="checkbox"/> Minimum Lot Size Variance <input type="checkbox"/> Seasonal Conversion Approval | DISPOSAL SYSTEM COMPONENTS <input checked="" type="checkbox"/> Complete Non-Engineered System <input type="checkbox"/> Primitive System-graywater & all toilet <input type="checkbox"/> Alternative Toilet, specify _____ <input type="checkbox"/> Non-Engineered Treatment Tank (only) <input type="checkbox"/> Holding Tank _____ Gallons <input type="checkbox"/> Non-Engineered Disposal Field (only) <input type="checkbox"/> Separated Laundry System <input type="checkbox"/> Complete Engineered System (2000 and up) <input type="checkbox"/> Engineered Treatment Tank (only) <input type="checkbox"/> Engineered Disposal Field (only) <input type="checkbox"/> Pre-treatment, specify _____ <input type="checkbox"/> Miscellaneous components | |
| SIZE OF PROPERTY 41,607 <input checked="" type="checkbox"/> sq. ft. <input type="checkbox"/> sq. ft. | DISPOSAL SYSTEM TO SERVE <input checked="" type="checkbox"/> Single Family Dwelling (1-4 Units or Berth/room) <input type="checkbox"/> Multiple Family Dwelling (5+ Units) <input type="checkbox"/> Other _____ | TYPE OF WATER SUPPLY <input type="checkbox"/> Drilled Well <input type="checkbox"/> Dug Well <input type="checkbox"/> Private <input checked="" type="checkbox"/> Public <input type="checkbox"/> Other | |
| SHORELAND ZONING <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No | | | |

| DESIGN DETAILS (SYSTEM LAYOUT SHOWN ON PAGE 3) | | | |
|--|--|---|--|
| TREATMENT TANK <input checked="" type="checkbox"/> Concrete <input type="checkbox"/> Regular <input type="checkbox"/> Low Profile <input type="checkbox"/> Plastic <input type="checkbox"/> Other _____ CAPACITY: 1000 gallons | DISPOSAL FIELD TYPE & SIZE <input type="checkbox"/> Stone Bed <input type="checkbox"/> Stone Filter <input checked="" type="checkbox"/> Proprietary Device <input type="checkbox"/> Cluster or pipe <input checked="" type="checkbox"/> Linear <input checked="" type="checkbox"/> Rebar <input type="checkbox"/> H-20 topped <input type="checkbox"/> Other _____ SIZE: 1344 sq. ft. <input checked="" type="checkbox"/> in. <input type="checkbox"/> in. 28 ELJEN IN-DRAIN UNITS | GARBAGE DISPOSAL UNIT <input checked="" type="checkbox"/> No <input type="checkbox"/> 3 <input type="checkbox"/> More <input type="checkbox"/> Yes (Specify one below) <input type="checkbox"/> Multi-compartment tank <input type="checkbox"/> Tank in series <input type="checkbox"/> Increase in tank capacity <input type="checkbox"/> Filter on tank outlet | DESIGN FLOW 360 gallons per day BASED ON: <input checked="" type="checkbox"/> Table 501.1 (Low-mid Area) L <input type="checkbox"/> Table 501.2 (Other Areas) SHOW CALCULATIONS for other facilities |
| SOIL DATA & DESIGN CLASS PROFILE: 2 / CONDITION: A/C / DESIGN: 1 Observation Hole # TP 2 Depth 22 Elevation _____ CALICEST LIMITING SOIL FACTOR _____ | DISPOSAL FIELD SIZING <input type="checkbox"/> Small - 2.0 sq. ft./cap <input type="checkbox"/> Medium - 2.5 sq. ft./cap <input checked="" type="checkbox"/> Medium-Large - 3.5 sq. ft./cap <input type="checkbox"/> Large - 4.1 sq. ft./cap <input type="checkbox"/> Extra-Large - 5.0 sq. ft./cap | PUMPING <input type="checkbox"/> Not required <input checked="" type="checkbox"/> May be required <input type="checkbox"/> Required (Specify only for engineered or experimental systems) | 4 BEDROOMS AT 90 GALLONS PER DAY EACH <input type="checkbox"/> Section 503.0 meter readings ATTACH WATER-METER DATA |

| SITE EVALUATOR STATEMENT | | | |
|--|--------------------------------|--|--|
| I certify that on 2/18/00 (date) I completed a site evaluation on this property and state that the data reported is accurate and that the disposal system is in compliance with the Subsurface Wastewater Disposal Rules and 1033-CMR 7411. | | | |
| Signature: <i>Albert Frick</i> Site Evaluator Signature | Date: 2/29/2000 Date | | |
| ALBERT FRICK ASSOCIATES - 95A COUNTY ROAD ROAD GORHAM, MAINE 04038 - (207) 638-9663 | | | |

SITE PLAN
 Scale 1" = 60 Ft.
 or as shown

SITE LOCATION PLAN
 (Attach Map from Maine Atlas for New System Variance)



APPROX PROPOSED LOT LINE (TO BE ESTABLISHED)

NOTE: PROPERTY LINE INFORMATION PER PLAN BY DANIEL DALFONSO ON FEB. 9, 2000

SOIL DESCRIPTION AND CLASSIFICATION (Location of Observation Holes Shown Above)

Observation Hole TP 2 Test Pit Boring
 Depth of Organic Horizon Above Mineral Soil

Observation Hole TP 3 Test Pit Boring
 Depth of Organic Horizon Above Mineral Soil

| Texture | Consistency | Color | Mottling |
|---------------------|----------------|-------------------|-------------------|
| CHANNERY | | DARK BROWN | |
| SANDY LOAM | FRIBLE | DARK YELLOW BROWN | |
| | | | FEW, FAINT |
| | | | FRACTURED BEDROCK |
| Soil Classification | Soil Condition | Soil Slope | Limiting Factor |
| 2 | A/C | | 22-26 |

| Texture | Consistency | Color | Mottling |
|---------------------|----------------|-------------------|-------------------|
| CHANNERY | | DARK BROWN | |
| SANDY LOAM | FRIBLE | DARK YELLOW BROWN | |
| | | | FEW, FAINT |
| | | | FRACTURED BEDROCK |
| Soil Classification | Soil Condition | Soil Slope | Limiting Factor |
| 2 | A | | 26 |

Albert Frick
 Site Engineer Signature

2/29/2000
 Date

SOIL DESCRIPTION AND CLASSIFICATION (Location of Observation Holes Shown Above)

Observation Hole TP 4 Test Pit Boring
 Depth of Organic Horizon Above Mineral Soil

| DEPTH BELOW SURFACE SOIL SURFACE IN FEET | Texture | Consistency | Color | Mottling |
|--|------------------------|-----------------|-------------------|----------|
| 0 | | FROZEN | DARK BROWN | |
| 5 | CRANNERY | | | |
| 10 | SANDY | | STRONG | |
| 15 | LOAM | FRITABLE | BROWN | |
| 30 | // FRACTURED // | | | |
| 35 | BEDROCK | | | |
| 40 | | | | |
| 50 | | | | |

| | | | |
|---------------------|-----------|-----------------|--|
| Soil Classification | Slope | Limiting Factor | <input type="checkbox"/> Ground Water |
| 2 | A | 2d | <input type="checkbox"/> Restrictive Layer |
| Profile | Condition | | <input type="checkbox"/> Bedrock |
| | | | <input type="checkbox"/> Pit Depth |

Observation Hole TP 5 Test Pit Boring
 Depth of Organic Horizon Above Mineral Soil

| DEPTH BELOW SURFACE SOIL SURFACE IN FEET | Texture | Consistency | Color | Mottling |
|--|------------------------|-----------------|-------------------|----------|
| 0 | | | DARK BROWN | |
| 5 | CRANNERY | | | |
| 10 | SANDY | FRITABLE | STRONG | |
| 15 | LOAM | | BROWN | |
| 30 | // FRACTURED // | | | |
| 35 | BEDROCK | | | |
| 40 | | | | |
| 50 | | | | |

| | | | |
|---------------------|-----------|-----------------|--|
| Soil Classification | Slope | Limiting Factor | <input type="checkbox"/> Ground Water |
| 2 | A | 2d | <input type="checkbox"/> Restrictive Layer |
| Profile | Condition | | <input type="checkbox"/> Bedrock |
| | | | <input type="checkbox"/> Pit Depth |

SOIL DESCRIPTION AND CLASSIFICATION (Location of Observation Holes Shown Above)

Observation Hole Test Pit Boring
 Depth of Organic Horizon Above Mineral Soil

| DEPTH BELOW SURFACE SOIL SURFACE IN FEET | Texture | Consistency | Color | Mottling |
|--|---------|-------------|-------|----------|
| 0 | | | | |
| 5 | | | | |
| 10 | | | | |
| 15 | | | | |
| 20 | | | | |
| 25 | | | | |
| 30 | | | | |
| 35 | | | | |
| 40 | | | | |
| 45 | | | | |
| 50 | | | | |

| | | | |
|---------------------|-----------|-----------------|--|
| Soil Classification | Slope | Limiting Factor | <input type="checkbox"/> Ground Water |
| Profile | Condition | | <input type="checkbox"/> Restrictive Layer |
| | | | <input type="checkbox"/> Bedrock |
| | | | <input type="checkbox"/> Pit Depth |


Observation Hole Test Pit Boring
 Depth of Organic Horizon Above Mineral Soil

| DEPTH BELOW SURFACE SOIL SURFACE IN FEET | Texture | Consistency | Color | Mottling |
|--|---------|-------------|-------|----------|
| 0 | | | | |
| 5 | | | | |
| 10 | | | | |
| 15 | | | | |
| 20 | | | | |
| 25 | | | | |
| 30 | | | | |
| 35 | | | | |
| 40 | | | | |
| 45 | | | | |
| 50 | | | | |

| | | | |
|---------------------|-----------|-----------------|--|
| Soil Classification | Slope | Limiting Factor | <input type="checkbox"/> Ground Water |
| Profile | Condition | | <input type="checkbox"/> Restrictive Layer |
| | | | <input type="checkbox"/> Bedrock |
| | | | <input type="checkbox"/> Pit Depth |

Albert Frick
 Site Evaluator Signature

2/29/2000
 Date



FILL REQUIREMENTS

Depth of F#1 (Shoulder) = 3' - 34"

Depth of F#1 (Downslope) = 35" - 43"

CONSTRUCTION ELEVATIONS

Finished Grade Elevation

Top of Distribution Box or Proprietary Device

Bottom of Disposal Area

ELEVATION REFERENCE POINT

Location & Description


NAIL IN PLANNED UTILITY POLE

Reference Elevation 00"


SEE
DETAIL
BELOW

SCALE:
VERTICAL 1" = 5' FT
HORIZONTAL 1" = 10' FT

DISPOSAL AREA CROSS SECTION



GRAVELLY COARSE SAND



CAP TOE OF FILL WITH SANDY LOAM MATERIAL TO PREVENT WASTEWATER BREAKOUT

Albert Frick
Site Evaluator Signature

63

2/29/2000

PROPOSED LOT B, BATTERY CRAWEN

PORTLAND (PEAKS ISLAND) HUSSEY ROAD RIC WEINSCHENK
TOWN LOCATION APPLICANT'S NAME

1) The Plumbing and Subsurface Wastewater Disposal Rules adopted by the State of Maine, Department of Human Services pursuant to 22 M.R.S.A. § 42 (the "Rules") are incorporated herein by reference and made a part of this application and shall be consulted by the owner/applicant, the system installer and/or building contractor for further construction details and material specifications. The system installer should contact Albert Frick Associates, Inc. 839-3563, if there are any questions concerning materials, procedures or designs. The system installer and/or building contractor installing the system shall be solely responsible for compliance with the Rules and with all state and municipal laws and ordinances pertaining to the permitting, inspection and construction of subsurface wastewater disposal systems.

2) This application is intended to represent facts pertinent to the Rules only. It shall be the responsibility of the owner/applicant, system installer and/or building contractor to determine compliance with and to obtain permits under all applicable local, state and/or federal laws and regulations (including, without limitation, Natural Resources Protection Act, wetland regulations, zoning ordinances, subdivision regulations, Site Location of Development Act and minimum lot size laws) before installing this system or considering the property on which the system is to be installed a "buildable" lot. It is recommended that a wetland scientist be consulted regarding wetland regulations.

Prior to the commencement of construction/installation, the local plumbing inspector shall inform the owner/applicant and Albert Frick Associates, Inc. of any local ordinances which are more restrictive than the Rules in order that the design may be amended. All designs are subject to review by local, state and/or federal authorities. Albert Frick Associates, Inc.'s liability shall be limited to revisions required by regulatory agencies pursuant to laws or regulations in effect at the time of preparation of this application.

3) All information shown on this application relating to property lines, well locations, subsurface structures and underground facilities (such as, utility lines, drains, septic systems, water lines, etc.) are based solely upon information provided by the owner/applicant and has been relied upon by Albert Frick Associates, Inc. in preparing this application. The owner/applicant shall review this application prior to the start of construction and confirm this information.

4) Installation of a garbage (grinder) disposal is not recommended. If one is installed, an additional 1000 gallon septic tank or a septic tank filter should be connected in series to the proposed septic tank.

5) The system user shall avoid introducing kitchen grease or fats into this system. Chemicals such as septic tank cleaners and/or chlorine (such as from water treatment) and controlled or hazardous substances shall not be disposed of in this system.

PORTLAND (PEAKS ISLAND) TOWN
 PROPOSED LOT B, BATTERY CRAGEN
 HUSSEY ROAD
 LOCATION
 RIC. WEINSCHENK
 APPLICANT'S NAME

- 6) The septic tank should be pumped within two years of installation and subsequently as recommended by the pump service, but in no event should the septic tank be pumped less often than once every three years.
- 7) The actual water flow or number of bedrooms shall not exceed the design criteria indicated on this application without a re-evaluation of the system as proposed. If the system is supplied by public water or a private service with a water meter, the water consumption per period should be divided by the number of days to calculate the average daily water consumption (water usage (cu. ft.) x 7.48 cu. ft. (gallons per cu. ft.) ÷ # of days in period).
- 8) The general minimum setbacks between a well and septic system serving a single family residence is 100-300 feet, unless the local municipality has a more stringent requirement. A well installed by an abutter within the minimum setback distances prior to the issuance of a permit for the proposed disposal system may void this design.
- 9) When a gravity system is proposed: **BEFORE CONSTRUCTION/INSTALLATION BEGINS**, the system installer or building contractor shall review the elevations of all points given in this application and the elevation of the existing and/or proposed building drain and septic tank inverts for compatibility to minimum slope requirements. In gravity systems, the invert of the septic tank(s) outlet(s) shall be at least 4 inches above the invert of the distribution box outlet at the disposal area. When an effluent pump is required, provisions shall be made to make certain that surface ground water does not enter the septic tank or pump station. An alarm device warning of a pump failure shall be installed. Also, when pumping is required to a chamber system, install a "T" connection in the distribution box and place 3 inches of stone or a splash plate in the first chamber. Insulate gravity pipes, pump lines and the distribution box as necessary to prevent freezing.
- 10) On all systems, remove the vegetation, organic duff and old fill material from under the disposal area and any fill extension. On sites where the proposed system is to be installed in natural soil, scarify the bottom and sides of the excavated disposal area with a rake. Do not use wheeled equipment on the scarified soil surface. For systems installed in fill, scarify the native soil by roto-tilling to a depth of at least 8 inches over the entire disposal and fill extension area to prevent glazing and to promote fill bonding. Place fill in loose layers no deeper than 8 inches and compact thoroughly before placing more fill (this ensures that voids and loose pockets are eliminated to minimize the chance of leakage). Do not use wheeled equipment on the scarified soil area until after 12 inches of fill is in place. Keep equipment off the chambers. Divert the surface water away from the disposal area by ditching or shallow swales.
- 11) Unless noted otherwise, fill shall be gravelly coarse sand which contains no more than 5% fines (silt and clay).
- 12) Do not install systems on loamy, silty, or clayey soils during wet periods since soil smearing/glazing may seal off the soil interface.
- 13) Seed all filled and disturbed surfaces with perennial grass seed, then mulch with hay or equivalent material to prevent erosion.

