

DOUBLE SIDES 7/16" STRUCTURAL SHEATHING 0.148"X2" NAILS UNLESS NOTED OTHERWISE \* FIELD FASTENING 12" O.C. TYPICAL

FORCE REQUIRED = 11273 LB

3" O.C. STAGGER W/ DOUBLE EDGE FRAMING

FASTEN TOP/BOTTOM PLATES TO RAILS W/ (2) ROWS 0.131"x2.5" NAILS @ 4" O.C. SILL TO FOUNDATION ON SITE BY OTHERS FOR 575 PLF RIM TO SILL = LAPPED SHEATHING W/ 0.131"x3" NAILS @ 2" O.C.

REAR RIGHT SIDE FRONT ELEVATION LEFT SIDE 2001 WFCM - 100 MPH W/EXPOSURE "C" BUILDING ASPECT RATIO (L/W) = 2.35%SHEAR WALL PERCENTAGE REQUIRED 28% 28% 70% ENGINEERED WALL PROVIDED 53% 76% 72% 8D COMMON FASTENING EDGE/FIELD 3"/12" 6"/12" O.C 6"/12" O.C 0.C

A 등 무 등 급 ABEL AND DATA PLA TE INDEX:

THIRD PARTY LABEL

MAINE STATE LABEL

CATA PLATE

CODE PLATE

MAINE HOUSING BOARD NEW HOMES WARRANTY

S INSTALLATION WARRANTY SEAL



ber, dgs, date, and return to NESI. Plans not checked, dgsset, and dated will be return to Ballier and subject to removal from Production Scheduling.

- I HAVE REVIEWED THESE PLANS FOR ACCURACY AND HEREBY AUTHORIZE N.E.H. TO DO THE FOLLOWING;
- REVISE THESE PLANS AS NOTED AND SEND ME ANOTHER SET OF PERMIT PLANS TO REVIEW.

NEW ENGLAND HOMES INDEPENDENT BUILDERS DULY AUTHORIZED AGENT PER CONTRACT AGREEMENT

3'-3/4

EGRESS PARC74X48LR

DO NOT INSTALL THE SLOPED — WALL ON THE FIRST TREAD, BUILDER TO SITE SUPPLY AND NINSTALL A BULLNOSE STARTER

/M

PANTRY L

UNDER STAIRS BY OTHERS

3/ 1 3/4" x 11-1/4" LVL

DE PERSON

(SHIP LOOSE

2/ 1 3/4" x 7" LYL EA, SIDE IN ROOF

UDROOM

ZIM)

116

R-21 BLOWN-IN INSULATION W/ VAPOR BARRIER PAINT AND INSULWEB

RAISE DOOR 3/4"
5'-11'3/21' 21'0 SPF#2 HEADER

LP-LP

2

BOOK SHELVES BY OTHERS

tread on site

IV MIOXGO STEEL BEAM EA. SIDE 2ND FLOOR DECK (CEILING ST

ĀPPED)

1'-0"

 $\sqrt{8}$ 

3'-10/2"

/bM

REFER TO SIIO FOR W7 WALL FRAMING

2/ 2x10 SPF#2 HEADER

SLOPED WALL

00

2x6 4'-1/

10" WIDE

恳

PORCH

5118-1

GEP#6

WAL

36X48R

SLOPED WALL W/ PINE CAP 4"
SHORTER THAN STANDARD.
BUILDER TO SUPPLY AND
INSTALLED RAIL ON TOP OF

CHASE FOR SITE SUPPLIED AND INSTALLED FUTURE ELEVATOR BY OTHERS. NEH TO FILL PIT IN WITH TEMP FLOOR/CEILING FRAMING

12'-5"

22'-7"

27'-2"

 $\langle \Sigma \rangle$ 

(EM)

W4

— SPF SUPPORT DECK TO BE REMOVED ON SITE BY OTHERS. DECK AND STAIRS ON SITE BY OTHERS.

SIDE /KI

34'-105/16"

3'-65%"

6'-115/8" SP

7'-11/4" LP

deck to be attached to house as per 2009 RC, section R502.2.2 decks (R502.2.2 thru R502.2.2.4)

SLOPED WAL

3'-1/2"

**PERMIT PLANS** 

THERE ARE NO CHANGES TO THIS PLAN, RELEASE THE JOB FOR PRODUCTION. REVISE THE PLANS AS NOTED AND RELEASE THESE PLANS FOR PRODUCTION.