

		ROOF	
ГЕМ	DESCRIPTION OF BUILDING ELEMENTS	NUMBER AND TYPE OF FASTENER a,b,c	SPACING AND LOCATION
1	BLOCKING BETWEEN CEILING JOISTS OR RAFTERS TO TOP PLATE	4-8d BOX (2-1/2"x0.113") OR 3-8d COMMON (2-1/2"x0.131") OR 3-10d BOX (3"x0.128") OR 3-3"x0.131" NAILS	TOE NAIL
2	CEILING JOISTS TO TOP PLATE	4-8d BOX (2-1/2"x0.113") OR 3-8d COMMON (2-1/2"x0.131") OR 3-10d BOX (3"x0.128") OR 3-3"x0.131" NAILS	PER JOIST, TOE NAIL
3	CEILING JOIST NOT ATTACHED TO PARALLEL RAFTER, LAPS OVER PARTITIONS {(SEE SECTIONS R802.3.1, R802.3.2 AND TABLE R802.5.1(9)}	4-10d BOX (3"x0.128") OR 3-16d COMMON (3-1/2"x0.162") OR 4-3"x0.131" NAILS	FACE NAIL
4	CEILING JOIST ATTACHED TO PARALLEL RAFTER (HEEL JOINT) {(SEE SECTIONS R802.3.1, R802.3.2 AND TABLE R802.5.1(9)}	TABLE R802.5.1(9)	FACE NAIL
5	COLLAR TIE TO RAFTER, FACE NAIL OR 1-1/4"x20GA. RIDGE STRAP TO RAFTER	4-10d BOX (3"x0.128") OR 3-10d COMMON (3"x0.148") OR 4-3"x0.131" NAILS	FACE NAIL EACH RAFTER
6	RAFTER OR ROOF TRUSS TO PLATE	3-16d BOX NAILS (3-1/2"x0.135") OR 3-10d COMMON NAILS (3"x0.148") OR 4-10d BOX (3"x0.128") OR 4-3"x0.131" NAILS	2 TOE NAILS ON ONE SIDE AND 1 TOE NAIL ON OPPOSITE SIDE OF EACH RAFTER OR TRUSS
7	ROOF RAFTERS TO RIDGE, VALLEY OR HIP RAFTERS OR ROOF RAFTER TO MINIMUM 2* RIDGE BEAM	4-16d (3-1/2"x0.135") OR 3-10d COMMON NAILS (3-1/2"x0.148") OR 4-10d BOX (3"x0.128") OR 4-3"x0.131" NAILS	TOE NAIL
		3-16d BOX (3-1/2"x0.135") OR 2-16d COMMON (3-1/2"x0.162") OR 3-10d BOX (3"x0.128") OR 3-3"x0.131" NAILS	END NAIL
		WALL	
8	STUD TO STUD (NOT AT BRACED WALL PANELS)	16d COMMON (3-1/2"x0.162")	24" O.C. FACE NAIL
		10d BOX (3"x0.128") OR 3"x0.131" NAILS	16" O.C. FACE NAIL
9	STUD TO STUD AND ABUTTING STUDS AT INTERSECTING WALL CORNERS (AT BRACED WALL PANELS)	16d BOX (3-1/2"x0.135") OR 3"x0.131" NAILS	12" O.C. FACE NAIL
		16d COMMON (3-1/2"x0.162")	16" O.C. FACE NAIL
10	BUILT-UP HEADER (2" TO 2" HEADER WITH 1/2" SPACER)	16d COMMON (3-1/2"x0.162")	16" O.C. EACH EDGE FACE NAI
		16d BOX (3-1/2"x0.135")	12" O.C.EACH EDGE FACE NAIL
11	CONTINUOUS HEADER TO STUD	5-8d BOX (2-1/2"x0.113") OR 4-8d COMMON (2-1/2"x0.131") OR 4-10d BOX (3"x0.128")	TOE NAIL
12	TOP PLATE TO TOP PLATE	16d COMMON (3-1/2"x0.162")	16" O.C. FACE NAIL
		10d BOX (3"x0.128") OR 3"x0.131" NAILS	12" O.C. FACE NAIL
13	DOUBLE TOP PLATE SPLICE FOR SDCs A-D ₂ WITH SEISMIC BRACED WALL LINE SPACING < 25'	8-16d COMMON (3-1/2"x0.162") OR 12-6d BOX (3-1/2"x0.135") OR 12-10d BOX (3"x0.128") OR 12-3"x0.131" NAILS	FACE NAIL ON EACH SIDE OF END JOINT (MINIMUM 24" LAP SPLICE LENGTH EACH
	DOUBLE TOP PLATE SPLICE SDCs D ₀ , D ₁ OR D ₂ ; AND BRACED WALL LINE SPACING ≥ 25'	12-16d (3-1/2"x0.135")	SIDE OF END JOINT)

T.R. ARNOLD & ASSOCIATES, INC. 4700
State(s) ____ MAINE

Aug 8, 2017 Letta Littee al of this document does no Justinorice or appro-sission or deviation from the requirements of

ID THESE PLANS FOR ACCURACY AND HEREBY AUTHORIZE N.E.H. TO DO THE FOLLOWING NO CHANGES TO THIS PLAN, RELEASE THE JOB FOR PRODUCTION. THERE ARE NO CHANGES TO THIS PLAN, RELEASE THE JOB FOR PRODUCTION.

REVISE THE PLANS AS NOTED AND RELEASE THESE PLANS FOR PRODUCTION.

REVISE THESE PLANS AS NOTED AND SEND ME ANTHER SET A CONTINUED OF THESE PLANS FOR PRODUCTION.

10

277 Locust Street, Salle B Dover, Mt 0820 www.nevenglandhome.net (telephone)600.80018831 (tm.)503.451.8640

EEEEEE

11256

to for the also computes of the membrated product is ULTHATELY the STAR. It of THE SHALOR LISTED SHALOR to based and flats. **New England** Homes

COLONAL