

LIGHT FIXTURE SCHEDULE					
TYPE	DESCRIPTION	MFR.	LAMPS	MOUNTING	NOTES
A	6"x6" 2 LAMP, PENDANT, DIRECT FLUORESCENT WITH PARABOLIC BAFFLES 277V	LITECONTROL P-D-66N24T8-PBSS	2-32W T8	PENDANT 8'-3" TO BOTTOM	MOST ARE EXISTING. NEW AND RELOCATED FIXTURES ARE SHOWN DARK.
A2	6"x6" 2 LAMP, PENDANT, DIRECT/INDIRECT, FLUORESCENT WITH PARABOLIC BAFFLES. 277V	LITECONTROL P-S/D-66N24T8-PBSS	2-32W T8	PENDANT 8'-3" TO BOTTOM	MOST ARE EXISTING. NEW AND RELOCATED FIXTURES ARE SHOWN DARK.
A3	6"x6" 2 UV FILTERED LAMPS, PENDANT DIRECT FLUORESCENT WITH PARABOLIC BAFFLES. 277V	LITECONTROL P-D-66N24T8-PBSS	2-32W T8 UV FILTERED	PENDANT 8'-3" TO BOTTOM	
A4	6"x6" 2 LAMP, PENDANT, DIRECT/INDIRECT, FLUORESCENT W/ PARABOLIC BAFFLES & DIMMING BALLAST. 277V	LITECONTROL P-S/D-66N24T8-PBSS-DU	2-32W T8	PENDANT 8'-3" TO BOTTOM	DIMMING BALLASTS.
A5	6"x6" 2 LAMP, RECESSED FLUORESCENT W/ PARABOLIC BAFFLES. 277V	LITECONTROL LG-D-66N24T8-PBSS	2-32W T8	RECESSED	
B1	SURFACE MOUNTED COMPACT FLUORESCENT DOWNLIGHT 277V	KURT-VERSEN P636-277	1-18W QUAD	SURFACE	EXISTING
C1	2'x2', 2 LAMP, PARABOLIC TROFFER WITH 9" CELL 4" DEEP LOUVERS. 277V	LITHONIA PARAMAX 2PM4-G-B-2-U40-9LD-277-GEB	2-40W U-LAMPS	RECESSED	EXISTING.
C2	2'x2', 2 LAMP, PARABOLIC TROFFER, WITH 9" CELL 4" DEEP LOUVERS AND DIMMING ELECTRONIC BALLAST. 277V	LITHONIA PARAMAX 2PM4-G-B-2-U316-9LD-277-GEB-DIM	2-31W T8 U-LAMPS	RECESSED	
C3	2'x2', 2 LAMP, PARABOLIC TROFFER, WITH 4" DEEP LOUVER. 277V	LITHONIA PARAMAX 2PM4-G-B-2-U316-9LD-277-GEB	2-31W T8 U-LAMPS	RECESSED	
C4	2'x2', 2 LAMP, SPECIFICATION GRADE NON-AIR TROFFER W/FLANGE KIT FOR MOUNTING IN DRYWALL CEILING. 277V	COLUMBIA 4PS22-31U1-G FSA12-EB8277	2-31W T8 U-LAMPS	RECESSED	PROVIDE FLANGE KIT PART NO. FK22 TO MOUNT IN DRYWALL CEILING.
D	4' SURFACE MOUNTED FLUORESCENT WRAPAROUND 277V	KEYSTONE 20M240A-277	2-32W T8	SURFACE	EXISTING
D1	4' SURFACE MOUNTED FLUORESCENT WRAPAROUND 277V	COLUMBIA WC4-232-EB8277	2-32W T8	SURFACE	
E1	EXIT SIGN, SINGLE FACE, RED LETTERS ON WHITE FACE AND HOUSING. 277V	DUAL-LITE 2FLX-1-RW-W2K-SINGLE FACE	2-5W PL	UNIVERSAL	MOST ARE EXISTING. RELOCATED FIXTURES ARE SHOWN DARK.
E2	EXIT SIGN, DOUBLE FACE, RED LETTERS ON WHITE FACE AND HOUSING. 277V	DUAL-LITE 2FLX-1-RW-W2K-DOUBLE FACE	2-5W PL	UNIVERSAL	MOST ARE EXISTING. RELOCATED FIXTURES ARE SHOWN DARK.
E3	EXIT SIGN, RED LETTERS, WHITE STENCIL AND HOUSING. UNIVERSAL MOUNTING 277V	DUAL-LITE LITECELL SERIES KSR-LLED	LED	UNIVERSAL	SINGLE FACE. FOR DOUBLE FACE CHANGE S TO D.
F	PENDANT MOUNTED ARCHITECTURAL DOWN LIGHT. COPPER COLOR 120V	LOUIS POULSEN NYHAW NYP-346-COPPER	1-75W TUNGSTEN HALOGEN T-10	PENDANT	MOUNT LIGHT 7"-6" AFF
G	6"x6" 2 LAMP, WALL MOUNTED, DIRECT FLUORESCENT WITH BLADE BAFFLES. 277V	LITECONTROL W-D-66N24T8-BW	2-32W T8	WALL	EXISTING
H	NON-METALLIC, FLUORESCENT GLOBED & GUARDED FIXTURE SUITABLE FOR DAMP LOCATIONS. 120V	RIG-A-LITE CVPD-18F-12-HR-G-W	1-18W DTT	WALL	
J	NOT USED.				
K	4' FLUORESCENT STRIP LIGHT. 277V	COLUMBIA CH4-132-EB8277	1-32W T8	SURFACE	USED IN COVES.
L	2'x2', RECESSED INDIRECT FLUORESCENT WITH DIMMING BALLAST. 277V	COLUMBIA STR22-240TTG-MPO-EB80277	2-40W TWIN TUBE	RECESSED	
P	8" VERTICAL QUAD OPEN, RECESSED COMPACT FLUORESCENT DOWNLIGHT. CLEAR ALZAK REFLECTOR. 277V	PRESCOLITE CFQ826EB-STF802	1-26W QUAD	RECESSED	
P1	8" VERTICAL QUAD OPEN, RECESSED COMPACT FLUORESCENT DOWNLIGHT. CLEAR ALZAK REFLECTOR, DIMMING BALLAST. 277V	PRESCOLITE CFQ826EBDM-STF802	1-26W QUAD	RECESSED	
S6	EXTERIOR SURFACE MOUNTED METAL HALIDE AREA/ACCENT LIGHT. 277V	KURT-VERSEN S22-250277-EF MHS	1-250W MH	SURFACE	EXISTING
T	TRACK LIGHTING, WHITE, LOW VOLTAGE, ROUND BACK CYLINDER W/INTEGRAL TRANSFORMER AND LOW VOLTAGE DIMMER. PROVIDE W/SOFTENING LENS AND UV FILTER. PROVIDE 8" WHITE SINGLE CIRCUIT TRACK UNLESS OTHERWISE SHOWN ON DRAWINGS 120V	PRESCOLITE GALLERY STYLE TV372-WH-LV19-LV701.	1-50W FL MR16 ANSI TYPE EXN	LIGHTING TRACK. PROVIDE 18" STEM & 12" LOW VOLTAGE WAND UNLESS NOTED OTHERWISE.	INSTALL 2' FROM WALL UNLESS OTHERWISE NOTED. FIXTURE SHALL BE INSTALLED AT 8'-6" AFF UNLESS OTHERWISE NOTED.
U	4" ROUND, SMALL APERTURE ADJUSTABLE DOWNLIGHT W/ CLEAR ALZAK REFLECTOR. 120V	PRESCOLITE PH4A-TA4C	1-50W PAR 20	RECESSED	
**	FIBER OPTIC ILLUMINATORS, GLASS END EMITTING CABLES, AND FIXTURE FOR FIBER OPTIC LIGHTING OF DISPLAY CASES.	LUCIFER LIGHTING ILLUMINATORS: 7-#ILQH-1 (X)  1-#ILMH-1 (X)  FIBERS: 46-#FBGE-S36 16-#FBGE-S24  FITTURE: 62-#FDL-12M	7-75W MR-16  1-150W HQI  (USED WITH ILQH)  (USED WITH ILMH)		6 OF THE ILQH-1 ILLUMINATORS TO BE MOUNTED IN BOTTOM OF DISPLAY CASES. 1 ILMH-1 ILLUMINATOR AND THE REMAINING ILQH-1 ILLUMINATOR TO BE MOUNTED ON SHELF IN OSHA STORAGE ROOM 613. INSTALLATION OF FIXTURES IN TOP OF DISPLAY CASES TO BE COORDINATED WITH ARCHITECT. PROVIDE COLOR WHEEL WITH EACH ILLUMINATOR.  X = QUANTITY OF FIBERS TO BE PROVIDED IN FIBER BUNDLE FROM ILLUMINATOR. QUANTITY IS SHOWN ON POWER PLANS.

**NOTE:**

1. SEE SHEET E-001 FOR LEGEND AND GENERAL NOTES.

0	ISSUED FOR CONSTRUCTION	3-17-03
REV.	DESCRIPTION	DATE

**ISSUED FOR CONSTRUCTION**  
**3-17-03**

CURRENT ISSUE STATUS:

--	--	--

**SMRT** ARCHITECTURE ENGINEERING PLANNING  
 SMRT  
 144 Fore Street/P.O. Box 618  
 Portland, Maine 04104  
 tel. (207) 772-3846  
 fax. (207) 772-1070

**GLICKMAN LIBRARY**  
**UNIVERSITY OF SOUTHERN MAINE**  
 PORTLAND, MAINE

PROJECT: **LIGHTING SCHEDULE**

SHEET TITLE:	SCALE:	NOT TO SCALE	DATE:
PROJECT MANAGER: SLB	GRAPHIC SCALE:	0" = 1"	
JOB CAP/DRAWN: CTB/JAC			
A/E OF RECORD: JPP			SHEET No.
SMRT CAD FILE: EL601-99092			<b>EL601</b>
PROJECT No. 99092			

A1

1/8"=1'-0"