

Certificate of Design Application

Mark D. Lee, AIA - Harriman

| Date: | August 5, 2015 | |
|--|---|--|
| ob Name: | University of Southern Maine Departr | ment Reorganization |
| Address of Construction: | 96 Falmouth Street, Building 5, Luthe | er Bonney Hall |
| Cons | University of Southern Maine Department Reorganization 2009 International Building Code Instruction project was designed to the building code criteria listed below: BC Use Group Classification (s) Business, A-3 Assembly If yes, separated or non separated or non separated (section 302.3) Geotechnical/Soils report required? (See Section 1802.2) No, No exterior work Is such a separated or non separated or non separated (section 302.3) Live load reduction Roof fine loads (1603.12, 1607.11) Roof snow loads (1603.12, 1607.11) Roof snow loads (1603.7.3, 1608) Ground snow loads (1603.7.3, 1608) Ground snow load, Pg (1608.2) If Pg > 10 psf, snow exposure factor, G If Pg > 10 psf, snow exposure factor, G If Pg > 10 psf, snow load importance factor, G If Pg > 10 psf, snow classing system (1617.6.2) Roof thermal factor, G (1608.4) Seismic design category (1616.3) Basic seismic force resisting system (1617.6.2) Analysis procedure (1616.6, 1617.5) Design base shear (1617.4, 1617.5.1) Flood Ioads (1607.5) Concentrated loads (1607.5) Concentrated loads (1607.5) Concentrated loads (1607.5) | |
| Building Code & Year 2009 IE | Use Group Classification | n (s) Business, A-3 Assembly |
| Type of Construction II-B | | |
| Will the Structure have a Fire su | ppression system in Accordance with S | Section 903.3.1 of the 2009 IRC No |
| s the Structure mixed use? Yes | If yes, separated or non sep | parated or non separated (section 302.3) |
| | | |
| Structural Design Calculation | s | Live load reduction |
| Submitted for all structural members (106.1 – 106.11) Design Loads on Construction Documents (1603) Uniformly distributed floor live loads (7603.11, 1807) Floor Area Use Loads Shown | | Roof live loads (1603.1.2, 1607.11) |
| | | Roof snow loads (1603.7.3, 1608) |
| | | Ground snow load, Pg (1608.2) |
| | | If $Pg > 10$ psf, flat-roof snow load pf |
| | | If $P_g > 10$ psf, snow exposure factor, G |
| | | If $Pg > 10$ psf, snow load importance factor, I_c |
| | | Roof thermal factor, $_{G}$ (1608.4) |
| | | Sloped roof snowload,p ₃ (1608.4) |
| Wind loads (1603.1.4, 1609) | | Seismic design category (1616.3) |
| Design option utilized (1609.1.1, 1609.6) | | Basic seismic force resisting system (1617.6.2) |
| Basic wind speed (1809.3) | | Response modification coefficient, R1 and |
| Building category and wind importance Factor, but table 1604 5 1609 5 | | deflection amplification factor $_{Gl}$ (1617.6.2) |
| table 1604.5, 1609.5) Wind exposure category (1609.4) | | Analysis procedure (1616.6, 1617.5) |
| Internal pressure coefficient (ASCE 7) | | Design base shear (1617.4, 16175.5.1) |
| Component and cladding pressures (1609.1.1, 1609.6.2.2) | | Flood loads (1803.1.6, 1612) |
| Main force wind pressures (7603.1.1, 1609.6.2.1) | | Flood Hazard area (1612.3) |
| Earth design data (1603.1.5, 1614-1623) | | Elevation of structure |
| Design option utilized (1614.1) | | Other loads |
| Seismic use group ("Category") | | Concentrated loads (1607.4) |
| • • • | | , |
| Site class (1615.1.5) | | Misc loads (Table 1607 8 1607 6 1 1607 7 |

1607.12, 1607.13, 1610, 1611, 2404