				_	_IGHTING	FIXTURE	SCHEDULE		
	FIXT. TYPE	MANUFACTURER	CATALOG NO.	VOLTS	NO. OF LAMPS	LAMP TYPE	MOUNTING	DESCRIPTION	
4	\supset	CORELITE ALERA LIGHTING	NAVIGATOR NBLM2T8-1C(IE)-AC ALS2T8-20/80-CM-XX- LD-XX-277MW-XX-X	277	<u>></u> >	F032/835/XPS/EC0 OR F32T8/SXL/SP35/EC0	PENDANT	DIRECT/INDIRECT FIXTURE, 30-20% UP AND 70-80% DOWN, FOR FIXTURE LENGTH AND NO. OF SECTIONS SEE PLANS. ALUMINUM HOUSING.	
	Al	CORELITE ALERA LIGHTING	NAVIGATOR NBLM3T8-2C(2E)-AC ALS3T8-20/80-CM-XX- LD-XX-277MW-XX-X	277	3	F032/835/XPS/EC0 OR F32T8/SXL/SP35/EC0	PENDANT	SAME AS FIXTURE TYPE "A" EXCEPT WITH 3 LAMPS AND TWO CIRCUITS FOR INNER/ OUTSIDE LAMP CONTROL.	
	В	CORELITE ALERA LIGHTING	NAVIGATOR NBNM2T8-1C(1E)-AC (3) ALS2T8-0/100-CM-XX- LD-XX-2/7MW-XX-X	277	2	F032/835/XPS/EC0 OR F32T8/SXL/SP35/EC0	PENDANT	SAME AS FIXTURE TYPE "A" EXCEPT 100% DOWN.	
	5	COOPER LIGHITNG	C6218-E-6251-LI-HB26	277	2	CF18DT/E/IN/835	RECESSED	6" DIA. OPEN DOWNLIGHT WITH CLEAR REFLECTOR AND WHITE TRIM, ELECTRONIC BALLAST.	
	<u>G</u> 1	COOPER LIGHITNG	C6218-E-6211-LI-HB26	277	2	CF18DT/E/IN/835	RECESSED	6" DIA. OPEN WALLWASH WITH CLEAR REFLECTOR AND WHITE TRIM, ELECTRONIC BALLAST.	D =
	工	LINEAR LIGHTING	WW2-D-I-ET8- 277-PBL-R-N0-XX (2)	277		F032/835/XPS/EC0 OR F32T8/SXL/SP35/EC0	RECESSED	LINEAR COVE LIGHT WITH BLADES, LENGTH AS SHOWN ON DRAWINGS.	П
		ROBERT	D/I-22-C-BIAX-277V	277	2	FT40DL/835/RS	RECESSED	2'X2' FLUORESCENT DIRECT/INDIRECT FIXTURE WITH PERFORATED LAMP ENCLOSURE.	
	J2	ROBERT	D/I-24-C-XX-277V (3)	277	2	F032/835/XPS/EC0 OR F32T8/SXL/SP35/EC0	RECESSED	SAME AS TYPE "J" EXCEPT 2'X4' FIXTURE	
	S	NEORAY	41/2T8-S72-XFT ③	277	○ >	F032/835/XPS/EC0 OR F32T8/SXL/SP35/EC0	RECESSED	FLUORESCENT RECESSED LINEAR FIXTRE WITH BOLD BAFFLES 1.2" O.C. FOR SECTIONS LENGTH REFER TO PLANS	
	S1	NEORAY	41/2T8-S72-XFT- (3)	277	○ >	F032/835/XPS/EC0 OR F32T8/SXL/SP35/EC0	RECESSED	SAME AS TYPE "S" EXCEPT WITH DIMMING BALLAST. FOR SECTION LENGTH REFER TO PLANS.	
	\Box	ALERA LIGHTING	ME-XX-232-CM-PAB-3 XX-277	277	2	F032/835/XPS/EC0 OR F32T8/SXL/SP35/EC0	PENDANT	2-LAMP PENDANT FIXTURE WITH PARABOLIC LOUVERS, FOR FIXTURE LENGTH AND NO. OF SECTIONS SEE PLANS.	
	Z	ALKC0	EG-12-FL-2-DS	120	2	6WT5	WALL	"IN-USE" LIGHT	
	EB	HINOHTIL	ELU4N-V-H1212 ELA MS4/8 — SHELF	120	2	12 W INC.	WALL	BATTERY PACK WITH TWO LAMPS, BATTERY — NICKEL CADMIUM, 50W CAPACITY	
	×	LIGHT PANEL TECHNOLOGIES, LLC	DCA-AC-2A	277	I	ELECTROLUMINESCENT	UNIVERSAL	DIE CAST ALUMINUM EXIT SIGN, W/ ELECTROLUMINESCENT LAMP LIGHT SOURCE, GREEN LETTERS, ARROWS AND FACE, REFER TO DRAWING	

NUMBER OF LAMPS IN CROSS SECTION. PROVIDE WALL-TO-WALL FIXTURE WITH STRAIGHT EXTENSION AS REQUIRED. PROVIDE MATCHING SYLAVANIA QUICKTRONIC OR GE ULTRAMAX BALLASTS.	\bigcirc	\bigcirc	
	PROVIDE MATCHING SYLAVANIA QUICKTRONIC OR GE ULTRAMAX BALLASTS.	PROVIDE WALL-TO-WALL FIXTURE WITH STRAIGHT EXTENSION AS REQUIRED.	NUMBER OF LAMPS IN CROSS SECTION.

MISCELLANEOUS SYMBOLS FUSED 3 POLE DISCONNECT SWITCH. "30A" DENOTES SWITCH SIZE, "20A" DENOTES FUSE SIZE. -FUSED DISCONNECT SWITCH. 3 POLE, 30 AMP, UNLESS OTHERWISE NOTED DUPLEX RECEPTACLE — GROUNDING TYPE — MOUNTED AT 42" A.F.F. OR 6" ABOVE COUNTER TOP OR BACK SPLASH WHERE EXISTENT. DUPLEX RECEPTACLE — GROUNDING TYPE — MOUNTED 18" A.F.F. UNLESS OTHERWISE INDICATED. NUMERAL INDICATES CIRCUIT NUMBER. RECEPTACLE SYMBOLS IPLEX RECEPTACLE — GROUNDING TYPE — "GFI" INDICATES OUND FAULT INTERRUPTING TYPE — MOUNTED 42" A.F.F. OR 6" OVE COUNTER TOP OR BACK SPLASH WHERE EXISTENT.

LA-1,3,5

RACEWAY CONCEALED IN FLOOR SLAB. FLEXIBLE RACEWAY; SIZE AS REQUIRED.

RACEWAY CONCEALED IN CEILING OR WALLS, OR EXPOSED IN UNFINISHED AREAS.

<u>SYMBOL</u>

CONDUIT AND WIRE SYMBOLS

- UPLEX RECEPTACLE GROUNDING TYPE WITH SURGE SUPPRESSION ROTECTION MOUNTED AT 18" A.F.F. UNLESS OTHERWISE INDICATED.
- OUPLEX RECEPTACLE ISOLATED GROUND TYPE MOUNTED AT 8" A.F.F. UNLESS OTHERWISE INDICATED. IGLE RECEPTACLE — GROUNDING TYPE — MOUNTED AT 18" A.F.F. LESS OTHERWISE INDICATED.

 $\mathbb{X}^{\mathsf{J}}\left(\frac{30\mathsf{A}}{20\mathsf{A}}\right)$

SYMBOL 20A

SYMBOL

SYMBOL

SYMBOL

SYMBOL

SYMBOL

- DOUBLE DUPLEX RECEPTACLE GROUNDING TYPE MOUNTED AT 18" A.F.F. UNLESS OTHERWISE INDICATED.
- _OOR OUTLET BOX WITH DUPLEX RECEPTACLE; REFER TO PECIFICATIONS.
- FLOOR OUTLET BOX WITH DOUBLE DUPLEX RECEPTACLE; REFER TO SPECIFICATIONS. FLOOR OUTLET BOX WITH SINGLE RECEPTACLE; REFER TO SPECIFICATIONS.

- WIREMOLD WITH DUPLEX GROUNDING RECI IME CLOCK. REFER TO SPECIFICATIONS. CONTACTOR. REFER TO SPECIFICATIONS.
-)RIZED DAMPER.
- OGRAM OR DOOR BELL. SHBUTTON STATION.

ABBREVIATIONS

<u>GENERAL</u>

WP N.I.C. A.F.F. XP N.T.S. PIR ER WEATHERPROOF.

NOT IN CONTRACT.

ABOVE FINISHED FLOOR.

EXPLOSION PROOF.

NOT TO SCALE.

PASSIVE INFRARED.

EXISTING DEVICE SHALL REMAIN.

EXISTING DEVICE SHALL BE REMOVED.

EXISTING DEVICE SHALL BE RELOCATED AS DIRECTED BY ARROW ON PLANS.

SURFACE MOUNTED 277/480 VOLT PANELBOARD 6'-6" A.F.F. TO TOP. (FLUSH MOUNTED) JRFACE MOUNTED 120/208 VOLT PANELBOARD 6'-6" A.F.F. TO TOP. LUSH MOUNTED) GNETIC MOTOR STARTER. SHBUTTON CONTROL STATION, FUNCTION AS INDICATED ON PLAN. RFACE MOUNTED CONTROL PANEL 6'-6" A.F.F. TO TOP. (FLUSH MOUNTED) RGENCY POWER OFF MUSHROOM TYPE PUSHBUTTON PROVIDED WITH FULL MINUM GUARD, MOUNTED AT 54" A.F.F. UNLESS OTHERWISE NOTED. BINATION STARTER/NON-FUSED DISCONNECT SWITCH. 3 POLE, 30 AMP CH, WITH NEMA SIZE 1 STARTER UNLESS OTHERWISE NOTED. (WITH ED DISCONNECT SWITCH) POWER POLE; REFER TO SPECIFICATIONS AND DRAWINGS FOR RECEPTACLE CONFIGURATION. CEILING MOUNTED BOX WITH DUPLEX RECEPTACLE; REFER TO SPECIFICATIONS. SPECIAL PURPOSE RECEPTACLE — "A" INDICATES TYPE AS SHOWN ON DRAWINGS OR IN SPECIFICATIONS. ECIAL PURPOSE RECEPTACLE — FLOOR OUTLET BOX — "A" DICATES TYPE AS SHOWN ON DRAWINGS OR IN SPECIFICATIONS.

ALARM SYMBOLS

WALL WASHING LIGHTING FIXTURE; ARROW INDICATES AIMING. SEE FIXTURE SCHEDULE FOR MOUN

EXIT LIGHT CEILING MOUNTED WITH DIRECTIONAL ARROW AS INDICATED ON PLAN. (WALL MOUNTED WITHOUT ARROWS).

SURFACE MOUNTED STRIP FLUORESCENT LIGHTING FIXTURE, "A" DENOTES TYPE (REFER TO FIXTURE SCHEDULE), NUMERAL DENOTES CIRCUIT NUMBER, "b" DENOTES FIXTURE CONTROLLED BY SWITCH "b".
CEILING RECESSED OR SURFACE MOUNTED INCANDESCENT, COMP. FLUOR OR HID LIGHTING FIXTURE. "B"
DENOTES TYPE, NUMERAL DENOTES CIRCUIT NUMBER, AND "b" DENOTES FIXTURE CONTROLLED BY SWITCH
"b". (WALL MOUNTED).

CEILING OR WALL, SURFACE OR RECESSED MOUNTED FLUORESCENT LIGHTING FIXTURE; "A" DENOTES TYPE (REFER TO FIXTURE SCHEDULE), NUMERAL DENOTES CIRCUIT NUMBER, "b" DENOTES FIXTURE CONTROLLED BY SWITCH "b".

LIGHTING SYMBOLS

REMOTE EMERGENCY LIGHTHEAD. EMERGENCY BATTERY UNIT WITH REMOTE LIGHTHEADS AS INDICATED ON PLANS.

EMERGENCY BATTERY UNIT WITH UNIT MOUNTED LIGHTHEADS. NUMBER OF LIGHT

LIGHTING FIXTURE WIRED TO NIGHT OR EMERGENCY LIGHTING CIRCUIT.

ACK LIGHTING WITH QUANTITY OF LIGHTHEADS AS INDICATED ON PLANS.

SYMBOL 110cd FIRE ALARM HORN / STROBE COMBINATION MOUNT BOTTOM OF DEVICE AT 6'-8" A.F.F. OR 6" BELOW CEILING, WHICHEVER IS LOWER. "110cd" DENOTES STROBE CANDELA RATING. NO "cd" VALUE INDICATES PROVIDE "75cd" STROBE.

110cd FIRE ALARM STROBE ONLY. MOUNT BOTTOM OF DEVICE AT 6'—8" A.F.F. DR 6" BELOW CEILING, WHICHEVER IS LOWER. "110cd" DENOTES STROBE CANDELA RATING. NO "cd" VALUE INDICATES PROVIDE "75cd" STROBE.

FIRE ALARM MINI-HORN / STROBE COMBINATION MOUNT BOTTOM OF DEVICE 6'-8" A.F.F. OR 6" BELOW CEILING, WHICHEVER IS LOWER. FIRE ALARM HEAT DETECTOR, FIXED TEMPERATURE TYPE. "135" INDICATES TEMPERATURE SETTING. IRE ALARM HEAT DETECTOR, COMBINATION RATE OF RISE / FIXED

TRE ALARM SMOKE DETECTOR WITH AUXILIARY CONTACTS FOR CROSS ZONING (ELEV. LOBBY).

FIRE ALARM SMOKE DETECTOR WITH RELAY BASE. FIRE ALARM SMOKE DETECTOR; STAND ALONE TYPE (120V.).

FIRE ALARM SMOKE DETECTOR BEAM TYPE — RECEIVER UNIT REFER TOPLANS FOR MOUNTING HEIGHT.

DOOR HOLD OPEN DEVICE.

TAMPER SWITCH.

FLOW SWITCH.

REMOTE (LED) INDICATOR LIGHT. EXTERIOR STROBE LIGHT. PRESSURE SWITCH.

FIRE ALARM CONTROL PANEL.

FIRE ALARM ANNUNCIATOR PANEL. FIRE ALARM MASTER BOX. SEE SPECIFICATIONS FOR MOUNTING. FIRE ALARM KEY LOCK BOX.

COMMUNICATION AND SIGNAL SYMBOLS

DUCT SMOKE DETECTOR REMOTE INDICATOR/TEST STATION MOUNTED 6'-8" A.F.F. OR 6" BELOW FINISHED CEILING WHICHEVER IS LOWER.

E OUTLET MOUNTED 18" A.F.F.: PROVIDE 4" SQUARE BOX WITH SINGLE GANG PLASTER 3/4" CONDUIT STUBBED UP 6" ABOVE CEILING AT 90 DEGREE ANGLE, TERMINATE WITH JSHING. JACK AND CABLE-N.I.C.

INDICATES MOUNTED 54" A.F.F.
INDICATES PAY PHONE.
INDICATES MOUNTED 42" A.F.F. OR 6" ABOVE COUNTER.
ET MOUNTED 18" A.F.F.: PROVIDE 4" SQUARE BOX WITH SINGLE GANG PLASTER RING AND 3/4"
TUBBED UP 6" ABOVE CEILING AT 90 DEGREE ANGLE, TERMINATE WITH PLASTIC BUSHING.
CABLE—N.I.C. INDICATES MOUNTED 42" A.F.F. OR 6" ABOVE COUNTER.

COMBINATION DATA/TELEPHONE OUTLET MOUNTED 18" A.F.F.: PROVIDE 4" SQUARE BOX WITH SINGLE GANG PLASTER RING AND 3/4" CONDUIT STUBBED UP 6" ABOVE CEILING AT 90 DEGREE ANGLE, TERMINATE WITH PLASTIC BUSHING. JACK AND CABLE—N.I.C.

INDICATES MOUNTED 42" A.F.F. OR 6" ABOVE COUNTER.

FLOOR OUTLET BOX WITH TELEPHONE OUTLET; REFER TO SPECIFICATIONS.

FLOOR OUTLET BOX WITH DATA OUTLET; REFER TO SPECIFICATIONS.

FLOOR MOUNTED CABLE TELEVISION OUTLET.

CABLE TELEVISION OUTLET MOUNTED AT 18" A.F.F. UNLESS OTHERWISE NOTED. CABLE TEL
CLOCK HA
DATA AND
TECHNOLO

SWITCHING DESIGNATIONS

WBO THREE WAY SWITCH MOUNTED 4'-0" A.F.F.

FOUR WAY SWITCH MOUNTED 4'-0" A.F.F.

DIMMER SWITCH MOUNTED 4'-0" A.F.F.

SINGLE POLE SWITCH - KEY OPERATED - MOUNTED 4'-0" A.F.F.

SINGLE POLE SWITCH AND PILOT LIGHT MOUNTED 4'-0" A.F.F.

MOTOR RATED SWITCH WITH THERMAL OVERLOAD PROTECTION.

VARIABLE SPEED FAN SWITCH MOUNTED AT 4'-0" A.F.F.

TIME SWITCH MOUNTED 4'-0" A.F.F.

LOW VOLTAGE SWITCH 4'-0" A.F.F.

MOMENTARY CONTACT SWITCH MOUNTED 4'-0" A.F.F.

PHOTOCELL CONTROL DEVICE JLTRASONIC OCCUPANCY SENSOR; "W" INDICATES MOUNTING HEIGHT OF 4'-0" A.F.F.

NFRA-RED OCCUPANCY SENSOR; "W" INDICATES MOUNTING HEIGHT OF 4'-0" A.F.F. PAYLIGHT SENSOR; "W" INDICATES MOUNTING HEIGHT OF $\iota^*{-}0$ " A.F.F.

SOUND SYMBOLS

UNIVERSITY OF
SOUTHERN MAINE
70 FALMOUTH STREET

RESEARCH WING PHASE III FIT-OUT

DUAL TECHNOLOGY OCCUPANCY SENSOR; "W" INDICATES MOUNTING HEIGHT OF 4'-0" A.F.F.

CEILING MOUNTED SPEAKER.

SPEAKER; FLUSH WALL MOUNTED.

LOUDSPEAKER; SURFACE WALL MOUNTED.

MICROPHONE OUTLET. "W" INDICATES WALL MOUNTED.

AMPLIFIER OMBINATION CLOCK/SPEAKER UNIT, FLUSH WALL MOUNTED

SECURITY SYMBOLS

LEGEND AN FIXTURE SCHEDULE

AND

SYMBOL

SECURITY MOTION DETECTOR (CEILING MOUNTED RADIAL TYPE). SECURITY MOTION DETECTOR (WALL MOUNTED DIRECTIONAL TYPE).

AWN BY
ECKED BY
J. ARCH. / EN

NONE

CARD KEY ACCESS READER.

DOOR LOCK (ELECTRIC STRIKE).

SIREN.

CLOSED CIRCUIT TV CAMERA

NOTE: ALL SYMBOLS ON THIS LIST ARE NOT NECESSARILY USED ON THIS JOB.

1000 Massachusetts Avenue Cambridge, Massachusetts 02138 617.547.5400 Fax 617.354.5758

NOTED.