PARTITION PRIORITY LEGEND		
FIRE & SMOKE	HIGHEST	2-HOUR FIRE WALL 2-HOUR FIRE BARRIER AT EXIT ENCLOSURE 2-HOUR FIRE BARRIER 1-HOUR FIRE BARRIER AT EXIT ENCLOSURE 1-HOUR FIRE BARRIER SMOKE PARTITION
	LOWEST	NON-RATED PARTITION OR FURRING
SOUND CLASS	HIGHEST	STC >= 60
		60 > STC > 50
	LOWEST	NO STC

ALL COMPONENTS OF THE HIGHER PRIORITY PARTITION ASSEMBLY MUST CONTINUE UNINTERRUPTED PAST THE LOWER PRIORITY PARTITION ASSEMBLY.

SEE SHEET A00x FOR FIRE, SMOKE AND STC VALUES OF PARTITION ASSEMBLIES.

NOTE:
SEE SPECIFIC PLAN DETAILS FOR INTERSECTIONS OF FIRE WALLS WITH EXTERIOR WALL SYSTEMS.

WOOD STUD PARTITION FULL HEIGHT	W4A
	W6A

WOOD FURRING
EXTEND GWB 3" ABOVE FIN. CLG. U.N.O.

NOTE:
MINIMUM CLEAR DIMENSIONS MAY NOT BE REDUCED. ADJUST HINGE SIDE DIMENSIONS AS NEEDED TO MAINTAIN CLEAR DIMENSIONS INDICATED.

PDT ARCHITECTS

49 DARTMOUTH STREET
PORTLAND, MAINE
04101
207-775-1059
www.pdtarchs.com

Date: 01/08/18

COPYRIGHT
PDT Architects
Reuse or reproduction of the contents of this document is not permitted without written permission of PDT Architects.

USM - ADA Upgrades
120 Bedford St. Portland, ME 04101

No.	Date	Description
Revision Schedule		

LICENSED ARCHITECT BRIAN K. CHECK STATE OF MAINE

JOB NO. 080316

DRWN. CHK
Checker

SCALE:

ISSUE
11/17/17

TITLE
Typical Assemblies

SHEET
A004