988933 ermit # ____ City of_

BUILDING PERMIT APPLICATION Fee_____

Zone_

115-0-018 _Map #____Lot# _

Please fill out any part which applies to job. Proper plans must accompany form.

The state of the s	
Owner: Phone #	For Official Use Only
Address:	Subdivision
LOCATION OF CONSTRUCTION	Date Name Name 1.15
Contractor: Sub.:	Ownership: Public Frivate
Address:Phone #	Bldg Code Ownership: Public Frivate Frivate
Est. Construction Cost: Proposed Use:	Zoning:
Past Use:	Street Frontage Provided: Provided Setbacks: Front Back Side Side
# of Existing Res. Units # of New Res. Units	Provided Setbacks: Front Back Side Side Review Required:
Building Dimensions LW Total Sq. Ft	Planning Board Approval: Yes No Date:
# Stories: # Bedrooms Lot Size:	Conditional Use: Variance Site Plan Subdivision
Is Proposed Use: Seasonal Condominium Conversion	Shoreland Zoning Yes No Floodplain Yes No
	Special ExceptionOther (Explain)
Explain Conversion	Other (Explain)
	Coiling
Foundation:	1. Ceiling Joists Size: HISTORIC PRODUCTION OF THE PRODUCTION OF T
1 There of Cail.	2. Ceiling Strapping Size Spacing Not in District not
2. Set Backs - Front	3. Type Ceilings: 4. Insulation Type Size 5. Ceiling Height:
3. Footings Size:	4 Tarantakian Trans
4. Foundation Size:	5. Ceiling Height:
5. Other	Roof:
Floor:	2. Sheathing Type Size
1. Sills Size: Sills must be anchored.	3. Roof Covering Type
2. Girder Size:	
3. Lally Column Spacing: Size:	Type: Number of Fire Places
4. Joists Size: Spacing 16" O.C.	Heating:
5. Bridging Type: Size: Size:	Type of Heat:
6. Floor Sheathing Type: Size:	Electrical:
7. Other Material:	Service Entrance Size: Smoke Detector Required Yes No
	Plumbing:
Exterior Walls:	1. Approval of soil test if required Yes No
1. Studding Size Spacing	2. No. of Tubs or Showers
2. No. windows	3. No. of Flushes
3. No. Doors	4. No. of Lavatories
4. Header Sizes Span(s)	5. No. of Other Fixtures
5. Bracing: Yes No.	Swimming Pools:
6. Corner Posts Size	1. Type:
7. Insulation Type Size	2. Pool Size: x Square Footage
8. Sheathing Type Size	3. Must conform to National Electrical Code and State Law.
9. Siding Type Weather Exposure	- D
10. Masonry Materials	remunecasta by
11. Metal Materials	3. Must conform to National Electrical Code and State Law. Pernance of Applicant VITH REQUIREMENTS. CEO's District
Interior Walls:	Date Date
1. Studding Size Spacing	
2. Header Sizes Span(s)	CEO's District
o. Wair Covering Type	
4. Fire Wall if required	CONTINUED TO DEVEDEE CIDE
5. Other Materials	CONTINUED TO REVERSE SIDE

White - Tax Assessor

Ivory Tag - CEO

PLOT PLAN		•			N
Base Fee \$ Subdivision Fee \$ Site Plan Review Fee \$ Other Fees \$	down From Front)		Inspect Son A : powed on whi	tion Record	Date 7
COMMENTS					
I hereby certify that I am the owner of recorowner to make this application as has authapplication is issued, I certify that the code reasonable hour to enforce the provisions	orized agent and I agree to c e official or the code official's	onform to all applicable laws authorized representative sh	OTTHIS JURISUICTION. III auc	muun, napenni	TOT MADILY DESCRIBED IN UN
SIGNATURE OF APPLICANT		Sebasco, Me	04565	389-/6 PHONE NO.	23

BUILDING PERMIT REPORT

ADDRESS: 35 Washburn BUR DATE: 21 /July/9
REASON, FOR PERMIT: TO CONSTRUCT Addition For
1/2 bath.
BUILDING OWNER: DAVID AUIT
CONTRACTOR: DAUR Johnson
PERMIT APPLICANT:
APPROVED: X/2

CONDITION OF APPROVAL:

- 1.) Before concrete for foundation is placed, approvals from Public Works and Inspection Services must be obtained.
 - 2.) Precaution must be taken to protect concrete from freezing.
 - 3.) All vertical openings shall be enclosed with construction having a fire rating of at least one(1) hour, including fire doors with selfclosers.
 - 4.) Each apartment shall have access to two(2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units.
 - 5.) The boiler shall be protected by enclosing with one(1) hour fire rated construction including fire doors and ceiling, or by providing automatic extinguishment. Sprinkler piping serving not more than six sprinklers may be connected to a domestic water supply system having a capacity sufficient to provide 0.15 gallons per minute, per square foot of floor throughout the entire area. An INDICATING shut-off valve shall be installed in an accessable location between the sprinkler and the connection to the domestic water supply. Minimum pipe size shall be 3/4 inch copper or 1 inch steel. Maximum coverage area of a residential sprinkler is 144 square feet per sprinkler.
 - 6.) Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside opening without the use of separate tools. Where windows are provided as a means of egress or rescue, they shall have a sill height not more than 44 inches (1118 mm) above the floor. All egress or rescue windows from sleeping rooms must have minimum net clear openings of 5.7 square feet (0.53m²). The minimum net clear opening height dimension shall be 24 inches (610 mm). The minimum net clear opening width dimension shall be 20 inches (508 mm).
 - 7.) All single and multiple-station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the building code (BOCA National Building Code 1990, and N.F.P.A. 74).

- 8.) Private garages located beneath rooms in buildings of Use Groups R-1, R-2, R-3 or I-1 shall have walls, partitions, floors and ceilings separating the garage space from the adjacent interior spaces constructed of not less than 1-hour fireresistance rating. Attached private garages shall be completely separated from the adjacent interior spaces and the attic area by means of 1/2-inch gypsum board or equivalent applied to the garage side. The sills of all door openings between the garage and adjacent interior spaces shall be raised not less than 4 inches (102 mm) above the garage floor. The door opening protectives shall be 1 3/4-inch solid core wood doors or approved equivalent.
- 9.) A guardrail system located near the open side of deck or elevated walking surfaces shall be constructed. Guards in buildings of Use Group R-3 shall be not less than 36 inches in height. Open guards shall have intermediate rails, balusters or other construction such that a sphere with a diameter of 4 inches cannot pass through any opening. Handrails on stairs shall be no less than 34 inches nor more than 38 inches. Handrails within individual dwelling units shall not be less than 30 inches nor more than 38 inches.
- 10.) Section 25-135 of the Municipal Code for the City of Portland states: "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year.
- 11.) The builder of a facility to which Section 4594-C of the Maine State Human Rights Act, Title 5 M.R.S.A. refers, shall obtain a certification from a design professional that the plans of the facility meet the standards of construction required by this section. Prior to commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services.

Sincerely,

P. Namuel Hoffses

Chief of Inspection Services

/e1 11/16/88 11/27/90

8/14/91

*12PLumbing Permit must be obtained,

3	XIO Raffers W	Roll Alyman	ed Rooting	Jove Ault 35 Washburn Butland Mc	Ave
1211 1211 1211 1211 1211 1211 1211 121	Vent				
tucia d	R 19				
Claybourds V. Elyman	axe studs	1 8A+	h Aldricon		
	- Poly Varon				
	3×10 9m				
	3 6 4591	古	on Inlatin		