

**City of Portland, Maine – Building or Use Permit Application** 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716

Location of Construction: 19 William St		Owner: Whicher, Robert		Phone: 776-6587		Permit No: <b>940755</b>	
Owner Address: 344		Leasee/Buyer's Name:		Phone:		Business Name: Mary Gresik	
Contractor Name: Ray Desroberts		Address:		Phone:		Permit Issued: JUL 26 1994 CITY OF PORTLAND	
Past Use: 3-1am		Proposed Use: 3-1am w/replaced decks		COST OF WORK: \$ 1,000.		PERMIT FEE: \$ 25.00	
				FIRE DEPT. <input type="checkbox"/> Approved <input type="checkbox"/> Denied		INSPECTION: Use Group: A-2 Type: B	
				Signature:		Signature: <i>[Signature]</i>	
Proposed Project Description:  Replace deck (Not to exceed existing footprint)				PEDESTRIAN ACTIVITIES DISTRICT (P.U.D.)			
				Action: <input type="checkbox"/> Approved <input type="checkbox"/> Approved with Conditions <input type="checkbox"/> Denied			
				Signature:		Date:	

Zone: CBL: 116-A-010

Zoning Approval: *[Signature]*

**Special Zone or Reviews:**

Shoreland  
 Wetland  
 Flood Zone  
 Subdivision  
 Site Plan maj  minor  mm

**Zoning Appeal**

Variance  
 Miscellaneous  
 Conditional Use  
 Interpretation  
 Approved  
 Denied

**Historic Preservation**

Not in District or Landmark  
 Does Not Require Review  
 Requires Review

Action:

Approved  
 Approved with Conditions  
 Denied

Date: 7/26/94

**PERMIT ISSUED WITH REQUIREMENTS**

**CERTIFICATION**

I hereby certify that I am the owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his authorized agent and I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in the application issued, I certify that the code official's authorized representative shall have the authority to enter all areas covered by such permit at any reasonable hour to enforce the provisions of the code(s) applicable to such permit

*Robert E. Whicher*  
 SIGNATURE OF APPLICANT Robert Whicher ADDRESS: DATE: 18 July 1994 PHONE:

RESPONSIBLE PERSON IN CHARGE OF WORK, TITLE PHONE:

CEO DISTRICT



BUILDING PERMIT REPORT

Address 19 William ST Date 21/July/94

Reason for Permit To replace deck

Bldg. Owner: R. Whicker

Contractor: RAY DESROBERTS

Permit Applicant: 1 1

Approval: \_\_\_\_\_

CONDITION OF APPROVAL:

1. Before concrete for foundation is placed, approvals from Public Works and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection).
2. Precaution must be taken to protect concrete from freezing.
3. It is strongly recommended that a register land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.
4. All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hr., including fire doors with selfclosers.
5. Each apartment shall have access to (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units.
6. The boiler shall be protected by enclosing with one (1) hour fire rated construction including fire doors and ceiling, or by providing automatic extinguishment. Sprinkler piping serving not more than six sprinklers may be connected to a domestic water supply system having a capacity sufficient to provide 0.15 gallons per minute, per square foot of floor throughout the entire area. An INDICATING shut-off valve shall be installed in an accessible locations between the sprinkler and the connection to the domestic water supply. Minimum pipe size shall be 3/4 inch copper or 1 inch steel. Maximum coverage area of a residential sprinkler is 144 square feet per sprinkler.
7. Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside opening without the use of special knowledge or separate tools. Where windows are provided as a means of egress or rescue, they shall have a sill height not more than 44 inches (1118 mm) above the floor. All egress or rescue windows from sleeping room must have minimum net clear opening height dimension shall be 24 inches (610 mm). The minimum net clear opening width dimension shall be 20 inches (508 mm), and a minimum net clear opening of 5.7 sq.ft.

8. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the building code 919.3.2 (BOCA National Building Code 1993), and NFPA 101 Chapter 18 & 19. (smoke detectors shall be installed and maintained at the following locations):

1. In the immediate vicinity of bedrooms
2. In all bedrooms
3. In each story within a dwelling unit, including basements

9. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by Fire Partitions and floor/ceiling assembly ;lies which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of 1/2 inch gypsum board or the equivalent applied to the garage side. (Chapter 4 section 407.0 of the BOCA/1993).

X 10. Guardrails & Handrails - A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Group 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I1, I-2 M and R and public garages and open parking structures, guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect.

11. All exit signs, lights and means of egress lighting shall be done in accordance with Chapter 10, section & subsections 1023.& 1024.0 of the City's building code (The BOCA National Building Code/1993).

12. Stair construction in Use Group R-3, R-4 is a minimum of 9" tread and 8-1/4" maximum rise.


13. Headroom in habitable space is a minimum of 7'6".

14. The minimum headroom in all parts of a stairway shall not be less than 80 inches.

15. All construction and demolition debris must be disposed at the City's authorized reclamation site. The fee rate is attached. Proof of such disposal must be furnished to the office of Inspection Services before final certificate or occupancy is issued or demolition permit is granted.

16. Section 25-135 of the Municipal Code for the City of Portland states: "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".

17. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act, Title 5 MRSA refers, shall obtain a certification from a design professional that the plans of the facility meet the standards of construction required by this section. Prior to commencing construction of the facility, the builder shall submit certification to the Division of Inspection Services.

  
P. Samuel Hoffses  
Chief of Inspections

18. Means of egress must be maintained  
Thru construction

/dmm 01/14/94(redo w/additions)

L.T. MacDougall P.F.D.

please check off the appropriate description

existing to STAY

FOUNDATION \_\_\_\_\_ Frost Wall, min 4" below grade. 8" thick

\_\_\_\_\_ Sono Tube, 4" below grade. 6" min. on footing, hard pan or bedrock.

\_\_\_\_\_ Other

SILL \_\_\_\_\_ Size

SPAN OF SILL \_\_\_\_\_ Distance between foundation supports

JOISTS SPAN \_\_\_\_\_

JOISTS SIZE \_\_\_\_\_ 2 x 6  2 x 8 \_\_\_\_\_ 2 x 10

DISTANCE BETWEEN JOISTS ..... 16" O.C. ..... 24" O.C. ..... other


DECKING  5/4 \_\_\_\_\_ other explain

GUARD HEIGHT \_\_\_\_\_ 32" \_\_\_\_\_ 36"  42"

DISTANCE BETWEEN BALUSTER  4" spacing between


STAIR CONSTRUCTION minimum 9" tread maximum 8 1/4" rise

please use space below for drawing of deck with measurements.



Replace/Repair existing (2) Porches with new 5/4 Pressure treated. Repair/Replace Joists As Req.

second floor deck ~~to~~ tongue & groove spruce



Replace Baluster to meet 4" max spacing