



SCALE: 1/4" = 1'-0"
 1 DRAINAGE AND VENT FLOOR PLAN
 P-2 PLUMBING

GENERAL NOTES:

1. FIELD VERIFY ALL DIMENSIONS AND EXISTING CONDITIONS PRIOR TO PROCEEDING WITH ANY WORK. WHERE DISCREPANCIES OCCUR BETWEEN THESE DOCUMENTS AND EXISTING CONDITIONS, THE DISCREPANCY SHALL BE REPORTED TO THE OWNER AND ENGINEER FOR RESOLUTION.
2. SEE ARCHITECTURAL DRAWINGS FOR CONTRACT LIMITS AND ANY CONSTRUCTION PHASING, SCHEDULE ALL SHUTDOWNS THAT AFFECT UTILITIES AND PORTIONS OF THE BUILDING THAT MUST REMAIN IN OPERATION WITH THE OWNER.
3. REFER TO ARCHITECTURAL DRAWINGS FOR EXACT MOUNTING HEIGHTS OF FIXTURES, OUTLETS, SOFFITS, CEILING AND EQUIPMENT.
4. SAW CUT CONCRETE FLOOR AS REQUIRED TO FACILITATE INSTALLATION OF UNDERSLAB UTILITIES.
5. PROVIDE EXPANSION JOINTS, FLEXIBLE PIPE CONNECTORS OR FLEXIBLE HOSE CONNECTORS AS REQUIRED AT EXPANSION JOINTS.
6. ISOLATE, DRAIN AND REFILL EXISTING SYSTEMS AS REQUIRED TO ACCOMMODATE BOTH THE NEW SYSTEM AND THE CONTINUED USE OF THE EXISTING SYSTEM. ALL NEW PIPING SYSTEMS SHALL BE FLUSHED, TESTED AND CLEANED PRIOR TO INITIAL OPERATION. REFER TO SPECIFICATION.
7. PROVIDE ALL NECESSARY TEMPORARY OR PERMANENT CAPS OR PLUGS FOR PIPING. DO NOT LEAVE PIPING OPEN ENDED.
8. PROVIDE PIPING SUPPORTS FOR ALL NEW PIPING. REFER TO DETAILS, SCHEDULES AND SPECIFICATIONS.
9. PROVIDE EQUIPMENT CONNECTION TRANSITIONS IN PIPING AS REQUIRED.
10. PRIOR TO STARTING CONSTRUCTION, DETERMINE EXACT INVERT ELEVATIONS, SIZES, DEPTH AND LOCATION OF EXISTING UTILITIES WHERE TERMINATIONS OR CONNECTIONS ARE TO BE MADE OR INTERSECTIONS OCCUR. NOTIFY ENGINEER OR OWNER OF ANY DISCREPANCY BETWEEN DRAWINGS AND ACTUAL FIELD CONDITIONS. WORK BACK TOWARD FIXTURE FROM UTILITY CONNECTION FOR ALL PIPING SYSTEMS.
11. LOCATE ACCESS PANELS IN NON-ACCESSIBLE CEILING AND WALLS FOR ALL VALVES, SHOCK ABSORBERS, CLEANOUTS AND ALL OTHER ITEMS THAT REQUIRE ACCESS TO PROPERLY MAINTAIN OR SERVICE THE BUILDING.
12. PROVIDE CLEANOUTS AT THE BASE OF ALL SANITARY DRAINAGE STACKS AND RAIN WATER CONDUCTORS.
13. ALL EXISTING SINKS THAT ARE TO REMAIN OR BE RELOCATED SHALL HAVE WRISTBLADE HANDLE FAUCETS INSTALLED IF NOT ALREADY FURNISHED.

SHEET NOTES:

- ① ROUTE OXYGEN VENT PIPING UP THRU ROOF/OUT SIDEWALL AS INDICATED ON PLAN. PROVIDE GOOSENECKS AND WIRE MESH SCREEN ON END OF PIPE. REFER TO DETAIL ON P-4.
- ② -NOTE DELETED-
- ③ PLUMBING CONTRACTOR SHALL PROVIDE NEW LAVATORY, FAUCET, VALVES, SEALS, TRAP, FITTINGS AND ASSOCIATED PIPING TO REPLACE EXISTING SHOWER. PROVIDE NEW ROUGH-IN AND ALL FINAL CONNECTIONS TO EXISTING PIPING AS REQUIRED TO PROVIDE A COMPLETE SYSTEM.

RestorixHealth
 Excellence in Wound Care

DENNIS NOSKIN ARCHITECTS
 1000 BROADWAY, SUITE 200
 PORTLAND, ME 04103

Z&F CONSULTING
 MECHANICAL, ELECTRICAL, PLUMBING
 FIRE PROTECTION
 1000 BROADWAY, SUITE 200
 PORTLAND, ME 04103
 PHONE: 603.633.2000
 WWW.ZANDF.COM

JOHN ZABLOWICZ, P.E.
 PROFESSIONAL ENGINEER
 LICENSE NO.: 13062

STATE: MAINE
JOHN ZABLOWICZ, P.E.
 PROFESSIONAL ENGINEER
 LICENSE NO.: 13062

PROJECT:
MAINE MEDICAL CENTER
 BRIGHTON CAMPUS
WOUND CARE AND
HYPERBARIC MEDICINE
 333 BRIGHTON AVENUE
 PORTLAND, ME 04103

KEY PLAN: GROUND FLOOR

ISSUE DATES:

▲ JANUARY 26, 2015	STATE APPROVALS
▲ MARCH 20, 2015	BLDG. DEPT. REVIEW
▲	
▲	
▲	
▲	

DRAWN BY:	ECH
CHECKED BY:	BF
SCALE:	AS NOTED
PROJECT NO.:	P14110

SHEET TITLE:
 PLUMBING
 DRAINAGE AND VENT
 FLOOR PLAN

DRAWING NO.:

P-2

©2014