City of Portland, Maine 389 Congress Street, 04101	e - Building or Use I Tel: (207) 874-8703,	Permit Applicatio Fax: (207) 874-87	01.0406	Sec. A sec.	CBL: 123 F01	3001	
Location of Construction: Owner Name:			Owner Address: Phone:				
288 Woodford St	Daj Inc		Po Box 6577 Scarborough, Me. C 070 207-883-3770				
Business Name:	Contractor Name:		Contractor Address				
n/a	no contractor/self		n/a n/a				
Lessee/Buyer's Name	Phone:		Permit Type: Zone:				
n/a	n/a		Alterations - Co	mmercial		RS	
				Cost of Work:	CEO District:	1 4220	
Past Use:	Proposed Use:		Permit Fee:	/ \$800.00		4385	
6 Unit Apartment Building	Same / Replacing existing 20' x 7' decks on 2nd floor & 3rd floor.		THEREOFICAL				
		K per met lofie	he	Approved	PERMIT RSUED WELLBERMENTS	Type: 5 <i>B</i>	
Proposed Project Description:] s	I MUST SO	7 JL +	40	
Replace two 20' x 7 decks.			Signature:	CIVITIES DISTRIC	Tarmey !		
			PEDESTRIAN AC	TIVITIES DISTRIC	T (P.A.D.)		
			Action: Appr	oved Approve		Denied	
		Signature: Date:					
Permit Taken By:	Date Applied For: 05/07/2001		Zonin	g Approval			
		Special Zone or Rev	views Zoning Appeal		Historic Preservation		
1. This permit application does not preclude the Applicant(s) from meeting applicable State and Federal Rules.		Shoreland	_	☐ Variance ☐ Mot in District		t or Landmarl	
2. Building permits do not include plumbing, septic or electrical work.		☐ Wetland	☐ Misce	☐ Miscellaneous		Does Not Require Review	
3. Building permits are vo within six (6) months of	id if work is not started	☐ Flood Zone ☐ Conditional Use ☐		Requires Rev	riew		
False information may i permit and stop all work	nvalidate a building	Subdivision W Interpretation		retation	Approved		
		Site Plan	his - Appro	oved	Approved w/	Conditions	
		Maj Minor M	M Denie	d	☐ Denied	2	
		Date: 5	Date:		Date:		
			1991		PERMITISSI WITH REQUIRE	JED MENTS	
		CERTIFICAT	ΓΙΟΝ				
I hereby certify that I am the I have been authorized by the jurisdiction. In addition, if a shall have the authority to en such permit.	e owner to make this apple permit for work describe	lication as his authorized in the application is	zed agent and I agrees issued, I certify the	ee to conform to a at the code official	all applicable laws al's authorized repr	of this resentative	
SIGNATURE OF APPLICANT		ADDR	ESS	DATE	PHC	ONE	

THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

All Purpose Building Permit Application

If you or the property owner owes real estate or personal property taxes or user charges on any property within the City, payment arrangements must be made before permits of any kind are accepted.

Location/Address of Construction: 288 Woodfords ST.
Total Square Footage of Proposed Structure Square Footage of Lot SAme
Tax Assessor's Chart, Block & Lot Number Chart#123 Block# F Lot#013 Owner: Jeffre J Odely 883-3770
Lessee/Buyer's Name (If Applicable) Owner's/Purchaser/Lessee Address: Owner's/Purcha
Current use: 6 Unit APT. Oldg
If the location is currently vacant, what was prior use: Approximately how long has it been vacant:
Proposed use: SAME
Project description: Replace existing Deck on 2 nd +3 Rd F
Contractor's Name, Address & Telephone: Teff Oldy 883-3710 Applicants Name, Address & Telephone: SCARboro John We 04070
Applicants Name, Address & Telephone:
Who should we contact when the permit is ready: Jeff Oldy or bobbie Telephone: 653 6427
If you would like the permit mailed, what mailing address should we use DEPT. OF EUROPECTION CALL Rec'd By:
1 2001

THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

PLOT PLAN INCLUDES THE FOLLOWING:

- The shape and dimension of the lot, all existing buildings (if any), the proposed structure and the distance from the actual property lines. Structures include decks porches; a bow windows cantilever sections and roof overhangs, as well as, sheds, pools, garages and any other accessory structures.
- Scale and North arrow; Zoning District & Setbacks
- First Floor sill elevation (based on mean sea level datum);
- Location and dimensions of parking areas and driveways;
- Location and size of both existing utilities in the street and the proposed utilities serving the building;
- Location of areas on the site that will be used to dispose of surface water.
- Existing and proposed grade contours

A COMPLETE SET OF CONSTRUCTION DRAWINGS INCLUDES THE FOLLOWING:

- Cross Sections w/Framing details (including porches, decks w/ railings, and accessory structures)
- Floor Plans & Elevations
- Window and door schedules
- Foundation plans with required drainage and damp proofing

 Electrical and plumbing layout. Mechanical drawings for any specialized equipment such as furnaces, chimneys, gas equipment, HVAC equipment (air handling) or other types of work that may require special review must be included.

SEPARATE PERMITS ARE REQUIRED FOR INTERNAL & EXTERNAL PLUMBING, HVAC AND ELECTRICAL INSTALLATIONS

- All construction must be conducted in compliance with the 1999 B.O.C.A. Building Code as amended by Section 6-Art II.
- All plumbing must be conducted in compliance with the State of Maine Plumbing Code.
- All Electrical Installation must comply with the 1999 National Electrical Code as amended by Section 6-Art III.
- HVAC (Heating, Ventilation and Air Conditioning) installation must comply with the 1993 BOCA Mechanical Code.

Minor/Minor Site Review Fee for New Single Family homes: \$300.00/Building Permit Fee: \$30.00 for the 1st \$1000.cost plus \$6.00 per \$1,000.00 construction cost thereafter.

ONE SET OF SUBMISSIONS INCLUDING CONSTRUCTION AND SITE PLAN DRAWINGS MUST BE SUBMITTED ON PAPER NO LARGER THAN 11" x 17" BEFORE ANY BUILDING PERMIT WILL BE ISSUED

Certification

I hereby certify that I am the Owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his/her authorized agent. I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in this application is issued, I certify that the Code Official's authorized representative shall have the authority to enter all areas covered by this permit at any reasonable hour to enforce the provisions of the codes applicable to this permit.

Signature of applicant:	1. Mans 1. C	Osh	Date: 5	17/01	
	Je production of the second			, , , , , , , , , , , , , , , , , , , ,	

BUILDING PERMIT REPORT

DATE: 9MAY 260/ ADDRESS: 288 Wood Ford STreet CBL: 123- F- \$13 REASON FOR PERMIT: To replace existing 7x20' decks on 2nds' 3nds/				
REASON FOR PERMIT: To replace existing 7x20 decks on 2nds 3rgs/				
BUILDING OWNER: Daj Inc.				
PERMIT APPLICANT: /CONTRACTOR SAO				
USE GROUP: R-2 CONSTRUCTION TYPE: 50 CONSTRUCTION COST: 800.00 PERMIT FEES! \$6.00				
The City's Adopted Building Code (The BOCA National Building Code/1999 with City Amendments) The City's Adopted Mechanical Code (The BOCA National Mechanical Code/1993)				
COMPTTONICS OF LINES OF LA				

CONDITION(S) OF APPROVAL

This permit is being issued with the understanding that the following conditions shall be met: 43.18.19	/ *//	*30,*33,*36 #32
		59

1. This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.

 Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection) "<u>ALL LOT LINES SHALL BE CLEARLY MARKED BEFORE CALLING."</u>

- 3. Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor elevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6" of the same material. Section 1813.5.2
- 4. Foundations anchors shall be a minimum of ½" in diameter, 7" into the foundation wall, minimum of 12" from corners of foundation and a maximum 6' O.C. between bolts. Section 2305.17
- 5. Waterproofing and dampproofing shall be done in accordance with Section 1813.0 of the building code.
- 6. Precaution must be taken to protect concrete and masonry. Concrete Sections 1908.9-19.8.10/ Masonry Sections 2111.3-2111.4.
- 7. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.
- 8. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than I-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4, Section 407.0 of the BOCA/1999)
- 9. All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993). Chapter 12 & NFPA 211
- 10. Sound transmission control in residential building shall be done in accordance with Chapter 12, Section 1214.0 of the City's Building Code.
- 11. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42". In occupancies in Use Group A, B.H-4, I-1, I-2, M, R, public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. Handrails shall be a minimum of 34" but not more than 38". Exception: Handrails that form part of a guard shall have a height not less than 36 inches (914 mm) and not more than 42 inches (1067 mm). Handrail grip size shall have a circular cross section with an outside diameter of at least 1 ½" and not greater than 2". (Sections 1021 & 1022.0). Handrails shall be on both sides of stairway. (Section 1014 7)
 - 12. Headroom in habitable space is a minimum of 7'6". (Section 1204.0)
 - 13) Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 1/4" maximum rise. All other Use Group minimum 11" tread, 7" maximum rise. (Section 1014.0)
 - 14. The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8") 1014.4
 - 15. The Minimum required width of a corridor shall be determined by the most restrictive of the criteria under section 1011.3 but not less then 36".
 - 16. Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508)mm, and a minimum net clear opening of 5.7 sq. ft. (Section 1010.4)
 - 17. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units. (Section 1010.1)
 - (18.) All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self closure's. (Over 3 stories in height requirements for fire rating is two (2) hours. (Section 710.0)
 - The boiler shall be protected by enclosing with (1) hour fire rated construction including fire doors and ceiling, or by providing automatic extinguishment. (Table 302.1.1)

- 20. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1999), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):
 - In the immediate vicinity of bedrooms
 - In all bedrooms
 - In each story within a dwelling unit, including basements
- 21. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. (Section 921.0)
- 22. The Fire Alarm System shall be installed and maintained to NFPA #72 Standard.
- 23. The Sprinkler System shall be installed and maintained to NFPA #13 Standard.
- All exit signs, lights and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023.0 & 1024.0 of the City's Building Code. (The BOCA National Building Code/1999)
- 25. Section 25 135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
- 26. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification the Division of Inspection Services.
- 27. Ventilation and access shall meet the requirements of Chapter 12 Sections 1210.0 and 1211.0 of the City's Building Code. (Crawl spaces & attics).
- 28. All electrical, plumbing and HVAC permits must be obtained by Master Licensed holders of their trade. No closing in of walls until all electrical (min. 72 hours notice) and plumbing inspections have been done.
- 29. All requirements must be met before a final Certificate of Occupancy is issued.
- / 30. All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code (The BOCA National Building Code/1996).
- 21. Ventilation of spaces within a building shall be done in accordance with the City's Mechanical code (The BOCA National Mechanical Code/1993). (Chapter M-16)

 32. Please read and implement the attached Land Use Zoning report requirements.
- 33. Boring, cutting and notching shall be done in accordance with Sections 2305.3, 2305.3.1, 2305.4.4 and 2305.5.1 of the City's Building Code.

34. Bridging shall comply with Section 2305.16.

35. Glass and glazing shall meet the requirements of Chapter 24 of the building code. (Safety Glazing Section 2406.0)

\$\alpha 36. All flashing shall comply with Section 1406.3.10.

37. All signage shall be done in accordance with Section 3102.0 signs of the City's Building Code, (The BOCA National Building Code/1999).

o lo remain	6 mis - No morebse	in Menumber of units is.
permitted.		
	<u> </u>	

Hotises, Building Inspector
LL McDougall, PFD

Marge Schmuckal, Zoning Administrator
Michael Nugent, Inspection Service Manager

PSH 10/1/00

**This permit is herewith issued, on the basis of plans submitted and conditions placed on these plans, any deviations shall require a separate approval.

***THIS PERMIT HAS BEEN ISSUED WITH THE UNDERSTANDING THAT ALL THE CONDITIONS OF THE APPROVAL SHALL BE COMPLETED. THEREFORE, BEFORE THE WORK IS COMPLETED A REVISED PLAN OR STATEMENT FROM THE PERMIT HOLDER SHALL BE SUBMITTED TO THIS OFFICE SHOWING OR EXPLAINING THAT THE CONDITIONS HAVE BEEN MET. IF THIS REQUIREMENT IS NOT RECEIVED YOUR CERTIFICATE OF OCCUPANCY SHALL BE WITHHELD. (You Shall Call for Inspections)

****ALL PLANS THAT REQUIRE A PROFESSIONAL DESIGNER'S SEAL, (AS PER SECTION 114.0 OF THE BUILDING CODE) SHALL ALSO BE PRESENTED TO THIS DIVISION ON AUTO CAD LT. 2000, DXF FORMAT OR EQUIVALENT.

*****CERTIFICATE OF OCCUPANCY FEE \$50.00

3 STORY Deck exist The 2nd Floor 4 3nd Floor Decks will be Replaced V Using existing SUPPORT PillARS The Roof. of 1st Floor structures will Romain exactly. As They AREN The Perimeter of Dock will Be FRAMED with 2x8 Doubled & Joist will.

Be 2x6x7. with HANGERS on each end Decking will be 5 x6 All materials will be pressure treated NO STAIRS will be needed As The existing ones will remain



CITY OF PORTLAND, MAINE

Department of Building Inspection

				1 1		- · ·	20	\
Re	ceived fro	om	*					a fee
						(400 Dal	l ()	
<u>of</u>		: t - II	* ****	Stewart and Stewart Control	<u> </u>	/100 Dol	lars \$	`
for	permit to	install erect alter		A Company		TWO	7x 00	i de la
at		move demolish	:			Est. Cost		
<u>u</u>						201. 0001	<u> </u>	
	8 1		11	270	5	i - In ya gapa ayak ayak is	and the second second second	
	C. 3.	}		المسدر		Inspector of b	ouildings	
		1	90	FOT	Per_	24		
							1 ~	

THIS IS NOT A PERMIT

No work is to be started until PERMIT CARD is actually posted upon the premises. Acceptance of fee is no guarantee that permit will be granted. PRESERVE THIS RECEIPT. In case permit cannot be granted the amount of the fee will be refunded upon return of the receipt less \$5.00 or 10% whichever is greater.

WHITE - Applicant's Copy YELLOW - Office Copy PINK - Auditors Copy