City of Portland, Maine – Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716 Permit No: 951154 Location of Construction: Owner: Phone: 871-7564 139 Ashmont St Bundin, Priscilla Leasee/Buyer's Name: Phone: BusinessName: Owner Address: PERMIT ISSUED Ptla. ME 04103 Permit Issued: Contractor Name: Address: Phone: NOV - 6 1995 COST OF WORK: Proposed Use: PERMIT FEE: Past Use: \$ 10,000.00 75.00 1-fam 2-fam CITY OF PORTLAND **FIRE DEPT.** □ Approved INSPECTION: ☐ Denied Use Group: Type: CBL: Zone: 124-G-006 Signature: Signature: Zoning Approval: Proposed Project Description: PEDESTRIAN ACTIVITIES DISTRICT (P.U.D.) Action: Approved Special Zone or Reviews: 1-fam dwelling Approved with Conditions: ☐ Shoreland w/l-fam dwelling ofer garage Denied □ Wetland ☐ Flood Zone Change Use from 1-fam to 2-fam (After the Fact) ☐ Subdivision Date: Signature: ☐ Site Plan maj ☐ minor ☐ mm ☐ Permit Taken By: Date Applied For: Mary Gresik 31 October 1995 **Zoning Appeal** ☐ Variance This permit application doesn't preclude the Applicant(s) from meeting applicable State and Federal rules. ☐ Miscellaneous Building permits do not include plumbing, septic or electrical work. 2. ☐ Conditional Use □ Interpretation Building permits are void if work is not started within six (6) months of the date of issuance. False informa-□ Approved tion may invalidate a building permit and stop all work.. ☐ Denied Historic Preservation WITH REQUIREMENTS ☐ Not in District or Landmark Does Not Require Review ☐ Requires Review Action: **CERTIFICATION** ☐ Appoved I hereby certify that I am the owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been ☐ Approved with Conditions □ Denied authorized by the owner to make this application as his authorized agent and I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in the application issued, I certify that the code official's authorized representative shall have the authority to enter all Date: areas covered by such permit at any reasonable hour to enforce the provisions of the code(s) applicable to such permit 31 October 1995 SIGNATURE OF APPLICANT DATE: PHONE: PHONE: RESPONSIBLE PERSON IN CHARGE OF WORK, TITLE **CEO DISTRICT**

White-Permit Desk Green-Assessor's Canary-D.P.W. Pink-Public File Ivory Card-Inspector

A. Level

CO	MM	EN	TS
----	----	----	----

COMMENTS		
3/18/96 - Not finished yet a Rom		
7/18/90 Not fives hed met. and an garage the center of the call in garage the center of the contract of the contract of the center of the cent		
,		
Inspection Record		
Type Date Foundation:		
Framing:		
Plumbing: Final:		
Other:		

CITY OF PORTLAND, MAINE

Department of Building Inspection

Certificate of Occupancy

LOCATION

139 Ashmont St (124-G-006)

Issued to Paiscilla Rundin Date of Issue 26 December 1996

This is to certify that the building, premises, or part thereof, at the above location, built — altered — changed as to use under Building Permit No. 951154 , has had final inspection, has been found to conform substantially to requirements of Zoning Ordinance and Building Code of the City, and is hereby approved for occupancy or use, limited or otherwise, as indicated below.

PORTION OF BUILDING OR PREMISES

APPROVED OCCUPANCY

Entire

Limiting Conditions:

Two Family Dwelling

1 - Single Family

1 - Single Family (Above Garage)

This certificate supersedes certificate issued

Approved:

(Date)

Inspector

Inspector of Buildings

Notice: This certificate identifies lawful use of building or premises, and ought to be transferred from owner to owner when property changes hands. Copy will be furnished to owner or lessee for one dollar.

	BUILDING PERMIT REPORT					
DATE: 3/NOV/95 ADDRESS: 139 AShmonTST.						
F	REASON FOR PERMIT: Change of USE I fam. dwelling Dottomil / dwelliz					
E	BUILDING OWNER: Priscilly Runding					
C	CONTRACTOR: , , , , , , , , , , , , , , , , , , ,					
ŀ	PERMIT APPLICANT: DENIED: 4/3*/14					
	CONDITION OF APPROVAL OR DENTAL					
-	Before concrete for foundation is placed, approvals from the					
-	Development Review Coordinator and Inspection Services must be					
	obtained. (A 24 hour notice is required prior to inspection)					
	2. Precaution must be taken to protect concrete from freezing.					
	3. It is strongly recommended that a registered land surveyor check all					
•	foundation forms before concrete is placed. This is done to verify					
	that the proper setbacks are maintained.					
4	All vertical openings shall be enclosed with construction having a fire					
7	rating of at least one(1) hour, including fire doors with selfclosers.					
t	Each apartment shall have access to two(2) separate, remote and					
•	approved means of egress. A single exit is acceptable when it exits					
	directly from the apartment to the building exterior with no					
	communications to other apartment units.	i				
(The boiler shall be protected by enclosing with one(1) hour fire-rated					
	construction including fire doors and ceiling, or by providing					
	automatic extinguishment. Sprinkler piping serving not more than six					
	sprinklers may be connected to a domestic water supply having a					
	capacity sufficient to provide 0.15 gallons per minute, per square foot					
	of floor throughout the entire area. An INDICATING shut-off valve	1				
	shall be installed in an accessible location between the sprinkler and					
	the connection to the domestic water supply. Minimum pipe size shall					
	be 3/4 inch copper or 1 inch steel. Maximum coverage area of a					
	residential sprinkler is 144 sq. feet per sprinkler.					
$\cdot V$						
A	and I-1 shall have at least one operable window or exterior door					
	approved for emergency egress or rescue. The units must be operable					
	from the inside without the use of special knowledge or					
	separate tools. Where windows are provided as means of egress or					
	rescue, they shall have a sill height not more than 44 inches (1118mm)					
	above the floor. All egress or rescue windows from sleeping rooms					
	shall have a minimum net clear opening height dimension of 24 inches					
	(610mm). The minimum net clear opening width dimension shall be 20 inches (508 mm), and a minimum net clear opening of 5.7 sq. feet.					
	8. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type.					
V	9. All single and multiple station smoke detectors shall be of an approved					
X	type and shall be installed in accordance with the provisions of the					
	City's building code Chapter 9, section 19, 919.3.2(BOCA National					
	Building Code/1993), and NFPA 101 Chapter 18 & 19. (Smoke detectors					
	shall be installed and maintained at the following locations):					
	printer no minoration draw manifestation do mio representational.					

- 1. In the immediate vicinity of bedrooms
- 2. In all bedrooms

3. In each story within a dwelling unit, including basements In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted.

- 10. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of 1/2 inch gypsum board or the equivalent applied to the garage side. (Chapter 4 section 407.0 of the BOCA/1993)
- side. (Chapter 4 section 407.0 of the BOCA/1993)
 Guardrail & Handrails—A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect.
 - 12. All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10, section & subsections 1023. & 1024. of the City's building code. (The BOCA National Building Code/1993)
- 13. Stair construction in Use Group R-3 & R-4 is a minimum of 9" tread and 8-1/4" maximum rise. All other Use Group minimum 11" tread, 7" maximum rise.
- X 14. Headroom in habitable space is a minimum of 7'6".
 - 15. The minimum headroom in all parts of a stairway shall not be less than 80 inches.
 - 16. All construction and demolition debris must be disposed at the City's authorized reclamation site. The fee rate is attached. Proof of such disposal must be furnished to the office of Inspection Services before final Certificate of Occupancy is issued or demolition permit is granted.
 - 17. Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
 - 18. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act, Title 5 MRSA refers, shall obtain a certification from a design professional that the plans of the facility meet the standards of construction required by this section. Prior to commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services.

19. This permit does not excuse the applicant from obtaining any license which may be needed from the City Clerk's Office.

P. Samuel Hoffses, Chief of Inspection Services

/el 3/16/95

Applicant: Priscilla Rund Address: 139 Ashmant (1 Assessors No.: 124-6-006 48

Date: 11/3/95

CHECK LIST AGAINST ZONTNG ORDTNANCE

	Date -
	Zone Location - R-S
	Interior or corner lot -
_	Use - a Change of use 1-> 2 m XS
	Sewage Disposal -
	Rear Yards -
	Side Yards -
	Front Yards -
	Projections -
	Height -
	Lot Area - 6060° per ASSESS or Sulding Area - $11,615$ Area per Family $-30004/md = 6,0004$
	Building Area -
	Area per Family $-30004/mJ = 6,0004$
	Width of Lot -
	Lot Frontage -
=	Off-street Parking - I for existing + 1/2 for New unit = 2/2 SPACES Loading Bays - Zeargarage + The Concection to be Shown
	Loading Bays - (Zeargarage + The Consect to be Shown

Site Plan - NA Shoreland Zoning - NA

Flood Plains -

PRISCILIA RUNDIN Situplans 139 ASHMONESE 1249-648 as Trustee for the Ashmont Street
Nominee Trust Ahment 2 b existing anager house Dispute Dispute Driveway 10

as Trustee for the & Ashmont Street Riscilla Runcin 139 Ashmont St. Nominee Trust Existing garage coopuin Snapym 181 のとり SINK DOOG DOOR boxi 38 Grapuim (ndpuim XND BIRK Shove - window -DOOR Stairs Window