City of Portland, Maine - Building or Use Permit Application 383 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716 Permit No: Location of Construction: Owner: Phone: 629 Forest Ave Ptdl 04103 William Gowen/Chekinah Co. Lessee/Buyer's Name: Owner Address: Phone: BusinessName: P.O. Box 1088 Windham OA Phone: Contractor Name: Address: Michael Fox 1043 Congress St Ptld 04102 842-9139 COST OF WORK: PERMIT FEE: Past Use: Proposed Use: 10.00 Retail Same **FIRE DEPT.** □ Approved INSPECTION: Use Group Type: 75 ☐ Denied Zone: CBL: Signature: Zoning Approval: Proposed Project Description: PEDESTRIAN ACTIVITIES DISTRICT (P.A.D.) to be 110 Approved П Action: Special Zone or Reviews: Temperary sign 3-1-99 - 3-30-99 Approved with Conditions: ☐ Shoreland П Denied □ Wetland ☐ Flood Zone □ Subdivision Signature: Date: ☐ Site Plan maj ☐minor ☐mm ☐ Permit Taken By: Date Applied For: SP February 26, 1999 **Zoning Appeal** □ Variance This permit application does not preclude the Applicant(s) from meeting applicable State and Federal rules. ☐ Miscellaneous Building permits do not include plumbing, septic or electrical work. ☐ Conditional Use □ Interpretation Building permits are void if work is not started within six (6) months of the date of issuance. False informa-☐ Approved tion may invalidate a building permit and stop all work... □ Denied PERMIT ISSUED WITH REQUIREMENTS **Historic Preservation** ☐ Not in District or Landmark ☐ Does Not Require Review ☐ Requires Review Action: CERTIFICATION ☐ Appoved ☐ Approved with Conditions I hereby certify that I am the owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been ☐ Denied authorized by the owner to make this application as his authorized agent and I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in the application is issued, I certify that the code official's authorized representative shall have the authority to enter all areas covered by such permit at any reasonable hour to enforce the provisions of the code(s) applicable to such permit February 26, 1999 SIGNATURE OF APPLICANT ADDRESS: DATE: PHONE: RESPONSIBLE PERSON IN CHARGE OF WORK, TITLE PHONE: **CEO DISTRICT**

COMMENTS

6/20/n -	Temp sum	gone -	Remanont	Sign in	place (permit # 990258) 70	n
1			V				
			,				
			Demit #	# 990159			
			1,1,1,0				
			CBL# 12	25-N-5			4 - 41
	1						
					,		
					A	No. A process demonstration of the contract of	
				De &	u/		
				U			
				/			
				and the second s			
					Type	Inspection Record	Date
				Foundatio			
				Framing:			
				Other			

	BUILDING PERMIT REPORT
DAT	TE: March 1999 ADDRESS: 629 Fores TAUR CBL 125-N- ASON FOR PERMIT: Temporary 3190 3-1-99-3-30-99
REA	SON FOR PERMIT: Tem Dorary 3197 3-1-99-3-30-99
BUII	LDINGOWNER: Gowen / CheKinah Co.
	TRACTOR: Michae For
	MIT APPLICANT:
USE	GROUPBOCA 1996 CONSTRUCTION TYPE
	CONDITION(S) OF APPROVAL
This	Permit is being issued with the understanding that the following conditions are met:
Anni	roved with the following conditions: × / ×3 (
$\sqrt{1.}$	This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.
2.	Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection)
2.5	Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more
2.5	than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside
	edge of the footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the
	floor, and that the top of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with
	an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be
	higher than the floor elevation. The top of joints or top of perforations shall be protected with an approved filter membrane
	material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6
	of the same material. Section 1813.5.2
26	Foundations anchors shall be a minimum of 1/2" in diameter, 7" into the foundation wall, minimum of 12" from corners of
	foundation and a maximum 6 'o.c. between bolts. (Section 2305.17)
3. 1	Precaution must be taken to protect concrete from freezing. Section 1908.0 It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to
4.	verify that the proper setbacks are maintained.
5.	Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from
	adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior
	spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board
	or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996)
6.	All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National
0.	Mechanical Code/1993). Chapter 12 & NFPA 211
7.	Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214.0 of the city's
	building code
8.	Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking
	surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum
	height all Use Groups 42" except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and R and
	public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a
	diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect.
	(Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not be less than 30", but not more than 38".)
	Handrail grip size shall have a circular cross section with an outside diameter of at least 1 1/4" and not greater than 2". (Sections
0	1021 & 1022.0) - Handrails shall be on both sides of stairway. (Section 1014.7) Headroom in habitable space is a minimum of 7'6". (Section 1204.0)
9.	Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group minimum
10.	11" tread. 7" maximum rise. (Section 1014.0)
11	The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8") 1014.4
11.	The minimum head oom in an parts of a state way state not so 2000 and to 2000 and to 2000.

12. Every sleeping room below the fourth story in buildings of use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special

knowledge or separate tools. Where windows are provided as <u>means of egress or rescue</u> they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft. (Section 1018.6)

- 13. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units. Section 1010.1
- All vertical openings shall be enclosed with construction having a fire rating of at lest one (1)hour, including fire doors with self closer's. (Over 3 stories in height requirements for fire rating is two (2) hours.) Section 710.0
- The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by providing automatic extinguishment. Table 302.1.1
- All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):
 - In the immediate vicinity of bedrooms
 - In all bedrooms
 - In each story within a dwelling unit, including basements

In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required) Section 920.3.2

- 17. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. Section 921.0
- 18. The Fire Alarm System shall be maintained to NFPA #72 Standard.
- 19. The Sprinkler System shall maintained to NFPA #13 Standard.
- 20. All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023. & 1024. Of the City's building code. (The BOCA National Building Code/1996)
- 21. Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
- The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services.
- 23. Ventilation shall meet the requirements of Chapter 12 Sections 1210. Of the City's Building Code. (crawl spaces & attics)
- All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade. No closing in of walls until all electrical (min. 72 hours notice) and plumbing inspections have been done.
- 25. All requirements must be met before a final Certificate of Occupancy is issued.
- All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code. (The BOCA National Building Code/1996).
- 27. Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical Code/1993). (Chapter M-16)
- 28. Please read and implement the attached Land Use-Zoning report requirements.
- 29. Boring, cutting and notching shall be done in accordance with Sections 2305.4.4, 2305.5.1 and 2305.3. of the City's building code.


30.	Glass and glazing shall meet the requirements of Chapter 24 of the building code.
A31.	Banners and Cloth signs Shall be hung as persection 3102,12,1 of The bldg, Code, Code, The BOCA NATURAL Bldg, Code /1996)
32.	

Samplel Hoffses, Building Inspector


Lt. McCongall, PFD Marge Schmuckal, Zoning Administrator

PSH 8-1-98

33.



will be attached to Blog with 4 HEAVY DUTY WAShers and Screws 3 inch long



THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

Building or Use Permit Pre-Application

Attached Single Family Dwellings/Two-Family Dwelling

Multi-Family or Commercial Structures and Additions Thereto

In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or Use Permit.

NOTE**If you or the property owner owes real estate or personal property taxes or user charges on ANY PROPERTY within the City, payment arrangements must be made before permits of any kind are accepted.

Location/Addressof Construction (include Portion of Building): # 629 FOREST AVE PORTLAND NE. 04103
Total Square Footage of Proposed Structure 500 SF Square Footage of Lot
Tax Assessor's Chart, Block & Lot Number Chart# 12 5 Block# Lot#0 5 CheKinah Co. Telephone#:
Owner's Address: SHEVINAH CO, Lessee/Buyer's Name (If Applicable) PO BOX 1088, WINDHAM ME 04062 Lessee/Buyer's Name (If Applicable) Cost Of Work: Fee Show in DHAM
Proposed Project Description: (Please be as specific as possible) BANER 3'X8'F. Letter NOW OPEN CGS Computer, Games & Gervices 3/1/99 - 3/30/99
Contractor's Name, Address & Telephone MICHAEL D. Fox 1043 Congress st. Portland 04102
Current Use: Proposed Use:
Separate permits are required for Internal & External Plumbing, HVAC and Electrical installation. •All construction must be conducted in compliance with the 1996 B.O.C.A. Building Code as amended by Section 6-Art III. •All plumbing must be conducted in compliance with the State of Maine Plumbing Code. •All Electrical Installation must comply with the 1996 National Electrical Code as amended by Section 6-Art III. •HVAC(Heating, Ventililation and Air Conditioning) installation must comply with You must Include the following with you application: 1) ACopy of Your Deed or Purchase and Sale Agreement 2) A Copy of your Construction Contract, if available 3) A Plot Plan/Site Plan Minor or Major site plan review will be required for the above proposed projects. The attached checklist outlines the minimum standards for a site plan. 4) Building Plans Unless exempted by State Law, construction documents must be designed by a registered design professional.

A complete set of construction drawings showing all of the following elements of construction:

- Cross Sections w/Framing details (including porches, decks w/ railings, and accessory structures)
- Floor Plans & Elevations
- Window and door schedules
- Foundation plans with required drainage and dampproofing
- Electrical and plumbing layout. Mechanical drawings for any specialized equipment such as furnaces, chimneys, gas equipment, HVAC equipment (air handling) or other types of work that may require special review must be included.

Certification

I hereby certify that I am the Owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his/her authorized agent. I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in this application is issued, I certify that the Code Official's authorized representative shall have the authority to enter all areas covered by this permit at any reasonable hour to enforce the provisions of the codes applicable to this permit.

citioree the provincing of the	ecues appreciate to this permit.		
Signature of applicant:	(Midlace D. Fox	Date:	2/25/99

Building Permit Fee: \$25.00 for the 1st \$1000.cost plus \$5.00 per \$1,000.00 construction cost thereafter.

Additional Site review and related fees are attached on a separate addendum

SIGNAGE PRE-APPLICATION

PLEASE ANSWER ALL QUESTIONS

ADDRESS: 629 FOREST AVE PORTLAND ME 04103 ZONE: 32
OWNER: WILLIAM GOWEN (CHERINAH CO.)
APPLICANT: MICHAEL D. FOX
ASSESSOR NO
PLEASE CIRCLE APPROPRIATE ANSWER
SINGLE TENANT LOT? YES NO MULTI-TENANT LOT? YES NO
FREESTANDING SIGN? (ex. Pole Sign) YES NO DIMENSIONS HEIGHT
MORE THAN ONE SIGN? YES NO DIMENSIONS HEIGHT SIGN ATTACHED TO BLDG.? (YES) NO DIMENSIONS 3'× 8'
SIGN ATTACHED TO BLDG.? (YES) NO DIMENSIONS 3 × 8.
MORE THAN ONE SIGN? YES NO DIMENSIONS
AWNING: YES NO IS AWNING BACKLIT? YES NO HEIGHT OFF SIDEWALK 8 / IS THERE ANY MESSAGE, TRADEMARK OR SYMBOL ON IT? CGS Computers, Games and Services
LIST ALL EXISTING SIGNAGE AND THEIR DIMENSIONS:
*** TENANT BLDG. FRONTAGE (IN FEET):

AREA FOR COMPUTATION

YOU SHALL PROVIDE:

A SITE SKETCH AND BUILDING SKETCH SHOWING EXACTLY WHERE EXISTING AND NEW SIGNAGE IS LOCATED MUST BE PROVIDED. SKETCHES AND/OR PICTURES OF PROPOSED ARE ALSO REQUIRED.

SIGNATURE OF APPLICANT: Micleace I	Fox DATE:	2/25/99
------------------------------------	-----------	---------

INFORMATION REQUIREMENTS FOR SIGN PERMIT APPLICATION

Applicants for a sign permit will be asked to submit the following information to the Code Enforcement Office:

- 1. Proof of insurance
- 2. Letter of permission from the owner
- A sketch plan of lot, indicating location of buildings, driveways and any abutting streets or right of ways. Lengths of building frontages and street frontages should be noted. (see attached)
- 4. Indicate on the plan all existing and proposed signs
- 5. Computation of the following:
 - A) Sign area of each existing and proposed building sign
 - B) Sign area height and setback of each existing and proposed freestanding sign
- 6. A sketch of any proposed sign(s), indicating dimensions, materials, source of illumination and construction method (see attached).
- 7. Certificate of flammability required for awning/canopy at time of application.
- 8. UL # required for lighted signs at the time of application.

Fee for permit - \$25.00 plus \$0.20 per square foot

Fee for awning based on cost of work - \$25.00 for the first \$1,000.00, \$5.00 for each additional \$1,000.000.

NOTE: Once a sketch plan has been filed for a property, the code enforcement office will keep a record of the plan so that a new sketch plan will not be required for later changes to signage on the property. In such an instance, applicants will only be required to submit information applicable to the new sign.

Certificate of Flame Resistance

ISSUED BY
CORMIER TEXTILE PRODUCTS, INC.
1 RIVER STREET
SANFORD, MAINE 04073

This is to certify that the materials described below are inherently auntlammable.

FOR	CGS Computers	Games 2 Services ADDRESS 629 FOREST AVE.	
CITY.	PORTLAND	STATE M€ 04103	

The articles described below are made from a firme-resistant factions or material registered and approved by the State Fire Marshal for such use.

Date Manufactured: 1993

Product: 10 3Z. (STANDARD COLORS); 13 3Z. ENAMEL RECEPTIVE; 13 3Z. ENAMEL RECEPTIVE; 12 3Z BLACKOUT (NHITE); AND 16 0Z BLACKOUT (NHITE); AND

The Flame Retardant Process Used WILL NOT Be Removed By Washing

signed: Paulth A Cormier, President

Name of Comany Officer
(207) 499-2400

Corporate Seal