City of Portland, Maine – Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716 Owner: Phone: Permit No: Location of Construction: Bearly in Business. Inc. 772-0300 540 Forest Avenue Owner Address: Lessee/Buyer's Name: Phone: BusinessName: SAA Permit Issued: Contractor Name: Address: Phone: MAR | 9 | 1999 COST OF WORK: PERMIT FEE: Past Use: Proposed Use: 800.00 \$ 25.00 CITY OF PORTLAND Restaurant Same **FIRE DEPT.** □ Approved INSPECTION: Type: ☐ Denied Use Group: CBL: 26-8-005 Zone: Signature: Signature: Zoning Approval: Proposed Project Description: PEDESTRIAN ACTIVITIES DISTRICT (P.A.D.) `Approved Action: Special Zone or Reviews: Approved with Conditions: Outside Dining 1999 Season ☐ Shoreland 15 Denied □ Wetland ·Chip ☐ Flood Zone □ Subdivision Signature: Date: ☐ Site Plan maj ☐minor ☐mm ☐ Permit Taken By: Date Applied For: March 17, 1999 **Zoning Appeal** □ Variance This permit application does not preclude the Applicant(s) from meeting applicable State and Federal rules. ☐ Miscellaneous Building permits do not include plumbing, septic or electrical work. ☐ Conditional Use Building permits are void if work is not started within six (6) months of the date of issuance. False informa-☐ Interpretation ☐ Approved tion may invalidate a building permit and stop all work.. □ Denied **Historic Preservation** ☐ Not in District or Landmark PERMIT ISSUED WITH REQUIREMENTS ☐ Does Not Require Review ☐ Requires Review Action: CERTIFICATION □ Appoved I hereby certify that I am the owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been ☐ Approved with Conditions ☐ Denied authorized by the owner to make this application as his authorized agent and I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in the application is issued, I certify that the code official's authorized representative shall have the authority to enter all areas covered by such permit at any reasonable hour to enforce the provisions of the code(s) applicable to such permit Karch 17, 1999 SIGNATURE OF APPLICANT ADDRESS: DATE: PHONE: RESPONSIBLE PERSON IN CHARGE OF WORK, TITLE PHONE: **CEO DISTRICT**

White-Permit Desk Green-Assessor's Canary-D.P.W. Pink-Public File Ivory Card-Inspector

COMMENTS

COMMENTS			
10/11/10 - Complied a Con 0/s Seating now Class	ed for Secreta		
,			
	Inspection Record		
	Type Foundation:	Date	
	Framing:Plumbing:		
	Final:Other:		
	Ouici,		

DITT DING DEDMIT DEDOOT

DOMDING PERMIT AND ONE
DATE: 18 MAYCH 1999 ADDRESS: 540 Fores T Ave. CBL 126-B-605
REASON FOR PERMIT: OUTside Dining 1999 Season
BUILDING OWNER: Bearly In Business Fre
CONTRACTOR:
PERMIT APPLICANT:
USE GROUP $4-3$ BOCA 1996 CONSTRUCTION TYPE
CONDITION(S) OF APPROVAL
This Permit is being issued with the understanding that the following conditions are met:
Approved with the following conditions: \\ \frac{\dagger}{\lambda} \dagg
1. This permit does not excuse the applicant from meeting applicable State and Federal rules and laws. Perfore concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be

- obtained. (A 24 hour notice is required prior to inspection)
- Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more 2.5 than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the top of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor elevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6" of the same material. Section 1813.5.2
- Foundations anchors shall be a minimum of 1/2" in diameter, 7" into the foundation wall, minimum of 12" from corners of 2.6 foundation and a maximum 6 'o.c. between bolts. (Section 2305.17)
- 3. Precaution must be taken to protect concrete from freezing. Section 1908.0
- It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.
- Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from 5. adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of 1/2 inch gypsum board or the equivalent applied to the garage means of 1/2 inch gypsum board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996)
- All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National 6. Mechanical Code/1993). Chapter 12 & NFPA 211
- Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214.0 of the city's 7. building code.
- Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking 8. surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not be less than 30", but not more than 38".) Handrail grip size shall have a circular cross section with an outside diameter of at least 1 1/4" and not greater than 2". (Sections 1021 & 1022.0) - Handrails shall be on both sides of stairway. (Section 1014.7)
- Headroom in habitable space is a minimum of 7'6". (Section 1204.0) 9.
- Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group minimum 10. 11" tread. 7" maximum rise.(Section 1014.0)
- The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8") 1014.4 11.
- Every sleeping room below the fourth story in buildings of use Groups R and I-1 shall have at least one operable window or 12. exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special

knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft. (Section 1018.6)

- Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units. Section 1010.1
- 14. All vertical openings shall be enclosed with construction having a fire rating of at lest one (1)hour, including fire doors with self closer's. (Over 3 stories in height requirements for fire rating is two (2) hours.) Section 710.0
- The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by providing automatic extinguishment. Table 302.1.1
- All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):
 - In the immediate vicinity of bedrooms
 - In all bedrooms
 - In each story within a dwelling unit, including basements

In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required) Section 920.3.2

- 17. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. Section 921.0
- 18. The Fire Alarm System shall be maintained to NFPA #72 Standard.
- 19. The Sprinkler System shall maintained to NFPA #13 Standard.
- All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023. & 1024. Of the City's building code. (The BOCA National Building Code/1996)
- 21. Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
- The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services.
- 23. Ventilation shall meet the requirements of Chapter 12 Sections 1210. Of the City's Building Code. (crawl spaces & attics)
- 24. All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade. No closing in of walls until all electrical (min. 72 hours notice) and plumbing inspections have been done.
- 25. All requirements must be met before a final Certificate of Occupancy is issued.
- All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code. (The BOCA National Building Code/1996).
- Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical Code/1993). (Chapter M-16)
- 28. Please read and implement the attached Land Use-Zoning report requirements.
- 29. Boring, cutting and notching shall be done in accordance with Sections 2305.4.4, 2305.5.1 and 2305.3. of the City's building code.

30.	Glass and glazing shall meet the requirements of Chapter 24 of the building code. See a Tracked Conditions For outside China - To be
V31.	See attached Conditions For outside Clining - 10 De
4	maintained during its uskap
32.	

P Samuel Boffses, Building Inspector

Lt. McDougall, PFD

Marge Schmuckal, Zoning Administrator

33.

'S IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

Building or Use Permit Pre-Application

Attached Single Family Dwellings/Two-Family Dwelling

Multi-Family or Commercial Structures and Additions Thereto

In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or Use Permit.

NOTE**If you or the property owner owes real estate or personal property taxes or user charges on ANY PROPERTY within the City, payment arrangements must be made before permits of any kind are accepted

promise of any kind are accepted.				
540 FONEST AVE	·			
Owner:	Telephone#:			
BEARLY IN BUSINESS, INC	772-0300			
Lessee/Buyer's Name (If Applicable)	Cost Of Work: Fee			
	3800 35°			
Proposed Project Description: (Please be as specific as possible) WOODEN PRCK FRUCKO-IN FOR ONT POOR DINHEL.				
ning: 1799	Lason			
	Rec'd By			
Proposed Use: Same	0			
or Internal & External Plumbing, HVAC and Electrical instance with the 1996 B.O.C.A. Building Code as ted in compliance with the State of Maine Pluth the 1996 National Electrical Code as amentioning) installation must comply with the 1900 our Deed or Purchase and Sale Agreement	amended by Section 6-Art II.			
	Square Footage of Lot 17, 135 Owner: J BEANLY IN BUSINESS, THE Lessee/Buyer's Name (If Applicable) Proposed Use: FRUCES-IN For Proposed Use: Seemed Plumbing, HVAC and Electrical instance with the 1996 B.O.C.A. Building Code as ed in compliance with the State of Maine Pluch the 1996 National Electrical Code as amendoning) installation must comply with the 19			

2) A Copy of your Construction Contract, if available

3) A Plot Plan/Site Plan

Minor or Major site plan review will be required for the above proposed projects. The attached checklist outlines the minimum standards for a site plan.

4) Building Plans

Unless exempted by State Law, construction documents must be designed by a registered design professional. A complete set of construction drawings showing all of the following elements of construction:


- Cross Sections w/Framing details (including porches, decks w/ railings, and accessory structures)
- Floor Plans & Elevations
- Window and door schedules
- Foundation plans with required drainage and dampproofing
- Electrical and plumbing layout. Mechanical drawings for any specialized equipment such as furnaces, chimneys, gas equipment, HVAC equipment (air handling) or other types of work that may require special review must be included.

Certification

I hereby certify that I am the Owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his/her authorized agent. I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in this application is issued, I certify that the Code Official's authorized representative shall have the authority to enter all areas covered by this permit at any reasonable hour to enforce the provisions of the codes applicable to this permit.

Signature of applicant:	Date: / /
	3/17/99
Ruilding Permit Fox \$25.00 for the 1 + \$1.000	

Building Permit Fee: \$25.00 for the 1st \$1000.cost plus \$5.00 per \$1,000.00 construction cost thereafter. Additional Site review and related fees are attached on a separate addendum



MAR-17-89 10:58 FR			(D:	PAGE
ACORD CERT	FICATE OF LIA	BILITY II	45URAN	DATE (MM/20//Y) 10/19/1998
TW See See See See See See See See See	FAX (207)7/4-2994	THIS CERTI	FICATE IS ISSUE	DAS A MATTER OF INFORMATION
DUGER (207)774-5257	140 /501/1/4-5334	ONLY AND	CONFERS NO RIC	SHTS UPON THE CERTIFICATE EDOES NOT AMEND, EXTEND OR
rk Associates		ALTER THE	COVERAGE AFF	ORDED BY THE POLICIES BELOW.
31 Congress Street 3 Bax 3543		1.00	COMPANIES	AFFORDING COVERAGE
reland, ME 04104		COMPANY	Acadia Insura	ance Co.
n:	Ext:	Α		
ukep.	And the second s	COMPANY		
Grizzly Bear, Inc.		8		
Dba the Great Lost	Bear'	COMPANY	the second of the second secon	
F.o. Box 8227		С		
Portland, ME 04104		COMPANY		
INDICATED, NOTWITHSTANDING A	LICIES OF INSURANCE LISTED BELOW NY REQUIREMENT, TERM OR CONDITI MAY PERTAIN, THE INSURANCE AFFOR F SUCH POLICIES. LIMITS SHOWN MAY	ON OF ANY CONTRACT RDED BY THE POLICIES HAVE BEEN REDUCES	FOR OTHER DOCUM S DESCRIBED HERE D BY PAID CLAIMS	AENT VVITH RESPECT TO VVIIGH 1009
n type of insurance	POLICY NUMBER	DATE (MM/DD/YY)	POLICY EXPIRATION DATE (MM/DD/YY)	LIMITS
GENERAL LIABIL'TY				GENERAL AGGREGATE \$ 2,000,00
χ COMMERCIAL GENERAL LIABILIT	(PRODUCTS - COMP/OP AGG \$ 2,000,00
OLAIMS MADE X OCCU	R CPA1001333-12	: : 10/24/1998	10/24/1999	PERSONAL & ADVINJURY \$ 1,000,00
OWNER'S SCONTRACTORS CRO	T	10/11/1330	20/21/222	EACH OCCURRENCE \$ 1.000.00
	:			FIRE DAMAGE (Any one fire) \$ 250.00
				MED EXP (Any one person) \$ 5, 31
AUTOMOBILE LIABILITY				COMBINED SINGLE LIMIT \$
ANY AUTO	•	;		1,000,5
ALL OWNED AUTOS				BODILY INJURY (Per person)
X SCHEDULED AUTOB	CAP0037158-12	11/18/1998	11/18/1999	Line in the second seco
X HIRED AUTOS				BODILY INJURY (Par accident)
X NOW-OVMED AUTOS				Principal Control of the Control of
() ()	•			PROPERTY DAMAGE \$
GARAGE LIABILITY	LEW AND THE PARTY OF THE PARTY		organization and transmission and the second	AUTO ONLY - EA ACCIDENT &
ANY AUTO	t .	:		OTHER THAN AUTO ONLY
•••				EACH ACCIDENT \$
				AGGREGATE \$
EXCESS LIABILITY				FACH DOCURRENCE 3
UMBRELLA FORM	•			AGGREGATE
OTHER THAN UMBRELLA FORM				; WC STRIP
WORKERS COMPENSATION AND				TORY LIMITS FR
EMPLOYERS LIABILITY	WCA1001473-11	07/01/1998	07/01/1999	EL EACH ACCIDENT \$ 100,0
THE PROPRIETOR/ PARTNERS/EXECUTIVE	SE SECULATION AND ALL			EL DISEASE - POLICY LIMIT \$ 500,0
OFFICERS ARE EX	CI.	:		EL DISEASE - EA EMPLOYEE \$ 100.0
OTHER				
	4			
	:	•		
	·			
	BATEUF BEICHERIAL STEEL			The state of the s
EACRIPTION OF OPERATIONS LOCATION ity of Portland is addi	evenicies/special items tional insured on the ge	neral liabilit	y with respec	t to the named insureds
ity of Portland is addi	evenicies/specialitems tional insured on the ge	neral liabilit	y with respec	to the named insureds
escription of operational ocation ty of Portland is addi serations only.	ENTERCLESSEPECIALITEMS Tional insured on the gen	neral liabilit	y with respec	tt to the named insureds

City of Portland Att: Samuel Hoffses Inspection Services 389 Congress Street Portland, M6 04191

ACORD 25-9 (*195)

SHOULD ANY OF THE ABOVE DESCRIBED POLICIES BE CANCELLED BEFORE THE EXPIRATION DATE THEREOF, THE ISSUING COMPANY WILL ENDEAVOR TO MAIL 10 DAYS WRITTEN NOTICE TO THE CERTIFICATE HOLDER NAMED TO THE LEFT. BUT FAILURE TO MAIL BUCH NOTICE SHALL IMPOSE NO OBLIGATION OR LIABILITY

OF ANY HIND UPON THE COMPANY, ITS AGENTS OR REPRESENTATIVES.

WACORD TORPURATION 1868