City of Portland, Maine - Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716 Location of Construction: Owner: Phone: ***53 Clifton Street 04101 Ben Walter 828-2972 Owner Address: Lessee/Buyer's Name: Phone: BusinessName: Same As Above Permit Issued: Contractor Name: Address: Phone: O'Reilly Construction JUN 1 0 1999 COST OF WORK: PERMIT FEE: Past Use: Proposed Use: \$ 4,000 \$ 40.00 1-Family Same **FIRE DEPT.** □ Approved INSPECTION: Use Group: AFT Type: 5B ☐ Denied BOCA96 126-H-004 Signature: Signature: 7 Proposed Project Description: PEDESTRIAN ACTIVITIES DISTRICT (P/A.D.) Action: Approved Deck/Pergola Approved with Conditions: ☐ Shoreland Denied □Wetland ☐ Flood Zone 3 Signature: Date: □ Subdivision ☐ Site Plan maj ☐minor ☐mm ☐ Date Applied For: Permit Taken By: SP June 2, 1999 Zoning Appeal □ Variance This permit application does not preclude the Applicant(s) from meeting applicable State and Federal rules. □ Miscellaneous Building permits do not include plumbing, septic or electrical work. 2. ☐ Conditional Use 3. Building permits are void if work is not started within six (6) months of the date of issuance. False informa-☐ Interpretation ☐ Approved tion may invalidate a building permit and stop all work... ☐ Denied Historic Preservation IDNot in District or Landmark □ Does Not Require Review □ Requires Review **PERMIT ISSUED** Action: WITH REQUIREMENTS **CERTIFICATION** ☐ Appoved ☐ Approved with Conditions I hereby certify that I am the owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his authorized agent and I agree to conform to all applicable laws of this jurisdiction. In addition, □ Denied if a permit for work described in the application is issued, I certify that the code official's authorized representative shall have the authority to enter all Date: areas covered by such permit at any reasonable hour to enforce the provisions of the code(s) applicable to such permit June 2, 1999 ADDRESS: SIGNATURE OF APPLICANT DATE: PHONE:

White-Permit Desk Green-Assessor's Canary-D.P.W. Pink-Public File Ivory Card-Inspector

RESPONSIBLE PERSON IN CHARGE OF WORK, TITLE

PHONE:

CEO DISTRICT

4/11/19 - Checked stakes in grownel for deck placement - appears OK - Talked to home owner regarding ballisters Istairs/plans. The
ameurs ok-
Talked to home owner regarding ballusters stairs plans. The
6134/97 Met w/ owner and builder, went over our plans owner has decided
against built in souts. Will call after puring of
Story 3 Stans from grade Rise # 1 6 to 63/8 # 2/344 all 57/8 Treads # 1 103/4 # 2 103/8 # 3 93/4 7
Treads #1 103/4 # 2 103/8 # 3 93/47
Step to landing & Rise Step to House 8 48 18
openy Botton Roil Left & Right (41/4) / Leller Effect to top Left Sil
Rail bleght alland 36/2
Inspection Record

THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

Building or Use Permit Pre-Application Additions/Alterations/Accessory Structures To Detached Single Family Dwelling

In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or Use Permit.

NOTE**If you or the property owner owes real estate or personal property taxes or user charges on any property within the City, payment arrangements must be made before permits of any kind are accepted.

Location/Address of Construction \$\ 53 CUIF	TOW ST 04/01	
Tax Assessor's Chart, Block & Lot Number Chart# / Block# / LOTE 004	BENWALTER_	Telephone#: 828-2972
Owner's Address: 53 CLIPTOW ST	Lessee Buyer's Name (If Applicable) BEN WACTER	Cost Of Work: Fee 40.
Proposed Project Description:(Please be as specific as possible) DETA / PERGOLA		
Contractor's Name, Address & Telephone ORFILLY CON	STRUCTION	ed By:
•All construction must be conducted in compliance of the conducted in comply we should be conducted. Installation must comply we should be should	eted in compliance with the State of Maine Plevith the 1996 National Electrical Code as ameritioning) installation must comply with the 19 application. ur Deed or Purchase and Sale Agreem cour Construction Contract, if available Plot Plan (Sample Attached) amplete plot plan (Site Plan) must include existing buildings (if any), the proposed structure porches, a bow windows cantilever sections are tructures.	s amended by Section 6-Art II. umbing Code. nded by Section 6-Art III. 193 BOCA Mechanical Code. nent tole e: and the distance from the actual
 A complete set of construction drawings Cross Sections w/Framing details (inclusive Floor Plans & Elevations Window and door schedules Foundation plans with required drainage Electrical and plumbing layout Mechanic equipment. HVAC equipment (air band) 	and dampproofing ieal drawings for any specialized equipment such thug) or other types of work that may require spec Certification	nas furnaces, chimneys, gas cral review must be included.

I hereby certify that I am the Owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his/her authorized agent. I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in this application is issued. I certify that the Code Official's anthorized representative shall have the authority to enter all areas covered by this permit at any reasonable bour to enforce the provisions of the codes applicable to this permit.

of ovisions of the codes applicable	и шіз рени				
Signature of applicant:	Do	121	Date:	6/2/	99

Building Permit Fee: \$25.00 for the 1st \$1000.cost plus \$5.00 per \$1,000.00 construction cost thereafter.

O::INSP:CORRESP MNUGENT APADSFD.WPD



Inspection Services Michael J. Nugent Manager Department of Urban Development Joseph E. Gray, Jr. Director

CITY OF PORTLAND



Building or Use Permit Application Additions/Alterations/Accessory Structures To Detached Single Family Dwelling

As an applicant for a building permit, you are about to enter into a relationship with our Office. We welcome any questions, comments or suggestions that will make the process more efficient. Attached you will find an application and some samples of the submissions you will provide at application time. Please read <u>ALL</u> of the information and if you need any further assistance please call 874-8703 or 874-8693.



BUILDING PERMIT REPORT

, Deliberto i Elderi i del Okt				
reason for permit: Deck / Pergola				
REASON FOR PERMIT: Deck / Pergola				
BUILDING OWNER: Ben Walter				
PERMIT APPLICANT: /Contractor O'Relly Cons/				
USE GROUP Deck / Porge/ BOCA 1996 CONSTRUCTION TYPE 5B				
CONDITION(S) OF APPROVAL				
This permit is being issued with the understanding that the following conditions are met:				
Approved with the following conditions: $\frac{x/\sqrt{2}, \frac{x}{1/\sqrt{13}}, \frac{x}{27}, \frac{12}{432}, \frac{x}{33}, \frac{x}{34}$				
This permit does not excuse the applicant from meeting applicable State and Federal rules and laws				

not excuse the applicant from meeting applicable State and Federal rules and laws.

Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection)

Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the top of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor elevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6" of the same material. Section 1813.5.2

4. Foundations anchors shall be a minimum of 1/2" in diameter, 7" into the foundation wall, minimum of 12" from corners of foundation and a maximum 6' o.c. between bolts. (Section 2305.17)

5. Waterproofing and damp proofing shall be done in accordance with Section 1813.0 of the building code.

6. Precaution must be taken to protect concrete from freezing. Section 1908.0

7. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.

8. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of 1/2 inch gypsum board or the equivalent applied to the garage means of 1/2 inch gypsum board or the equivalent applied to the garage side. (Chapter 4, Section 407.0 of the BOCA/1996)

All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993). Chapter 12 & NFPA 211

Sound transmission control in residential building shall be done in accordance with Chapter 12, Section 1214.0 of the City's Building

X 11. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2, M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 3c4" but not more than 38". Use Group R-3 shall not be less than 30", but not more than 38".) Handrail grip size shall have a circular cross section with an outside diameter of at least 1 1/4" and not greater than 2". (Sections 1021 & 1022.0) - Handrails shall be on both sides of stairway. (Section 1014.7)

Headroom in habitable space is a minimum of 76". (Section 1204.0)

Stair construction in Use Group R-3 & R-4is a minimum of 10" tread and 7 1/2" maximum rise. All other Use Group minimum 11" 13. tread, 7" maximum risc. (Section 1014.0)

The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8") 1014.4 14.

- Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door 15. approved for emergency egress or reseue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft. (Section 1018.6)
- Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits 16. directly from the apartment to the building exterior with no communications to other apartment units. (Section 1010.1)
- All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self 17. closer's. (Over 3 storics in height requirements for fire rating is two (2) hours.) (Section 710.0)

- 18. The boiler shall be protected by enclosing with (1)hour fire rated construction including fire doors and ceiling, or by providing automatic extinguishment. (Table 302.1.1)
- 19. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 &19. (Smoke detectors shall be installed and maintained at the following locations):
 - In the immediate vicinity of bedrooms
 - In all bedrooms
 - In each story within a dwelling unit, including basements

In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required) Section 920.3.2.

- 20. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. (Section 921.0)
- The Fire Alarm System shall maintained to NFPA #72 Standard. 21.
- 22. The Sprinkler System shall maintained to NFPA #13 Standard.
- All exit signs, lights and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023.0 & 1024.0 23. of the City's Building Code. (The BOCA National Building Code/1996)
- Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open 24. any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
- 25. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification the Division of Inspection Services.
- 26. Ventilation shall meet the requirements of Chapter 12 Sections 1210.0 of the City's Building Code. (Crawl spaces & attics).
- All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade. No closing in of walls until X 27. all electrical (min. 72 hours notice) and plumbing inspections have been done.
 - 28. All requirements must be met before a final Certificate of Occupancy is issued.
- All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code (the BOCA National Building <u>X</u> 29. Code/1996).
 - 30. Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical Code/1993). (Chapter M-16)
 - Please read and implement the attached Land Use Zoning report requirements. 31.
- Boring, cutting and notching shall be done in accordance with Sections 2305.4.4, 2305.5.1 and 2305.5.3 of the City's Building Code.

¥32. ¥33. Glass and glazing shall meet the requirements of Chapter 24 of the building code.

¥ 34.	Foundation Piens must rest on	Footing with anchor between
<u></u>	The FOOTING and Pien-	
35.		

36.

loffses, Building Inspector McDougall, PFD

Marge Schmuckal, Zoning Administrator

PSH 12-14-98

^{**}On the basis of plans submitted and conditions placed on these plans any deviations shall require a separate approval.

Submission Requirements Residential Construction

When a property owner is proposing either a new structure or an addition, this office requires:

• A plot or site plan, showing the shape and dimensions of the entire lot, all existing and proposed structures on the lot and the distance that the structures are from all lot lines. For a new dwelling the plan must be prepared by a registered design professional. For dwelling additions, the plan can be prepared by the owner or agent. (See Figure 1)





Figure 1. Typical Plot Plan

As can be seen, it is easy to establish the extent of compliance with the required setbacks and lot coverage.

• For new construction, structural alterations, or additions, plans showing structural details must be provided. Minimally they should include foundation plans, including drainage and support column spacing framing details, floor plans and a cross section. (See Figures 2, 3 &4)






Figure 2. Typical Foundation Plan




Figure 4. Typical Framing and Cross Section

These plans are all done by professionals, you can do your own plans for the purposes of residential construction, the plan does not have to be of this quality, but the level of detail and accuracy is important. When proposing and addition, similar plans are required, the same goes for a detached garage or an attached deck.