City of Portland, Maine – Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716 Location of Construction: Phone: **84-86 Codman Street 04103 * Louis & Becky Pirone 772-1499 Lessee/Buver's Name: Owner Address: Phone: BusinessName: 86 Codman Street Permit Issued: Contractor Name: Address: Phone: Mike Walker MG 20 COST OF WORK: PERMIT FEE: Past Use: Proposed Use: \$ 1,500 \$ 36.00 **FIRE DEPT.** □ Approved Same INSPECTION: 2-Family Use Group: \$3 Type 5 ☐ Denied CBL: 128-A-017 Signature: Zonin 🖋 Approval: Proposed Project Description: PEDESTRIAN ACTIVITIES DISTRICT Replace porch, steps and rails. Action: Approved Special Zone or Reviews: Approved with Conditions: □ Shoreland nl w Denied ☐ Wetland □ Flood Zone 4 ☐ Subdivision. Signature: Date: ☐ Site Plan mai ☐minor ☐n Permit Taken By: Date Applied For: UB 8-13-99 **Zoning Appeal** □ Variance This permit application does not preclude the Applicant(s) from meeting applicable State and Federal rules. ☐ Miscellaneous Building permits do not include plumbing, septic or electrical work. ☐ Conditional Use □ Interpretation Building permits are void if work is not started within six (6) months of the date of issuance. False informa-3. ☐ Approved tion may invalidate a building permit and stop all work.. **** Mail To: Louis & Becky Pirone □ Denied 84-86 Codman Street Historic Preservation Portland, ME 04103 Not in District or Landmark ☐ Does Not Require Review ☐ Requires Review PERMIT ISSUED WITH REQUIREMENTS Action: CERTIFICATION ☐ Appoved □ Approved with Conditions I hereby certify that I am the owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been □ Denied authorized by the owner to make this application as his authorized agent and I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in the application is issued, I certify that the code official's authorized representative shall have the authority to enter all Date: areas covered by such permit at any reasonable hour to enforce the provisions of the code(s) applicable to such permit 8-13-99 SIGNATURE OF APPLICANT ADDRESS: DATE: PHONE: RESPONSIBLE PERSON IN CHARGE OF WORK, TITLE PHONE: **CEO DISTRICI**

White-Permit Desk Green-Assessor's Canary-D.P.W. Pink-Public File Ivory Card-Inspector

ub

THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

Building or Use Permit Pre-Application Attached Single Family Dwellings/Two-Family Dwelling

Multi-Family or Commercial Structures and Additions Thereto

In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or Use Permit.

NOTE**If you or the property owner owes real estate or personal property taxes or user charges on ANY PROPERTY within the City, payment arrangements must be made before permits of any kind are accepted.

	College Colleg	
Location/Addressof Construction (include Portion of Build	ling) + 84-86 COdM+	AN STreet 04103
Total Square Footage of Proposed Structure	Square Footage of Lot	
Tax Assessor's Chart, Block & Lot Number	Ownest	Telephone#:
Chart# 128 Block# A Lot# OI	Louis + Becker Piron	R 7721499
Owner's Address:	Lessee/Buyer's Name (If Applicable)	Cost Of Work: Fee
86 CodmAN ST		\$ 1,500 \$ 36-
Proposed Project Description:(Please be as specific as poss	ible)	
Replaced Porch + Contractor's Name, Address & Telephone Mich	STEPS + RALS	
Contractor's Name, Address & Telephone	ze unlker	Rec'd By UB
	Proposed Use:	SAME
7 Famaily		
Separate permits are rec	uired for Internal & External Plumbing, HVAC and Electronic Internal & Property of the Propert	
	npliance with the 1996 B.O.C.A. Building C nducted in compliance with the State of Ma	
	oly with the 1996 National Electrical Code a	
	onditioning) installation must comply with	the 1993 BOCA Mechanical Code.
You must Include the following with you applic		CITY OF PORTLAND, ME
1) ACopy	of Your Deed or Purchase and Sale Agreen	nent Nent
2) A Co	py of your Construction Contract, if availab	ole Arc Longo
	3) A Plot Plan/Site Plan	D AUG 3 1999
Minor or Major site plan review will be require		1101
cbecklist outlines the minimum standards for a		B B B I W R
VI-1	4) Building Plans	
A complete set of construction drawings shown	struction documents must be designed by a	
	eluding porches, decks w/ railings, and accessor	
• Floor Plans & Elevations	cluding potenes, decks w/ faitings, and accessor	ry suddimes)
Window and door schedules		
Foundation plans with required drain	age and damporoofing	
	nanical drawings for any specialized equipment	such as furnaces, chimneys, gas
	ndling) or other types of work that may require	
1 1	Certification	332-241-
I hereby certify that I am the Owner of record of the named owner to make this application as his/her authorized agent.	property, or that the proposed work is authorized by the ow I agree to conform of applicable laws of this jurisdiction	mer of record and that I have been authorized by t 1. In addition, if a permit for work described in thi

Building Permit Fee: \$30.00 for the 1st \$1000.cost plus \$6.00 per \$1,000.00 construction cost thereafter.

Additional Site review and related fees are attached on a separate addendum

Date:

application is issued, I certify that the Code offigial's authorized representative shall have the authority to enter all areas covered by this permit at any reasonable hour to

cuforce the provisions of the codes applicable to this permit.

Signature of applicant:

	BUILDING PERMIT REPORT		
DAT	sonforpermit: Replace Porch - STeps & Vails		
REA	SONFORPERMIT: Replace Porch - STeps & Kails		
BUIL	LDING OWNER: Piyon e		
PERI	MIT APPLICANT: 1Contractor MIKe Walker		
USE	GROUP R-3 CONSTRUCTION TYPE 5-B		
	City's Adopted Building Code (The BOCA National Building Code/1996 with City Amendments) City's Adopted Mechanical Code (The BOCA National Mechanical Code/1993)		
	CONDITION(\$) OF APPROVAL		
This p	permit is being issued with the understanding that the following conditions are met: *1, *27 *30 *32 *33		
Appro	oved with the following conditions:		
1. 2.	This permit does not excuse the applicant from meeting applicable State and Federal rules and laws. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection)		
3.	Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the top of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor elevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be		
ა 4.	placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6" of the same material. Section 1813.5.2 Foundations anchors shall be a minimum of 1/2" in diameter, 7" into the foundation wall, minimum of 12" from corners of foundation and		
	a maximum 6' o.c. between bolts. (Section 2305.17)		
5. '	Waterproofing and dampproofing shall be done in accordance with Section 1813.0 of the building code.		
5. 7.	Precaution must be taken to protect concrete from freezing. Section 1908.0 It is strongly recommended that a registered land surveyor cheek all foundation forms before concrete is placed. This is done to verify		

that the proper setbacks are maintained.

8. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than I-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of 1/2 inch gypsum board or the equivalent applied to the garage means of 1/2 inch gypsum board or the equivalent applied to the garage side. (Chapter 4, Section 407.0 of the BOCA/1996)

All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code, (The BOCA National Mechanical Code/1993). Chapter 12 & NFPA 211

Sound transmission control in residential building shall be done in accordance with Chapter 12, Section 1214.0 of the City's Building Code.

Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces X11. for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2, M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 3e4" but not more than 38". Use Group R-3 shall not be less than 30", but not more than 38".) Handrail grip size shall have a circular cross section with an outside diameter of at least 1 1/4" and not greater than 2". (Sections 1021 & 1022.0) - Handrails shall be on both sides of stairway. (Section 1014.7)

Headroom in habitable space is a minimum of 76". (Section 1204.0)

Stair construction in Use Group R-3 & R-4is a minimum of 10" tread and 7 1/2" maximum rise. All other Use Group minimum 11" X-13. tread, 7" maximum rise. (Section 1014.0)

The minimum headroom in all parts of a stainway shall not be less than 80 inches. (6'8") 1014.4 14.

Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door 15. approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft. (Section 1018.6)

Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits 16. directly from the apartment to the building exterior with no communications to other apartment units. (Section 1010.1)

	All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self
	closer's. (Over 3 stories in height requirements for fire rating is two (2) hours.) (Section 710.0)
	The boiler shall be protected by enclosing with (1)hour fire rated construction including fire doors and ceiling, or by providing automatic extinguishment. (Table 302.1.1)
	All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of
	the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 &19. (Smoke detectors shall be installed and maintained at the following locations):
	In the immediate vicinity of bedrooms
	In all bedrooms
	 In each story within a dwelling unit, including basements
	In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall
	receive power from a battery when the AC primary power source is interrupted. (Interconnection is required) Section 920.3.2.
	A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved
	type. (Section 921.0)
	The Fire Alarm System shall maintained to NFPA #72 Standard.
	The Sprinkler System shall maintained to NFPA #13 Standard.
	All exit signs, lights and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023.0 & 1024.0
	of the City's Building Code. (The BOCA National Building Code/1996)
	Section 25-135 of the Municipal Code for the City of Portland states, 'No person or utility shall be granted a permit to excavate or open
	any street or sidewalk from the time of November 15 of each year to April 15 of the following year.
	The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification the Division of
	Inspection Services.
	Ventilation shall meet the requirements of Chapter 12 Sections 1210.0 of the City's Building Code. (Crawl spaces & attics).
	All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade. No closing in of walls until
	all electrical (min.72 hours notice) and plumbing inspections have been done.
	All requirements must be met before a final Certificate of Occupancy is issued.
	All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code (the BOCA National Building Code/1996).
	Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical
	Code/1993). (Chapter M-16) (DA)ot to increase or amal footing
	Code/1993). (Chapter M-16) Please read and implement the attached Land Use Zoning report requirements DNOT to increase Number of units Boring. cutting and notching shall be done in accordance with Sections 2305.4.4, 2305.5.1 and 2305.5.3 of the City's Building Code.
	Boring, cutting and notching shall be done in accordance with Sections 2305.4.4, 2305.5.1 and 2305.5.3 of the City's Building Code.
	Glass and glazing shall freet the requirements of Chapter 24 of the building code.
	All signage, shall be done in accordance with Section 3102.0 signs of the City's Building Code, (The BOCA National Building Code
	1996).
0	
1	h_1

Hell Hallises, Building Inspector

Marge Schmuckal, Zoning Administrator

PS117/2499

**On the basis of plans submitted and conditions placed on these plans any deviations shall require a separate approval.

84- M. Codonan St PironE

Louis + Becky PIPONE FRONT VEIN 17' WIDE Y' DEEP = 6x6 SUPPORT COLUME See Dermil 4x4 POST 227 (4"06) ZX4 TOP/BUTTOM RAIL 5/4 DECK TOP Zeg (16 OC) 42 7 1/4" NKE asTers 11 " TREAT Faster SFT Dem 5FT Down EXISTING PIEN EXISTING PIEVZ