City of Portland, Maine – Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716

Location of Construction: 5 Bryant St	of Construction: Owner: Phone: Phone:			Permit No: 990209
Owner Address: 5 Bryant St	Lessee/Buyer's Name:	Phone: Busin	essName:	PERMIT ISSUED
Contractor Name: Address: 167 Mussey St S. Portland 04106 Phone:				Fermit Issued: MAR 5 999
Past Use:	Proposed Use:	COST OF WORK: \$	PERMIT FEE: \$ 25.00	
Single Family	same w/Nome Occupaton	FIRE DEPT. Approved Denied	I INSPECTION: Use Group: Type:	Zone: CBL: 129-C-002
		Signature:	Signature:	Zoning Appreval:
Proposed Project Description:		PEDESTRIAN ACTIVIT		1
Chagae of Use 1-famm to 1-fam wit	http://www.ton	Action: Approved Approved Denied	I with Conditions:	□ Shoreland
	a come e compare o	Signature:	Date:	
Permit Taken By:	Date Applied For:	ch 12, 1999	· · · · · ·	Site Plan maj 🗆 minor 🗆 mm 🗆
2. Building permits do not include plumb	started within six (6) months of the date of issu and stop all work	ance. False informa-	RMIT ISSUED REQUIREMENTS	Zoning Appeal Zoning Appeal Variance Miscellaneous Conditional Use Interpretation Approved Denied Historic Preservation Mot in District or Landmark Does Not Require Review Requires Review Action:
	CERTIFICATION			
authorized by the owner to make this applic if a permit for work described in the applica	d of the named property, or that the proposed we cation as his authorized agent and I agree to con- tion is issued, I certify that the code official's a able hour to enforce the provisions of the code	nform to all applicable laws of uthorized representative shall	this jurisdiction. In addition	n □ Approved with Conditions n, □ Denied
SIGNATURE OF APPLICANT	ADDRESS:	DATE:	PHONE:	-
RESPONSIBLE PERSON IN CHARGE OF		PHONE:		
	ite Dermit Deek, Creen Accessor's Cons	n DDW Disk Dublis File	hom Card Increation	

/hite–Permit Desk Green–Assessor's Canary–D.P.W. Pink–Public File Ivory Card–Inspector

COMMENTS 9 1 aler old removed & new alima nctual work thenge This tis permale 5 (1) -0170 is cheedout - Wai Until 0 to actions stude to N **Inspection Record** Туре Date Foundation: Framing: Plumbing: Final:

Other:

BUILDING PERMIT REPORT

1

DA	TE: 12 MArch 1999 ADDRESS: 5 Bryant ST. CBL 129-C-PB2			
RE	ASON FOR PERMIT: Change of USE Single family with Home Occupancy			
	ILDING OWNER: Vennena Willy			
co	INTRACTOR: ANdrew J, Green			
PEI	RMIT APPLICANT:			
	E GROUP R-3 BOCA 1996 CONSTRUCTION TYPE 53			
0.51				
	CONDITION(S) OF APPROVAL			
Thi	s Permit is being issued with the understanding that the following conditions are met:			
Anr	proved with the following conditions: <u>*1</u> , *24 *25 *31			
1-1-1				
×1.	This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.			
2.	Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be			
• 2.5	obtained. (A 24 hour notice is required prior to inspection) Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more			
° 2.5	than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside			
	edge of the footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the			
	floor, and that the top of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with			
	an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be			
	higher than the floor elevation. The top of joints or top of perforations shall be protected with an approved filter membrane			
	material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6"			
	of the same material. Section 1813.5.2			
2.6	Foundations anchors shall be a minimum of 1/2" in diameter, 7" into the foundation wall, minimum of 12" from corners of			
2	foundation and a maximum 6 'o.c. between bolts. (Section 2305.17)			
3.	Precaution must be taken to protect concrete from freezing. Section 1908.0 It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to			
4.	verify that the proper setbacks are maintained.			
5.	Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from			
	adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting			
	rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior			
	spaces and the attic area by means of 1/2 inch gypsum board or the equivalent applied to the garage means of 1/2 inch gypsum board			
	or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996)			
6.	All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National			
	Mechanical Code/1993). Chapter 12 & NFPA 211			
7.	Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214.0 of the city's building code.			
8.	Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking			
0.	surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum			
	height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and R and			
	public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a			
	diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect.			
	(Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not be less than 30", but not more than 38".)			
	Handrail grip size shall have a circular cross section with an outside diameter of at least 1 1/4" and not greater than 2". (Sections			
	1021 & 1022.0) - Handrails shall be on both sides of stairway. (Section 1014.7)			
9.	Headroom in habitable space is a minimum of 7'6". (Section 1204.0)			
10.	Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group minimum			
	11" tread. 7" maximum rise. (Section 1014.0)			

11. The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8") 1014.4

knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft. (Section 1018.6)

- 13. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units. Section 1010.1
- 14. All vertical openings shall be enclosed with construction having a fire rating of at lest one (1)hour, including fire doors with self closer's. (Over 3 stories in height requirements for fire rating is two (2) hours.) Section 710.0
- The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by providing 15. automatic extinguishment. Table 302.1.1
- 16. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):
 - In the immediate vicinity of bedrooms
 - In all bedrooms
 - In each story within a dwelling unit, including basements

In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required) Section 920.3.2

- 17. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. Section 921.0
- 18. The Fire Alarm System shall be maintained to NFPA #72 Standard.
- The Sprinkler System shall maintained to NFPA #13 Standard. 19.
- All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023. & 20. 1024. Of the City's building code. (The BOCA National Building Code/1996)
- Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate 21. or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
- The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a 22. certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services.
- 23. Ventilation shall meet the requirements of Chapter 12 Sections 1210. Of the City's Building Code. (crawl spaces & attics)
- All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade. No closing in of walls \$ 24. until all electrical (min. 72 hours notice) and plumbing inspections have been done.
 - 25. All requirements must be met before a final Certificate of Occupancy is issued.
 - All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code. (The BOCA National 26. Building Code/1996).
- Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National 27. Mechanical Code/1993). (Chapter M-16)
- Please read and implement the attached Land Use-Zoning report requirements.~ AffArbud 28.
- Boring, cutting and notching shall be done in accordance with Sections 2305.4.4, 2305.5.1 and 2305.3. of the City's building 29. code.
- Glass and glazing shall meet the requirements of Chapter 24 of the building code. 30.

This permit is being issued with The understanding That NO Interior work except 2 Non bearing 6't 4 Kyre walls are being erected. 31. 32.

33.

fises, Building Inspector IcDougall, PFD

Marge Schmuckal, Zoning Administrator

PSH 8-1-95

LAND USE - ZONING REPORT

ADDRESS: 5 Bry AV DATE: ome Occupat **REASON FOR PERMIT:** 120 BUILDING OWNER: C-B-L: Greek PERMIT APPLICANT: AWNEW APPROVED: With conditions DENIED: CONDITION(S) OF APPROVAL This permit is being approved on the basis of plans submitted. Any deviations shall require a separate approval before starting that work. During its existence, all aspects of the Home Occupation criteria, Section 14-410, shall be maintained. The footprint of the existing ______ shall not be increased during maintenance 3. reconstruction. All the conditions placed on the original, previously approved, permit issued on _____ 4. are still in effect for this amendment. 5. Your present structure is legally nonconforming as to rear and side setbacks. If you were to demolish the building on your own volition, you will not be able to maintain these same setbacks. Instead you would need to meet the zoning setbacks set forth in today's ordinances. In order to preserve these legally non-conforming setbacks, you may only rebuild the ______ in place and in phases. 6. This property shall remain a single family dwelling. Any change of use shall require a separate permit application for review and approval. Our records indicate that this property has a legal use of ______ units. Any change 7. in this approved use shall require a separate permit application for review and approval. Separate permits shall be required for any signage. under home Occupation's guideling Separate permits shall be required for future decks, sheds, pool(s), and/or garage. 10. This is not an approval for an additional dwelling unit. You shall not add any additional kitchen equipment, such as stoves, microwaves, refrigerators, or kitchen sinks, etc. without special approvals. Other requirements of condition_____ 11. Marge Schmuckal, Zoning Administrator

Willa Vennema and Carter Waldren 5 Bryant St. Portland, ME 04103

To: City of Portland, Office of Zowing/Code inforcement. My home occupation "Fine Artist / painter" meets the criteia for section 14-410 as Followso L a) the square feet of our studio Sprice will be between 300-325 52. Ft., less than in the area of our home. b.) We will not ston goods [s-pplies o-tride or have displays C.) Most UF the space will be used for printing with minimal Storage D.) There will be no exterior signs e.) The house will not be altered on the exterior F.) There will be no need for extra parting (the use will be private) environmental dista-bance gi) There will be no in any way.

h.) There will be no complayees (h.) No additional traffic will be generated J.) There is no verson for a vehical other than a family car.

The space will be used Soley for the purpose of painting works of art.