	<b>∑</b>	DOW	SCH	WINDOW SCHEDULE
MADK	S	SIZE	0+.10	NOTES
	WIDTH	THOITH	Otyle	NOIEO
1	2'-6 1/2"	2'-8"	Awning	
2	2'-6 1/2"	2'-8"	Awning	
3	2'-61/2"	4'-4"	Double Hung	
4	2'-61/2"	4'-4"	Double Hung	
5	2'-6 1/2"	4'-4"	Double Hung	!
6	2'-6 1/2"	4'-4"	Double Hung	!!
7	2'-6 1/2"	4'-4"	Double Hung	!!
8	2'-6 1/2"	4'-4"	Double Hung	!!
9	2'-6 1/2"	4'-4"	Double Hung	EGRESS
10	2'-6 1/2"	4'-4"	Double Hung	!
1	2'-6 1/2"	4'-4"	Double Hung	!!
12	2'-6 1/2"	4'-4"	Double Hung	!!
13	2'-6 1/2"	4'-4"	Double Hung	!
14	2'-6 1/2"	4'-4"	Double Hung	1-1-
<u>ה</u>	つ'_ 6 1/2"	A'_A"	Double Hung	

MARK WD HGT GLAZING FIRE Not ATING NOT SIZE    1 6'-0" 7'-0"   TEMPERED     Tempered	DO	OR \		DOOR AND FRAME SCHE	ME	SCHEDUL
SIZE WD HGT GLAZING C 3'-0" 4'-6" 2'-6 1/4" 2'-8" 6'-8" 2'-6" 6'-8" 2'-6" 6'-8" 2'-8" 6'-8" 2'-8" 6'-8"		DC	OR			
WD HGT GLAZING RATING 6'-0" 7'-0" TEMPERED 3'-0" 6'-8" TEMPERED 4'-6" 6'-8" 2'-6 1/4" 6'-8" 2'-8" 6'-8" 2'-8" 6'-8" 2'-8" 6'-8"		SIZ	ΉÌ		FIRE	
0"       7'-0"       TEMPERED          0"       6'-8"       TEMPERED          6"       6'-8"           1/4"       6'-8"           8"       6'-8"           6"       6'-8"           8"       6'-8"           8"       6'-8"	MARK	VD	нст		RATING LABEL	NOTES
		2				l
0" 6'-8" TEMPERED - 6" 6'-8" 8" 6'-8" 6" 6'-8" 8" 6'-8"		6'-0"	7'-0"	TEMPERED		Tempered glass sidelites
6 6 6 8 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	2	3'-0"	6'-8"	TEMPERED	1	
1/4" 6'-8" 8" 6'-8" 6" 6'-8" 8" 6'-8"	3	4'-6"	6'-8"			
0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0	4	2'-6 1/4"	6'-8"		1	
5, 5, 6, 6, 6, 6, 6, 6, 6, 6, 6, 6, 6, 6, 6,	5	2'-8"	6'-8"			
6'-8"	6	2'-6"	6'-8"			
	7	2'-8"	6'-8"			

WINDOW NOTES:

Picture

CONTRACTOR SHALL VERIFY ALL WINDOW OPENINGS AND EGRESS REQUIREMENTS BEFORE ORDERING

ALL WINDOWS SHALL BE LOW E, ARGON FILLED INSULATING GLASS.

ALL WINDOWS TO HAVE A U-FACTOR RATING OF 0.30 OR BETTER.

ALL WINDOW GRILLES SHALL BE SIMULATED DIVIDED LITE.

ALL GLAZING SHALL CONFORM TO IRC 2009 R308

WINDOW GLAZING WITH SILL HTS LESS THAN 18" TO BE TEMPERED

WINDOW GLAZING 24" OR CLOSER TO DOORS SHALL BE TEMPERED.

WINDOW GLAZING 36" OR CLOSER TO STAIRWAYS AND 36" OR LESS ABOVE FLOOR SHA LL BE TEMERED.

WINDOW GLAZING WITHIN 60" OF THE BOTTOM OF A STAIRWAY AND LESS THAN 36" ABOVE THE FLOOR SHALL BE TEMPERED

OPENING TO 4". ALL WINDOWS WITH SILL HTS LESS THAN 24" AND MORE THAN 72" ABOVE GRADE TO HAVE OPENING LIMITERS TO RESTRICT

ALL WINDOWS SHALL CONFORM TO R312.2 WINDOW FALL PROTECTION

R310 EMERGENCY ESCAPE AND RESCUE OPENINGS

SLEEPING ROOMS SHALL HAVE AT LEAST ONE EGRESS WINDOW WITH A SILL HT OF NOT MORE THAN 44", A MINIMUM CLEAR OPENING HEIGHT OF 24" AND A MINIMUM CLEAR OPENING WIDTH OF 20"

DODGE **SCHEDULES & DETAILS** 

DRAWN BY: BB DATE 3.22.2017





