Location of Construction:	Owner:		Phone:	774-3268	Permit No:9 8 1 0 6 6
Owner Address:	Lessee/Buyer's Name:	Phone:	BusinessN		PERMIT ISSUED
Contractor Name:	Address:	Phor	201		Permit Issued:
Portland Builders, Inc.			9-0118		Permit Issued: SEP 2 2 1998
Past Use:	Proposed Use:	COST OF WOR \$ 6,000.0	0 9	PERMIT FEE:	CITY OF PORTLAND
		FIRE DEPT. □ Signature:	Denied	NSPECTION: Use Group: Type:	Zone: CBL:
Proposed Project Description:	·	PEDESTRIAN A	ACTIVITIES	DISTRICT (P.A.D.	
Int Reno/Sasement		Action:	Approved Approved wit Denied		Special Zone or Reviews: Shoreland Wetland Flood Zone Subdivision
Permit Taken By:	Date Applied For:	Signature:		Date:	☐ State Plan maj ☐minor ☐mm ☐
 Building permits do not include plumb Building permits are void if work is not tion may invalidate a building permit a 	started within six (6) months of the date			T ISSUED UIREMENTS	☐ Miscellaneous ☐ Conditional Use ☐ Interpretation ☐ Approved ☐ Denied Historic Preservation ☐ Not in District or Landmark ☐ Does Not Require Review ☐ Requires Review
I hereby certify that I am the owner of record authorized by the owner to make this applic if a permit for work described in the applica	ation as his authorized agent and I agree	sed work is authorized by to conform to all applicab	le laws of this	jurisdiction. In addit	Action: Approved Approved with Conditions Denied
areas covered by such permit at any reasona				,	Date:
SIGNATURE OF APPLICANT	ADDRESS:	ll Sept 98 DATE:	F	PHONE:	

BUILDING PERMIT REPORT

	01 Cast (CC
	ATE: 21 Sept 98 ADDRESS: 177 GLENWOOD AVE. 131-4-211
	EASON FOR PERMIT: In Temior renovalions
	UILDING OWNER: H. Sample
CC	ONTRACTOR: PTLD. Bldg. Inc.
PE	RMIT APPLICANT:
	E GROUP R-3 BOCA 1996 CONSTRUCTION TYPE 5 PS
	CONDITION(S) OF APPROVAL
Thi	is Permit is being issued with the understanding that the following conditions are met:
Apı	proved with the following conditions: *1, *12 * 16, *26, *21
1.	This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.
2.	Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services
	must be obtained. (A 24 hour notice is required prior to inspection)
2.5	Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing
	not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches
	beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not higher than the
	bottom of the base under the floor, and that the top of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used.
	the invert of the pipe or tile shall not be higher than the floor elevation. The top of joints or top of perforations shall be
	protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or
	crushed stone, and shall be covered with not less than 6" of the same material. Section 1813.5.2
2.6	Foundations anchors shall be a minimum of 1 1/2" in diameter. 7" into the foundation wall, minimum of 12" form corners of
	From corners of foundation and a maximum 6'o.c. between bolts. (Section 2305.17)
3.	Precaution must be taken to protect concrete from freezing. Section 1908.0
4.	It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is
_	done to verify that the proper setbacks are maintained.
5.	Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from
	adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire
	resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from
	the interior spaces and the artic area by means of 1/2 inch gypsum board or the equivalent applied to the garage means of 1/2
5.	inch gypsum board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996) All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA
٠.	National Mechanical Code/1993). Chapter 12 & NFPA 211
7.	Sound transmission control in residential building shall be done in accordance with Chapter 12 section 121±.0 of the city's
	building code.
3.	Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated
	walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower
	level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-
	1, I-2 M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such
	that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that
	would provide a ladder effect. (Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not be
	less than 30", but not more than 38".) Handrail grip size shall have a circular cross section with an outside diameter of at
	least 1 1/4" and not greater than 2". (Sections 1021 & 1022.0)
D.	Headroom in habitable space is a minimum of 7'6". (Section 1204.0)
J.	Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group minimum 11" tread. 7" maximum rise.(Section 1014.0)
l	The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6' 8") 1014.4
1. 2.X	Every sleeping room below the fourth story in buildings of use Groups R and I-1 shall have at least one operable window or
M	exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of
	special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height

not more than +1 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft. (Section 1018.6)

- Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units. Section 1010 1
- All vertical openings shall be enclosed with construction having a fire rating of at lest one (1)hour, including fire doors with self closer's. (Over 3 stories in height requirements for fire rating is two (2) hours.) Section 710.0
- 15. The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by providing automatic extinguishment. Table 302.1.1
 - All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 19, 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):
 - In the immediate vicinity of bedrooms
 - In all bedrooms

X16.

• In each story within a dwelling unit, including basements

In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required) Section 920.3.2

- 17. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. Section 921.0
- 18. The Fire Alarm System shall be maintained to NFPA #72 Standard.
- 19. The Sprinkler System shall maintained to NFPA #13 Standard.
- 20. All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023. & 1024. Of the City's building code. (The BOCA National Building Code/1996)
- 21. Section 25-135 of the Municipal Code for the City of Portland states. "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
- The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services.
- 23. Ventilation shall meet the requirements of Chapter 12 Sections 1210. Of the City's Building Code. (crawl spaces & attics)
- 42.4. All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade.
- 25. All requirements must be met before a final Certificate of Occupancy is issued,
- All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code. (The BOCA National Building Code/1996).
- 27. Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical Code/1993). (Chapter M-16)

28. 29.	Please read and implement the attached Land Ose-Zolling report requirements.	
30.		
31.		 · · · · · ·

·

Samual Hotists, Building Inspector

cc: Lt McDougall FD

Marge Schmuckal, Zoning Administrator

32.

LAND USE - ZONING REPORT

	ESS: 177 Glenwood Ave DATE: 9/18/98
REASC	ON FOR PERMIT: mtaion renovation
BUILE	ong owner: Herb & Cond Surplé-B-L: 131-K-219,23
PERM	IT APPLICANT: Portland Builders
	OVED: with conditions DENIED:
	45 49
	CONDITION(S) OF APPROVAL
1	During its existence, all aspects of the Home Occupation criteria, Section 14-410, shall be
2.	maintained. The footprint of the existing shall not be increased during maintenance
	reconstruction. All the conditions placed on the original, previously approved, permit issued on
٥,	are still in effect for this amendment.
4.	Your present structure is legally nonconforming as to rear and side setbacks. If you were to demolish the building on your own volition, you will <u>not</u> be able to maintain these same
	setbacks. Instead you would need to meet the zoning setbacks set forth in today's
	ordinances. In order to preserve these legally non-conforming setbacks,—you may only
(5)	rebuild the garage in place and in phases. This property shall remain a single family dwelling. Any change of use shall require a
3.)	separate permit, application for review and approval.
6.	Our records indicate that this property has a legal use of units. Any change
-	in this approved use shall require a separate permit application for review and approval.
7. 8-	Separate permits shall be required for any signage. Separate permits shall be required for future decks and/or garage. Addita
(,0)	The state of the s
	dwelling unit. No Additional Kitchen equipment SMI
	be wstalled
Ť	
١.	
	Marge Schmuckal, Zoning Administrator,
-0	Asst. Chief of Code Enforcement

THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

Building or Use Permit Pre-Application Additions/Alterations/Accessory Structures

To Detached Single Family Dwelling

In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or Use Permit.

NOTE**If you or the property owner owes real estate or personal property taxes or user charges on any property within the City, payment arrangements must be made before permits of any kind are accepted.

ordy, pay ment at tangements	made be made before permits of any kind are	accepted.		
Location/Address of Construction: 177 GLENWOOD NENUE PORTLAND				
		,		
Tax Assessor's Chart, Block & Lot Number	Owner: HERB & CAROL	Telephone#:		
Chart# 13 / Block# / Lot# 021	SEMPLE	774-3268		
Owner's Address: 177 G WENWOOD	Lessee/Buyer's Name (If Applicable)	Cost Of Work: Fee		
PORTLAND, ME		\$600000 \$ 50		
Proposed Project Description:(Please be as specific as possible)				
FINISH A ROOM IN BASE	MENT & SMALL AMOUNT A	ENDU. TO HACCUA		
Contractor's Name, Address & Telephone	D BOX 4902 879-01/8 Rec'd	1By:		
CORTLAND BULDERS INC 1	PORTLAND ME 0411 >	IVI		
Separate permits are required for Internal & External Plumbing, HVAC and Electrical installation. •All construction must be conducted in compliance with the 1996 B.O.C.A. Building Code as amended by Section 6-Art II. •All plumbing must be conducted in compliance with the State of Maine Plumbing Code. •All Electrical Installation must comply with the 1996 National Electrical Code as amended by Section 6-Art III. •HVAC(Heating, Ventilation and Air Conditioning) installation must comply with the 1993 BOCA Mechanical Code. You must Include the following with you application: 1) A Copy of Your Deed or Purchase and Sale Agreement 2) A Copy of your Construction Contract, if available 3) A Plot Plan (Sample Attached) If there is expansion to the structure, a complete plot plan (Site Plan) must include • The shape and dimension of the lot, all existing buildings (if any), the proposed structure and the distance from the actual property lines. Structures include decks porches, a bow windows cantilever sections and toof evertances, as well as, sheds, pools, garages and any other accessory structures.				
Scale and required zoning district setbacks				
4) Build	ding Plans (Sample Attached)			

A complete set of construction drawings showing all of the following elements of construction:

- Cross Sections w/Framing details (including porches, decks w/ railings, and accessory structures)
- Floor Plans & Elevations
- Window and door schedules
- Foundation plans with required drainage and dampproofing
- Electrical and plumbing layout. Mechanical drawings for any specialized equipment such as furnaces, chimneys, gas equipment, HVAC equipment (air handling) or other types of work that may require special review must be included.

Certification

I hereby certify that I am the Owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his/her authorized agent. I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in this application is issued, I certify that the Code Official's authorized representative shall have the authority to enter all areas covered by this permit at any reasonable hour to enforce the provisions of the codes applicable to this permit.


Signature of applicant: Jahrah Curaman Date: 9-9.98	
---	--

Building Permit Fee: \$25.00 for the 1st \$1000.cost plus \$5.00 per \$1,000.00 construction cost thereafter.

O:\INSP\CORRESP\MNUGENT\APADSFD.WPD

d

Semple Presidence 177 Glenwood Aue Portland, ME



MAIN FLOOR NO SCALE REMOVE SHELVING,
RELOCATE DOOR

NEW LIGHT (BY OWNER INSTALL BY CONT,

NEW WOOD OVER YAT TO

WADD - LEVEL AS

REQ'O
REWILL SWITCH

