



**GENERAL PLAN NOTES**  
1. ALL INTERIOR PARTITION TYPES ARE M7 TYPE UNLESS NOTED OTHERWISE. SEE STRUCTURAL DRAWINGS FOR INTERIOR CMU LOAD BEARING WALLS. ALL OTHER PARTITION TYPES ARE RUNNING BOND UNLESS OTHERWISE NOTED.  
2. REFER TO ALL DRAWINGS INCLUDING ARCHITECTURAL, CIVIL, STRUCTURAL, MECHANICAL, ELECTRICAL AND PLUMBING DRAWINGS FOR ADDITIONAL GENERAL NOTES, ABBREVIATIONS AND SYMBOLS.  
3. ALL DRAWINGS ARE OF EQUAL IMPORTANCE IN DEFINING THE WORK OF THE CONTRACT DOCUMENTS. DISCREPANCY WITHIN AND BETWEEN THE DRAWINGS SHALL BE RESOLVED BY THE ARCHITECT PRIOR TO INSTALLATION OF SAID WORK. ANY WORK SHOWN ON THESE DRAWINGS WHICH IS NOT SHOWN ON THE CONTRACT DOCUMENTS SHALL BE CONSIDERED AT ITS EXPENSE AND AT NO ADDITIONAL COST TO OWNER OR ARCHITECT.  
4. DO NOT SCALE DRAWINGS. THE DRAWINGS ARE NOT NECESSARILY TO SCALE. USE GIVEN DIMENSIONS. DIMENSIONS AT THE JOB SITE PRIOR TO THE START OF CONSTRUCTION. IF DISCREPANCIES ARE FOUND, NOTIFY ARCHITECT IMMEDIATELY. ALL DIMENSIONS ARE GIVEN TO FACE OF STUD. FACE OF MASONRY OR FACE OF CONCRETE. ALL DIMENSIONS ARE GIVEN TO FACE OF PARTITION TYPES FOR EXACT CONSTRUCTION.  
5. LOCATE DOOR FRAMES IN MASONRY CONSTRUCTION ON THE SIDE OF THE WALL TOWARD THE ROOM WHICH THE DOOR SWINGS INTO UNLESS OTHERWISE NOTED.  
6. PROVIDE BULLNOSE OUTSIDE VERTICAL CMU CORNERS AT CONDITIONS WITH EXPOSED MASONRY UNLESS OTHERWISE NOTED.  
7. SEE SHEET G003 AND G004 FOR REFERENCE PLAN DIMENSIONS. ALL FINISHED FLOORS AND SPACES SHALL BE MECHANICALLY FLEETED AND FINISHED THROUGHOUT THROUGH FIRE RATED CONSTRUCTION SHALL BE SLEAVED AND FIRE SAVED AND/OR HAVE FIRE DAMPERS THROUGH THE JOINT. FIRE RATINGS OF THE CONSTRUCTION.  
8. ALL PITCHED ROOF AREAS SHOWN WITH PITCH LINES SHALL SLOPE AT 1/4" PER FOOT UNLESS OTHERWISE NOTED. PROVIDE A SLAB DEPRESSION AT ALL FLOOR DROPS WHERE PITCH LINES ARE NOT SHOWN ON PLANS.  
9. DETAILS NOT SHOWN ARE SIMILAR IN CHARACTER TO DETAILS SHOWN. WHERE SPECIFIC DIMENSIONS, DETAILS OR CONDITIONS ARE NOT SHOWN, REFER TO ALL ARCHITECT BEFORE PROCEEDING WITH THE WORK. UNLESS OTHERWISE NOTED.  
10. FINISH FLOOR ELEVATIONS ARE TO TOP OF CONCRETE UNLESS OTHERWISE NOTED.  
11. WHEN UNDIMENSIONED DOORS APPEAR IN PARTITIONS, THE DOOR WIDTH AND DOOR FRAME DETAILS DETERMINE THE LOCATION OF THE DOORS AND PARTITIONS. SEE DETAIL N1 SHEET A507 FOR TYPICAL SPACING.  
12. FINISH FLOOR ELEVATIONS FOR DIMENSIONS OF STAIRS, TOILETS AND ELEVATOR SHIPTS UNLESS OTHERWISE NOTED.  
13. ELEVATOR SUBCONTRACTOR SHALL ASSIST G.C. AND VERIFY OPENINGS PRIOR TO FORMING. NOTIFY ARCHITECT OF ANY MODIFICATIONS PRIOR TO FORMING.  
14. CONTRACTOR SHALL PROVIDE STIFFENERS, BRACING, BACKING PLATES AND SUPPORTING BRACKETS REQUIRE FOR ALL TOILET ROOMS, TOILET PARTITIONS AND TOILET ROOM ACCESSORIES. TOILET PARTITIONS AND MISCELLANEOUS EQUIPMENT WHETHER SUCH SUPPORTS ARE SHOWN OR NOT.  
15. INSTALL ALL RECESSED CABINETS, PANELS, BOXES LOCATED IN FIRE RATED PARTITIONS TO MAINTAIN THE FIRE RATED CONSTRUCTION.  
16. ALL HOUSEKEEPING CONCRETE PADS ARE TO BE 4" HIGH MINIMUM UNLESS OTHERWISE NOTED.  
17. G.C. SHALL COORDINATE ALL EQUIPMENT BASE AND ELECTRICAL CONTRACTORS. INSTALL THE PADS AND BENEATH THE FULL PROJECTED AREA OF EQUIPMENT.  
18. G.C. SHALL COORDINATE ALL MECHANICAL AND ELECTRICAL FLOOR, ROOF AND WALL SLEEVES AND ALL MECHANICAL SHEETS WITH MECHANICAL PLUMBING FIR ARCHITECTURAL DRAWINGS.  
19. REFER TO MECHANICAL AND ELECTRICAL CONTRACTORS DRAWINGS AND MANUFACTURERS TEMPLATE DRAWINGS FOR ALL MECHANICAL AND ELECTRICAL EQUIPMENT. ISOLATIONS, SPRINGS ISOLATION, ETC. NOT SHOWN ON THE DRAWINGS.

