

WOOD FRAMING:

Dimension Lumber is designed and shall be supplied using BASE VALUES Design Criteria.

Spruce-Pine-Fir #2 and better (Maximum Moisture Content 19%) U.O.N.

"Pressure treated lumber" shall be framing material of the specified species which has been pressure treated with a decay and insect resistant solution, meeting all current standards for wood in contact with

Sill plates in contact with masonry or concrete foundations, footings or slabs may be treated Timber Strand LSL (zinc borate treatment). Sodium borate treatment may also be acceptable for sill plate applications when protected from weather.

Acceptable treatment mediums for wood in contact with earth or in exterior applications include ACQ-C and ACQ-D (Alkaline Copper Quaternary) and copper azole (CBA-A and CBA-B).

DO NOT USE WOODS WHICH HAVE BEEN TREATED WITH AMMONIA BASED CARRIERS.

All connectors shall meet the recommendations of the pressure treated wood manufacturer, but shall be not less than Hot Dipped Galvanized meeting requirements of ASTM A653, such as Simpson ZMAX. (G185). All screws, nails and bolts shall match hangers and other connectors, and shall meet ASTM A123 for individual connectors, and ASTM A153 for fasteners.

For durability, it is our recommendation that connectors used in exposed conditions with treated lumber be stainless steel.

Do not mix galvanized and stainless products.

Do not allow aluminum to contact treated wood.

Laminated Veneer Lumber (LVL): Manufactured 1 3/4" wide Microllams (ML) by Trus Joist or

Fb=2,600 psi, E=1,900,000 psi, Fv=285 psi, depth noted on plans.

Minimum nailing shall comply with IBC Table 2304.9.1 except where more or larger nailing shown on

Metal connectors: Simpson Strong Tie unless otherwise noted, installed with number and type of nails to achieve maximum rated capacity. Note that heavy duty and skewed hangers may require special order.

All beams shall be braced against rotation at points of bearing.

Drypack grout all beam pockets full after beams are set.

Lead holes for lag bolts shall be 60% to 70% of lag shank diameter in compliance with AITC criteria.

STRUCTURAL ERECTION AND BRACING REQUIREMENTS

The structural drawings illustrate the completed structure with all elements in their final positions, properly supported and braced. The contractor, in the proper sequence, shall provide proper shoring and bracing as may be required to achieve the final completed structure.

These plans have been engineered for construction at one specific building site. Builder assumes ALL responsibility for use of these plans at Any Other building site. Plans shall not be used for construction at any other building site without specific review by the engineer.

Observations of foundation reinforcing or framing required by the owner, lender, insurer, building department or any other party will be accomplished by the engineer at the owner's expense. At least 24 hours advance notice is requested.

All slabs on grade shall be separated from adjacent structural and finish elements to allow free movement of the slab, unless specifically shown and noted otherwise.

ABBREVIATIONS KEY BRG **BEARING** CLR CLEAR **CMU** CONCRETE MASONRY UNIT COL **COLUMN** CONC CONCRETE CONN CONNECTION DWG **DRAWING** EA **EACH EACH SIDE** (E) EXISTING, BLUE GALV **GALVANIZED** LOC LOCATION LAMINATED VENEER LVL LUMBER NTS NOT TO SCALE NEW , RED (N) PT, P.T. PRESSURE TREATED (R) REMOVE SIM SIMILAR SQ **SQUARE** T&B TOP AND BOTTOM TYP TYPICAL UNLESS NOTED UNO OTHERWISE WA WEDGE ANCHOR

KERZUNER-FLEISGTructural Int. MKL SI 4/12/17

Portland, ME, 04101 p. 207-774-4614 f. 866-793-7835

BUILD WITH CONFIDENCE


SI# 17-0088

GENERAL REPAIR NOTES:

- CONTRACTOR TO SHORE FRAMING AS NEEDED TO MAKE
- NOTIFY ENGINEER OF ANY DISCREPANCIES FOUND IN FIELD.

FRAM	ING PLAN SYMBOLS KEY
	WOOD OR STEEL POST/COLUMN NUMBER OF WOOD STUDS IN POST BELOW
A/B/C	COLUMN (ABOVE, BELOW, CONTINUOUS) AT THIS LEVEL
(E) / (N)	EXISTING / NEW (N) JOIST BEARING
	(E) JOIST BEARING (N) CONTINUOUS JOIST WITH INTERMEDIATE BEARING
7	(E) CONTINUOUS JOIST WITH INTERMEDIATE BEARING (N) FLUSH FRAMED JOIST BEARING WITH HANGER
m	(E) JOIST W/ (N) FLUSH HANGER
NOT	(N) BEARING WALL BELOW (N) SHEATHING /SHEAR WALL
NOT	INDICATES 2x6 @ 16" O.C. OVERFRAMED CRICKET ON EXISTING ROOF BEARING ON 2x PLATES AND STUB BEARING WALLS @ 48" O.C. MAX.
(#)T (#)K	NUMBER OF TRIM STUDS UNDER HEADER NUMBER OF KING STUDS ADJACENT TO HEADER

LEGEND	
DROPPED BEAM	
FLUSH BEAM	





Fleisch Herzlinger Propose

	X
r / Framing Plan	DRW / CHK BY: AEP /
sed 1st Floor	04/20/17
ĕ	


DWG SCALE:

01-21-17

KW Archit	Kristi Kenne	PO Box 404	Wells, Main	2 555 (505)
ST	EC.	TIH	SKC	\









2nd Floor / Framing Fleisch Herzlinger Proposed



Plan


줒

DRW / CHK BY:

01-21-17

PROJECT #









KW Arc	Kristi Ke	PO Box 4	Wells, M.	i co
ST	EC	LIH	BC	1






DRW / CHK BY: 01-21-17

PROJECT #

DWG SCALE:

AEP / KK 1/8" = 1'-0"






Herzlinger - Fleisch Proposed Elevations

DATE:	04/20/17	DRW / CHK BY:	AEP /	춪
PROJECT #	01-21-17	DWG SCALE:	1/8" = 1'-0"	0-

KW Architects	Kristi Kenney, RA	PO Box 404	Wells, Maine 0409	0010 555 (500)
ST	.EC	TIH	BC	A










춪	.0-
AEP /	1/8" = 1'-0"
DRW / CHK BY:	DWG SCALE:
04/20/17	01-21-17
ATE:	ROJECT#



STOBLIHOMA









1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1				
DATE:	04/20/17	DRW / CHK BY: AEP /	AEP /	KK
PROJECT #	01-21-17	DWG SCALE:	1/8" = 1'-0"	-0

KW Arc	Kristi Ke	PO Box 4	Wells, M.	(,,,,,,,,
ST	EC.	TIH	SEC.	\forall











줒


AEP

DRW / CHK BY: DWG SCALE:

01-21-17

PROJECT #

Fleisch **Building Section** Herzlinger







Herzlinger - Fleisch

Existing 1st Floor Plan

	/ KK	1/8" = 1'-0"
	AEP	1/8":
5	DRW / CHK BY: AEP /	DWG SCALE:
	04/20/17	01-21-17
	DATE:	PROJECT #

(W Architects (risti Kenney, RA 20 Box 404 Mells, Maine 040 207) 332-9199	
ARCHITECTS \$ 5 & 5	









Fleisch Herzlinger

Existing 2nd Floor Plan

	KK	.0-
	AEP /	1/8" = 1'-0"
	DRW / CHK BY:	DWG SCALE:
	04/20/17	01-21-17
)	TE:	JECT#










•	DRW / CHK BY:	DWG SCALE:	
Existing Elevations	04/20/17	01-21-17	
l fillisix =	DATE:	PROJECT #	

AEP / KK 1/8" = 1'-0"

KW Architects	Kristi Kenney, RA	PO Box 404	Wells, Maine 0409	(207) 332-9199
ST	.EC	LIH	KC	A








Herzlinger - Fleisch Existing Elevations

04/20/17	DRW / CHK BY:	AEP /	축
01-21-17	DWG SCALE:	1/8" = 1'-0"	0-

KW Architects	Kristi Kenney, RA	Wells, Maine 04090 (207) 332-9199
ST	DELL	РВСН










•				
DATE:	04/20/17	DRW / CHK BY:	AEP / K	X
PROJECT #	01-21-17	DWG SCALE:	1/8" = 1'-0"	(

KW Architects	Kristi Kenney, RA	PO Box 404	Wells, Maine 0409	0010 555 (700)
ST	.EC	LIH	BC	A







Fleisch Herzlinger -

	X	<u>.</u> -0.
	AEP /	1/8" = 1'-0"
	DRW / CHK BY:	DWG SCALE:
	04/20/17	01-21-17
,	DATE:	PROJECT #



STOBLIHOMA

KW Architects



