



CONCRETE SIZE & REINFORCEMENT SCHEDULE			
MARK	TYPE	SIZE	REINFORCING
TYPICAL	TYPICAL FND WALL UNO	8" WIDE x CONT.	(2) #5 CONT. TOP AND BOT -TYP #4 HORIZ @ 18" #4 VERT @ 16" SEE SECTION A/S2.1
	TYPICAL CONT FOOTING UNO	20" WIDE x 8" THICK x CONT.	(2) #4 CONT.
WG1	GARAGE FND WALL UNO	8" WIDE x CONT.	(2) #5 CONT. TOP AND BOT -TYP #4 HORIZ @ 18" #4 VERT @ 32" SEE SECTION A/S2.1
F4.5	ISOLATED FTG	4'-6" SQ. x 10" THICK	#4 @ 12" O.C. E.W. MID DEPTH

- MARK "T" DENOTES THE TYPICAL CONCRETE FOOTING AND FOUNDATION WALL SIZE AND REINFORCING FOR THE PLAN SHOWN.
- ADDITIONAL REINFORCING IS ALSO INDICATED IN PLANS AND SECTION

Bild Architecture
 PO Box 8235
 Portland, ME
 04104
 207.408.0168
 evan@bildarchitecture.com

STATE OF MAINE
 AARON C. JONES
 No. 10966
 LICENSED PROFESSIONAL ENGINEER
 Mar 11th, 2016

PROJECT NO.
15002
 PROJECT NAME
15 WALTON STREET
PORTLAND, ME

REVISIONS

1	4/18/14
2	
3	
4	
5	

FOR PERMIT SET

DRAWN BY
MKL
 SHEET TITLE
Foundation Plan

ISSUE DATE
3/11/15
 SHEET SCALE
1/4" = 1'-0"

S
S1.1

Structural Integrity
 Consulting Engineers, Inc.
 BUILD WITH CONFIDENCE
 SI # 15-0042

77 Oak Street
 Portland, ME, 04101
 p. 207-774-4614
 f. 866-793-7835
 www.structuralinteg.com