

NAC Circuit Voltage Drop Calculation

Project Name	CMP- Portland Service Center		
Date	2/6/2017		
Circuit Number	Nac#1		
Area Covered			
NAC Source Alarm Voltage	19.1	Wire Gauge 14	Resistance Per Kft Cable 3.14
Minimum Device Voltage	16		
Distance to first appliance	20		
Total Circuit Current	1.135		

Wire Gauge for balance of circuit	14	3.14
-----------------------------------	----	------

	Device Current	Distance from previous device	Voltage at Device	Drop from source	Percent Drop
Circuit is within limits					
Appliance 1	0.167		19.03	0.07	0.4%
Appliance 2	0.281	60	18.85	0.25	1.3%
Appliance 3	0.281	75	18.68	0.42	2.2%
Appliance 4	0.125	25	18.65	0.45	2.3%
Appliance 5	0.281	100	18.56	0.54	2.8%
END			18.56	0.54	2.8%
END			18.56	0.54	2.8%
END			18.56	0.54	2.8%
END			18.56	0.54	2.8%
END			18.56	0.54	2.8%
END			18.56	0.54	2.8%
END			18.56	0.54	2.8%
END			18.56	0.54	2.8%
END			18.56	0.54	2.8%
END			18.56	0.54	2.8%
END			18.56	0.54	2.8%
END			18.56	0.54	2.8%
END			18.56	0.54	2.8%
END			18.56	0.54	2.8%
END			18.56	0.54	2.8%
END			18.56	0.54	2.8%
END			18.56	0.54	2.8%
END			18.56	0.54	2.8%
END			18.56	0.54	2.8%
END			18.56	0.54	2.8%
END			18.56	0.54	2.8%
END			18.56	0.54	2.8%
END			18.56	0.54	2.8%
END			18.56	0.54	2.8%
END			18.56	0.54	2.8%
END			18.56	0.54	2.8%
END			18.56	0.54	2.8%
Totals	1.135	280			

Appliance circuit voltage drop calculations start at "end of battery life" as NAC Source Alarm Voltage and use 20% below nameplate rating for Minimum Appliance Voltage.

Note. Wire resistance is based on the 2014 NEC Table 8 Uncoated DC resistance. All resistance is based on solid conductors