

NAC Circuit Voltage Drop Calculation

Project Name	CMP- Portland Service Center		
Date	2/6/2017		
Circuit Number	Nac#3		
Area Covered			
NAC Source Alarm Voltage	19.1	Wire Gauge	Resistance
Minimum Device Voltage	16	14	Per Kft Cable
Distance to first appliance	150		3.14
Total Circuit Current	1.252		

Wire Gauge for balance of circuit	14	3.14
-----------------------------------	----	------

	Device Current	Distance from previous device	Voltage at Device	Drop from source	Percent Drop
Circuit is within limits					
Appliance 1	0.179		18.51	0.59	3.1%
Appliance 2	0.125	50	18.34	0.76	4.0%
Appliance 3	0.316	35	18.24	0.86	4.5%
Appliance 4	0.316	40	18.16	0.94	4.9%
Appliance 5	0.316	75	18.08	1.02	5.3%
END			18.08	1.02	5.3%
END			18.08	1.02	5.3%
END			18.08	1.02	5.3%
END			18.08	1.02	5.3%
END			18.08	1.02	5.3%
END			18.08	1.02	5.3%
END			18.08	1.02	5.3%
END			18.08	1.02	5.3%
END			18.08	1.02	5.3%
END			18.08	1.02	5.3%
END			18.08	1.02	5.3%
END			18.08	1.02	5.3%
END			18.08	1.02	5.3%
END			18.08	1.02	5.3%
END			18.08	1.02	5.3%
END			18.08	1.02	5.3%
END			18.08	1.02	5.3%
END			18.08	1.02	5.3%
END			18.08	1.02	5.3%
END			18.08	1.02	5.3%
END			18.08	1.02	5.3%
END			18.08	1.02	5.3%
END			18.08	1.02	5.3%
END			18.08	1.02	5.3%
Totals	1.252	350			

Appliance circuit voltage drop calculations start at "end of battery life" as NAC Source Alarm Voltage and use 20% below nameplate rating for Minimum Appliance Voltage.

Note. Wire resistance is based on the 2014 NEC Table 8 Uncoated DC resistance. All resistance is based on solid conductors