Location of Construction: 424 Ocean Ave	Owner: Payson Park Evans	gelical Free Church	Phone: n 774–4054	Permit No:	
Owner Address: SAA	Lessee/Buyer's Name:	Phone:	BusinessName:		
Contractor Name: The Signery	Address:	Phone:		Permit Issued:	
Past Use:	Proposed Use:	COST OF WORK:	PERMIT FEE: \$ 30.00		
Church		FIRE DEPT. □ A _F □ De	pproved INSPECTION: use Group: Type:	Zone: CBL: 159-B-018	
Proposed Project Description:		Action: Ap	Signature: TIVITIES DISTRICT (P.A.D. oproved		
Replace existing sign by tearing down old structure & building new one		Approved with Conditions: Denied Signature: Date:		☐ Shoreland ☐ Wetland ☐ Flood Zone ☐ Subdivision	
Permit Taken By: S.P.	Date Applied For:	29 May 1998		☐ Site Plan maj ☐minor ☐mm ☐ Zoning Appeal	
2. Building permits do not include plumb	started within six (6) months of the date of i			☐ Variance ☐ Miscellaneous ☐ Conditional Use ☐ Interpretation ☐ Approved ☐ Denied	
12 D	ip Vandette eering Rd am, ME 04038			Historic Preservation ☐ Not in District or Landmark ☐ Does Not Require Review ☐ Requires Review Action:	
I hereby certify that I am the owner of record authorized by the owner to make this application if a permit for work described in the application areas covered by such permit at any reason	ation as his authorized agent and I agree to tion is issued, I certify that the code official	conform to all applicable l's authorized representative	aws of this jurisdiction. In addit e shall have the authority to ente	ion, Denied	
SIGNATURE OF APPLICANT	ADDRESS:	02 June 1998 DATE:	PHONE:		
		<u>_</u> .			
RESPONSIBLE PERSON IN CHARGE OF	WORK, TITLE	i i	PHONE:	CEO DISTRICT	

Cold leat lettering.

Primary sign i sweed w/

Primary sign i sweed w/ 24" ×96" (3) 12" ×36" illumination

	BUILDING PERMIT REPORT
DATE	: 4 June 98 ADDRESS: 424 O Cean AVC. (159-B-Ø18)
REAS	ON FOR PERMIT: replace sign -
BUIL	DINGOWNER: Pay 500 Park Fuange/Ical Free Church
CONT	rictor: The Signery
	IIT APPLICANT:
USE G	BOCA 1996 CONSTRUCTION TYPE
	CONDITION(S) OF APPROVAL
This F	Permit is being issued with the understanding that the following conditions are met:
Appro	oved with the following conditions: X1, 82, *24 × 30
-1. 2.	This permit does not excuse the applicant from meeting applicable State and Federal rules and laws. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be abbrical.
3.	obtained. (A 24 hour notice is required prior to inspection) Precaution must be taken to protect concrete from freezing.
4.	It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to
_	verify that the proper setbacks are maintained.
5.	Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996)
6.	All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993).
7.	Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214.0 of the city's building code.
8.	Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not be less than 30", but not more than 38".) Handrail grip size shall have a circular cross section with an outside diameter of at least 1 1/4" and not greater than 2".
9.	Headroom in habitable space is a minimum of 7'6".
10.	Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group minimum 11" tread, 7" maximum rise.
11.	The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8")
12.	Every sleeping room below the fourth story in buildings of use Groups R and I-1 shall have at least one operable window or
	exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm),

Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it

All vertical openings shall be enclosed with construction having a fire rating of at lest one (1)hour, including fire doors with self

The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by providing

All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the

exits directly from the apartment to the building exterior with no communications to other apartment units.

closer's. (Over 3 stories in height requirements for fire rating is two (2) hours.)

and a minimum net clear opening of 5.7 sq. ft.

automatic extinguishment.

13.

14.

15.

16.

provisions of the City's Building Code Chapter 9, Section 19, 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):

- In the immediate vicinity of bedrooms
- In all bedrooms
- In each story within a dwelling unit, including basements

In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required)

- 17. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type.
- 18. The Fire Alarm System shall be maintained to NFPA #72 Standard.
- 19. The Sprinkler System shall maintained to NFPA #13 Standard.
- 20. All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023. & 1024. Of the City's building code. (The BOCA National Building Code/1996)
- Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
- 22. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services.
- 23. Ventilation shall meet the requirements of Chapter 12 Sections 1210. Of the City's Building Code.
- (24. All electrical plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade.
- 25. All requirements must be met before a final Certificate of Occupancy is issued.
- All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code. (The BOCA National Building Code/1996).
- 27. Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical Code/1993).

	Procedured Code (333).
28.	Please read and implement the attached Land Use-Zoning report requirements.
29.	No more sign Dermit will be issued to you without a structural
	No more sign permit will be issued to your without a structural detail of the sign - Please submit this 18 formation to this office
% .	before work beging -
	· · · · · · · · · · · · · · · · · · ·
31.	
32.	

cc: Lt McDougall, PFD

Enførcement

Marge Schmuckal

SIGNAGE

PLEASE ANSWER ALL QUESTIONS

zone:

Single Te	nant Lot?: Yes	No			
	int Lot?: Yes				
			N	n to t	
	ng (Ext pole sign				× ×O ¬
More than	(1) one sign?: Y	esNO _	Dime	ensions	
Brad Mart	sign (att to bldg)? Yes	NO	Drwenaroua	
List all e					
	6 Height	5 8 lena	<u>, L</u>	width	
	<u>_</u>				
		ı	-		
Lot Fronta	ge(feet):	Ten	ant Fronta	age(feet):	•
Lot Fronta	ge(feet):			age(feet):	· · · · · · · · · · · · · · · · · · ·
Lot Fronta	ge(feet):	Ten		age(feet): _	
Lot Fronta Awning?:		AWNINGS	5		
Awning?:	YesNo	AWNINGS	s ning Backl	it?: Yes	ио
Awning?: Is there a	Yes No ny. comunication, r	AWNINGS	s ning Backl	it?: Yes	ио
Awning?:	Yes No ny. comunication, r	AWNINGS	s ning Backl	it?: Yes	ио
Awning?: Is there a	Yes No ny. comunication, r	AWNINGS	s ning Backl	it?: Yes	ио
Awning?: Is there a Height of	Yes No ny comunication, r Awning?:	AWNINGS IS AWN Nessage, traden .	ning Backl nark or sy	it?: Yes mbol on aẃni	.ng?
Awning?: Is there a Height of PLEASE NOT	Yes No ny comunication, r Awning?:	AWNINGS IS AWN Nessage, traden signs on the P	ning Backl mark or sy	it?: Yes mbol on aẃni	ฟo .ng?
Awning?: Is there a Height of PLEASE NOT	Yes No ny. comunication, r Awning?: E: Approvals for	AWNINGS IS AWN Nessage, traden signs on the P	ning Backl mark or sy	it?: Yes mbol on aẃni	.ng?
Awning?: Is there a Height of PLEASE NOT COME under ALSO: See	Yes No ny comunication, r Awning?: E: Approvals for different require reverse side for	AWNINGS IS AWN nessage, traden signs on the Poments and regulational inf	ning Backl mark or sy Tublic Sid lations.	it?: Yesmbol on awniewalk and telegricement:	ng?
Awning?: Is there a Height of PLEASE NOT: come under ALSO: See	Yes No ny comunication, rewerse side for speeded for signage	AWNINGS IS AWN nessage, traden signs on the Pomonts and regulational info	ning Backl mark or sy ublic Sid lations.	it?: Yesmbol on awniewalk and teleguirement:	ng?
Awning?: Is there a Height of PLEASE NOT: Come under ALSO: See	Yes No ny comunication, rewerse side for speeded for signage	AWNINGS IS AWN nessage, traden signs on the Pomonts and regulational info	ning Backl mark or sy ublic Sid lations.	it?: Yesmbol on awniewalk and teleguirement:	ng?
Awning?: Is there a Height of PLEASE NOT: Come under ALSO: See	Yes No ny comunication, r Awning?: E: Approvals for different require reverse side for	AWNINGS IS AWN nessage, traden signs on the Pomonts and regulational info	ning Backl mark or sy ublic Sid lations.	it?: Yesmbol on awniewalk and teleguirement:	ng?

Circuity Existing (proposed sign lac.

The portion