

DOOR SCHEDULE

NUMBER	TYPE	MAKE	MODEL	WIDTH	HEIGHT	PAIR	THICKNESS	FINISH	REMARKS
E1		WOOD-ULTREX INTEGRITY	INSWING FRENCH DOOR IIF03068XL	3'-0"	6'-8"		1 3/4"	PAINT	
2		TBD	TBD	2'-4"	6'-8"		1 3/8"	PAINT	
3		TBD	TBD	3'-0"	6'-8"		1 3/8"	PAINT	POCKET DOOR
4		TBD	TBD	3'-0"	6'-8"		1 3/8"	PAINT	
5		TBD	TBD	2'-8"	6'-8"		1 3/8"	PAINT	
6		TBD	15 LITE FRENCH DOORS	6'-0"	6'-8"	X	1 3/8"	PAINT	

DOOR NOTES:

1. THE CONTRACTOR SHALL PROVIDE DOORS OF TYPES AND SIZES AS NOTED BY THE DRAWINGS AND DOOR SCHEDULE.
2. ALL GLAZING SHALL BE DOUBLE-Pane, LOW E INSULATING GLASS WITH A CENTER "U" VALUE OF 0.40 (MINIMUM).
3. CONTRACTOR MUST CONFIRM ALL SIZES, ROUGH OPENING DIMENSIONS, AND INSTALLATION DETAILS BEFORE COMMENCING CONSTRUCTION. NOTIFY ARCHITECT OF ANY DISCREPANCIES BEFORE PROCEEDING AND/OR ORDERING DOORS.
4. ALL EXTERIOR DOORS SHALL BE PRE-HUNG AND MUST BE SHIMMED, FLASHED, INSULATED, CAULKED WITH POLYURETHANE ADHESIVE CAULK, AND SEALED AGAINST AIR INFILTRATION TO THE HIGHEST QUALITY OF WORKMANSHIP AND MATERIALS.
5. ALL INTERIOR DOORS SHALL BE PRE-HUNG WITH DOUBLE-RABBETTED SOLID FRAMES (NOT SPLIT JAMBS) AND MUST BE INSTALLED TO THE HIGHEST QUALITY OF MANUFACTURERS SPECIFICATIONS.
6. ALL INTERIOR DOORS MUST BE DEFECT FREE, SOLID, ULTRA-LOW VOC MDF DOORS.

