CITY OF PORTLAND, MAINE RESURGAM
Reviewed for Code Compliance
Inspections Division
Approved with Conditions
Date: 04/21/17

ABBREVIATIONS

AB	Anchor Bolts
BO	By Others
BS	Both Sides
CL	Centerline
CLR	Clear Distance
COL	Column
CONC	Concrete
CONT	Continuous
CIP	Cast-In-Place
DIA	Diameter
EB	Expansion Bolt
EMBT	Embedment
EA	Each
EQ	Equal
EXG	Existing
FDN	Foundation
FF	Finish Floor
FT	Feet
FTG	Footing
GA	Gauge
GC	General Contractor
GALV	Hot-Dip Galvanized
HORIZ	Horizontal
IN.	Inches
MAX	Maximum
MIN	Minimum
NTS	Not To Scale
N&W	Nut and Washer
O.C.	On Center
OPNG	Opening
PL	Plate
PT	Pressure Treated
RO	Rough Opening
REQ'D	Required
SCH	Schedule
SIM	Similar
SPECS	Specifications
SS	Stainless Steel
SYP	Southern Yellow Pine
TOF	Top of Footing Elevation
TOW	Top of Wall Elevation
T & B	Top and Bottom
TYP	Typical
UON	Unless otherwise noted
VERT	Vertical
W/	With
VIF	Verify in Field
16d	16 Penny Nail
@	At
&	And