1/4" = 1'-0"

SMOKE ALARMS

SHALL BE INTERCONNECTED & INSTALLED IN THE FOLLOWING LOCATIONS

- 1. EACH SLEEPING AREA
- 2. OUTSIDE EACH SEPARATE SLEEPING AREA IN THE IMMEDIATE VICINITY OF THE BEDROOMS
- 3. ON EACH ADDITIONAL STORY OF THE DWELLING INCLUDING BASEMENTS
- 4. FIRE SEPARATION PER TOWN AND LOCAL CODE WHEN REQUIRED
- * <u>EGRESS WINDOWS</u>

CARBON MONOXIDE ALARMS;

SHALL BE INSTALLED IN THE FOLLOWING LOCATIONS

- OUTSIDE EACH SEPARATE SLEEPING AREA IN THE IMMEDIATE VICINITY OF THE BEDROOMS
- 2. IN THE IMMEDIATE VICINITY OF THE BEDROOMS IN DWELLING UNITS WITHIN WHICH FUEL-FIRED APPLIANCES ARE INSTALLED AND IN DWELLING UNITS THAT HAVE ATTACHED GARAGES

FOUNDATION NOTES:

- 1. 4" DIA. CONTINUOUS PERF. PERIMETER DRAIN WITH HOLES ORIENTED DOWN. SLOPED TO DAYLIGHT OR TO STORM SEWER OR DRYWELL.
- 2. ALL LALLY COLUMNS THIS SHEET ASSUMED TO BE TYP.
- 3. ALL INTERIOR FOOTINGS TO BE DESIGNED PER SOIL CONDITIONS. CONTRACTOR TO VERIFY.
- 4. DECK SUPPORTS ASSUMED TO BE 10" DIA. SONOTUBES. SOIL CONDITIONS TO DETERMINE FOOTING DESIGN. CONTRACTOR TO VERIFY.
- 5. FOR PLUMBING LOCATION/LAYOUT, SEE GROUND FLOOR PLAN.
- 6. CONTRACTOR TO VERIFY CONDITIONS IN FIELD AND STEP FND./FTGS AS REQUIRED PER GRADE. AND SOIL CONDITIONS
- 7. BASEMENT FINISHES PER OWNER/CONT. (TO BE DETERMINED)
- CONTRACTOR TO VERIFY GRADE IN FIELD BEFORE CONSTRUCTION OF TYPICAL FOUNDATION WALLS OR DAYLIGHT BASEMENT. DESIGN SHOWN MAY DIFFER FROM ACTUAL FINISHED CONSTRUCTION. FINAL MATERIALS, WINDOW/DOOR LOCATIONS AND SIZES, TO BE DETERMINED PER OWNER/CONT. AND LOCAL CODES.



Proposed Foundation P Wilson Residence Portland, ME

Revisions:

BRUCE W. MACLEOD

12/02/15 REVISED PLANS **Date:** 12/02/15 Scale: 1/4"=1'-0"

Drawn By: JTM **Project:** C070815 Sheet Number:

2 of 5