



GB 3/4" ID Insulated Rubber Steel Clamps (PPR-1575)
Placed 60" on center



Non-ADA Fabricated Sign Specifications

Job Name: SPURWINK
 Job #: 18549
 Customer Name: SPURWINK
 Scope: DIBOND RAILING SIGN
 Sales Rep/Drawn By: JS / KMR
 Revision #: 1
 Date: 4.9.15
 File Location: J: SPURWINK 18549



207.833.6200
www.welchusa.com

Sign Components

Face Material/Thickness: 3MM DIBOND

Edges: Straight

Corners: Square

West System: Yes

Insert: NA

First Surface Color: NA

Second Surface Color: NA

Vinyl Color: NA

2nd Layer Material/Thickness: NA

First Surface Color: NA

Second Surface Color: NA

Sides: SINGLE

Graphic Content

Process: FRONT APPLIED CONTROL TAC

Copy Height: PER LOGO / 3.8"

Copy Style: BRANDON MED

Copy Color: BLACK

Mounting

Hardware: INSULATED RUBBER STEEL CLAMPS

Holes: .21"

Mounting Location: NA

Tape: NA

Surface: NA

Glass Backer/mat/color: NA

Frame

Type: NA

Size: NA

Color: NA

Approved By: _____

Date: _____

DISCLAIMER: Welch is not responsible for the output of customer supplied files or logos. It is the customer's responsibility to make sure they have supplied the files in the correct resolution and PMS colors. Colors will vary from monitor to printer. Welch is not responsible for color variation. Custom proof color matching is available for an additional fee. Please call or visit www.welchusa.com/network for file information

VEHICLES: Although Vehicle Graphics are meant to last 3-5 years, Welch will only warranty the replacement of vehicle graphics 60 days from the install date. Graphics are a temporary advertisement. Please note that sunlight, bad weather, rocks, pressure washing and incorrect care of your graphics can shorten life span.

©2013 Welch Signage, All Rights Reserved. All information contained in this drawing is confidential; do not distribute or reproduce.

Proofed - In Design:

In Production: