Location of Construction:	Owner:		Phone: 774-9000	990836
78 Madeline St Owner Address:	Chris Chad Lessee/Buyer's Name:	Phone:	BusinessName:	990830
78 Madelin St Ptld	cessee/Buyer's Ivaine.	Phone.	The second secon	CIRLIPSE THANGED
Contractor Name:	Address:	Phone	e: call 450 0930	Permit Issued:
*Thomas Eassler	HIM 2 Mayflower D		4074 885-5907	1110 0 1010
Past Use:	Proposed Use:	COST OF WOR		AUG 9 1999
		\$ 24,690	\$ 168.00	
1-Family	Same	FIRE DEPT.	Approved INSPECTION:	OLTY OF PORTLAND
			Denied Use Group #3 Type	52 THO TORTLAND
			BOCAGEI	Zone: CBL: 180-C-010
Daniel De Control		Signature:	Signature:	Zanian Annequals
Proposed Project Description:	The state of the s		ACTIVITIES DISTRICT (P/)	a la balan
	MINIL		Approved	Special Zone or Reviews:
EMM Construct Addition	MIMI		Approved with Conditions:	□ Shoreland ——
	AL ALL		Denied	□ □ Wetland
	11 4.	Ciamatana	Data	☐ Flood Zone
Permit Taken By:	Date Applied For:	Signature:	Date:	☐ Site Plan maj ☐minor ☐mm ☐
SP SP	Date Applied For:	agust 5, 1999	a	The state of the s
			100000000000000000000000000000000000000	Zoning Appeal
 This permit application does not precl 	ude the Applicant(s) from meeting application	able State and Federal rules.		☐ Variance ☐ Miscellaneous
Building permits do not include plun	bing, septic or electrical work,			□ Conditional Use
 Building permits are void if work is no 	ot started within six (6) months of the date	of issuance. False informa-	age billion	□ Interpretation
tion may invalidate a building permit		IIUFI	Warmen Lines	□Approved
	LXE		The state of the state of the	Denied
		The same of		Historic Preservation
		The same of the same of	Samuel Control of the	□ Not in District or Landmark
				☐ Does Not Require Review
			PERMIT ISSUED	☐ Requires Review
			WITH REQUIREMENTS	
			William	Action:
	CERTIFICATION	N .		□Appoved
I hereby certify that I am the owner of reco			ne owner of record and that I have	
authorized by the owner to make this appl				
if a permit for work described in the applie				ter all
areas covered by such permit at any reaso	nable hour to enforce the provisions of th	e code(s) applicable to such	permit	Date:
		August 6,	1999	
SIGNATURE OF APPLICANT	ADDRESS:	DATE:	PHONE:	
			F-125-51-51-51	
				3
RESPONSIBLE PERSON IN CHARGE O	The state of the s		PHONE:	CEO DISTRICT

The property of the property of the party of

COMMENTS

Call Revised	ave in Alac	"Rock on Dat	
Back of	ne hevel To header 5	Garage 5/8	SMIX
8-13-49 was missing one tabe on left Sale will call Back when it is dong in FR) 15et Back ok 8-16-49 callod Town H. 7:35 4m asked him To Bring in Revised	Foundation plan + 1:-5 for (TR) 9-10-99 Oid Franing Inspection Stairs From one hevel To anouther need to Berrecut To have a 10" Net tweed all headers are in Alac	Ridge Tusulation Still needs to be Tustaled to Proctect Slab on Drivagay Side, Explained Seperation on Garage 5/g"Rock on Det Sides T.R.	Permit Expires - SMH
e tabo	pertion 5ta	lained Sex	Promue E
tissing on	raning Tusp ent To have	n Still n.	ne arestrol
was m Kuhan i	9-10-99 Ord Francis Ins nord to Berrent Toh	Ridge Insulation Driver ay Sid Sides TR.	3-25-09 110 FIND Re Chestrol
8-13-99 Bae	Founda 9-10-6	Ridge Drives Sides	3-25-09

Inspection Record					
Inspectio					
Type					
I	Foundation:	Framing:	Plumbing:	Final:	

BUILDING PERMIT REPORT ADDRESS: REASON FOR PERMIT: PERMIT APPLICANT: CONSTRUCTION TYPE \$ 24.000 - \$168.00 The City's Adopted Building Code (The BOCA National Building Code/1996 with City Amendments) The City's Adopted Mechanical Code (The BOCA National Mechanical Code/1993) CONDITIONIS) OF APPROVAL This permit is being issued with the understanding that the following conditions are met: $\frac{x}{3}$ \frac{x} This permit does not excuse the applicant from meeting applicable State and Federal rules and laws. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection) Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the top of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor elevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6" of the same material. Section 1813.5.2 4. Foundations anchors shall be a minimum of 1/2" in diameter, 7" into the foundation wall, minimum of 12" from corners of foundation and a maximum 6' o.c. between bolts. (Section 2305.17) 5. Waterproofing and dampproofing shall be done in accordance with Section 1813.0 of the building code. Precaution must be taken to protect concrete from freezing. Section 1908.0 6. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify 7. that the proper setbacks are maintained. £ 8. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of 1/2 inch gypsum board or the equivalent applied to the garage means of 1/2 inch gypsum board or the equivalent applied to the garage side. (Chapter 4, Section 407.0 of the BOCA/1996) All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993). Chapter 12 & NFPA 211

9.

Sound transmission control in residential building shall be done in accordance with Chapter 12, Section 1214.0 of the City's Building 10.

Guardraits & Handraits: A guardrail system is a system of building components located near the open sides of elevated walking surfaces /(네. for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2, M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 3e4" but not more than 38". Use Group R-3 shall not be less than 30", but not more than 38".) Handrail grip size shall have a circular cross section with an outside diameter of at least 1 1/2" and not greater than 2". (Sections 1021 & 1022.0) - Handrails shall be on both sides of stairway, (Section 1014.7)

Headroom in habitable space is a minimum of 76". (Section 1204.0)

Stair construction in Use Group R-3 & R-4is a minimum of 10" tread and 7 %" maximum rise. All other Use Group minimum 11" tread, 7" maximum rise. (Section 1014.0)

The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8") 1014.4

Every sleeping room-below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door **X** 15. approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft. (Section 1018.6)

Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits 16.

directly from the apartment to the building exterior with no communications to other apartment units. (Section 1010.1)

- 17. All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self closer's. (Over 3 stories in height requirements for fire rating is two (2) hours.) (Section 710.0)
- 18. The boiler shall be protected by enclosing with (1)hour fire rated construction including fire doors and ceiling, or by providing automatic extinguishment. (Table 302.1.1)
- 19. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 &19. (Smoke detectors shall be installed and maintained at the following locations):
 - In the immediate vicinity of bedrooms
 - In all bedrooms
 - In each story within a dwelling unit, including basements

In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required) Section 920.3.2.

- A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. (Section 921.0)
- The Fire Alarm System shall maintained to NFPA #72 Standard.
- The Sprinkler System shall maintained to NFPA #13 Standard.
- All exit signs, lights and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023.0 & 1024.0 of the City's Building Code. (The BOCA National Building Code/1996)
- 24. Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
- 25. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification the Division of Inspection Services.
- 426. Ventilation shall meet the requirements of Chapter 12 Sections 1210.0 of the City's Building Code, (Crawl spaces & atties).
- All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade. No closing in of walls until all electrical (min.72 hours notice) and plumbing inspections have been done.
 - 28. All requirements must be met before a final Certificate of Occupancy is issued.
- All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code (the BOCA National Building Code/1996).
- Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical Code/1993). (Chapter M-16)
- (31.) Please read and implement the attached Land Use Zoning report requirements.
- Boring, cutting and notching shall be done in accordance with Sections 2305.4.4, 2305.5.1 and 2305.5.3 of the City's Building Code.
- X 33. Glass and glazing shall meet the requirements of Chapter 24 of the building code.
 - All signage, shall be done in accordance with Section 3102.0 signs of the City's Building Code, (The BOCA National Building Code 1996).
- *35. MAX SUAN FOR rafter 2x60.16 O.C. IS 10'A"
- 136. MAX Span For 2x 10 Floor Joists Q16"O.C. 15 15 8"
- 37. The proposed Foundation-8" sono Tules (Piers) Shall he placed an Footings min of 4" below grade with Connector between per and Footing siso a fasterner shall be used between pier and Franing

8. Shall be used be Tween Pier and Framing. 88. All France attached to buildness Shall be no bedger to good toolted To building to all Wyod bounders shall be protected as per section 3311.9 of the building!

L. McDougall, PFD

Marge Schmuckal, Zoning Administrator

PSH 7/24/99

**On the basis of plans submitted and conditions placed on these plans any deviations shall require a separate approval.

THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL PERMIT IS ISSUED

Building or Use Permit Pre-Application Additions/Alterations/Accessory Structures To Detached Single Family Dwelling

In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or Use Permit.

NOTE**If you or the property owner owes real estate or personal property taxes or user charges on any property within the City, payment arrangements must be made before permits of any kind are accepted.

Location/Address of Construction: 18 112 C	telino 5t	
Tax Assessor's Chart, Block & Lot Number Chart# 180 Block# C 1.01#010	Chris Chandlel	Telephone#.
Owner's Address. 78 makelin St Partland	Lessee/Buyer's Name (If Applicable)	Cost Of Work: Fee \$/68
Proposed Project Description: (Please be as specific as possible) Famula Room Adeletion	with much from 3 /2	: Bafg
Family Rom Adeletion Remarker's Name, Address & Telephone 2/1 Thomas Hassel Scalborou	Nay(lower dt 014 Ro	e'd By:
Separate permits are required for In-	ternal & External Plumbing, HVAC an	d Electrical installation.

- All construction must be conducted in compliance with the 1996 B.O.C.A. Building Code as amended by Section 6-Act II. All plumbing must be conducted in compliance with the State of Maine Plumbing Code.
 - All Electrical Installation must comply with the 1996 National Electrical Code as amended by Section 6-Art 141.
- HVAC(Heating, Ventilation and Air Conditioning) installation must comply with the 1993 BOCA Mechanical Code. You must Include the following with you application:
 - 1) A Copy of Your Deed or Purchase and Sale Agreement
 - 2) A Copy of your Construction Contract, if available

3) A Plot Plan (Sample Attached)

If there is expansion to the structure, a complete plot plan (Site Plan) must include:

- The shape and dimension of the lot, all existing buildings (if any), the proposed structure and the distance from the actual property lines. Structures include decks porches, a bow windows cantilever sections and roof overhangs, as well as, sheds, pools, garages and any other accessory structures.
- Scale and required zoning district setbacks

4) Building Plans (Sample Attached)

A complete set of construction drawings showing all of the following elements of construction:

- Cross Sections w/Framing details (including porches, decks w/ railings, and accessory structures)
- Floor Plans & Elevations
- Window and door schedules
- Foundation plans with required dramage and dampproofing
- Electrical and plumbing layout. Mechanical drawings for any specialized equipment such as furnaces, chimneys, gas equipment. HVAC equipment (air handling) or other types of work that may require special review must be included.

Certification

I hereby certify that I am the Owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his/her authorized agent. I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in this application is issued. I certify that the Code Official's authorized representative shall have the authority to enter all areas covered by this permit at any reasonable hour to enforce the provisions of the codes applicable to this permit.

Signature of applicant:	Than Hall	Date: 8/3	199
Building Permit Fee:	\$30.00 for the 1st \$1000.cost plus \$6	6.00 per \$1,000.00 construction	cost thereafter.