Location of Construction:	Owner:		Phone:	Permit No:
Owner Address:	Lessee/Buyer's Name:	Phone:	BusinessName:	00061
Owier Address.	Lessee/Buyer's Name.	riione.	Dusinessivanie.	DEDMAT 100
Contractor Name:	Address:	Pho	ne:	Perhit Saled 1000
Past Use:	The state of the s	COST OF WO	RK: PERMIT I	NIN O)
Past Use:	Proposed Use:	\$		1 1 00:1
1.1 × 1.4 (1.4 × 4	\$ \$ \$100 € 50 € 50 €	FIRE DEPT.	Approved INSPECTI	ON:
			Denied Use Group	#3Type: 5% CITY OF PURILANLY
			BOC# 99	Zonez CBL:
Proposed Project Description:		Signature:	Signature:	
1 Toposed Project Description.		Action:	ACTIVITIES DISTRIC Approved	
the second second	· Description of the control of the	Action.	Approved with Condition	
INTERIORR	PRAKE		Denied	□ □ Wetland
110 (012012)	CI TOOCIEMS		ъ.	☐ Flood Zone☐ Subdivision
Permit Taken By:	Date Applied For:	Signature:	Date:	☐ Subdivision ☐ Site Plan maj ☐minor ☐mm ☐
Termit Taken by.	Date Applied For.	A Professional Company		
1 This name to analization does not may	aluda tha Ameliaant(a) from mooting ameliaahl	State and Foderal miles		Zoning Appeal Variance
	clude the Applicant(s) from meeting applicable	e State and rederal rules	S.	□ Miscellaneous
2. Building permits do not include plu	- -		,	☐ Conditional Use
3. Building permits are void if work is tion may invalidate a building perm	not started within six (6) months of the date of	issuance. False informa	1- <u>1</u>	☐ Interpretation☐ Approved
tion may invalidate a building perm	in and stop an work		र्च.	□Denied
			12 21 84 28	Historic Preservation
				□ Not in District or Landmark
				☐ Does Not Require Review
			PERMIT ISSUE	Requires Review
			PERMIT ISSUE WITH REQUIREM	Action:
	CERTIFICATION		Admir	□Appoved
I hereby certify that I am the owner of re-	cord of the named property, or that the propose	d work is authorized by	the owner of record and th	at I have been
	plication as his authorized agent and I agree to			
	lication is issued, I certify that the code officia			ity to enter all Date:
areas covered by such permit at any reas	sonable hour to enforce the provisions of the c	ode(s) applicable to suc	n bennn	
SIGNATURE OF APPLICANT	ADDRESS:	DATE:	PHONE:	
				TOLAIT ISSUED
				DEKINI 1 100 APRIL 1
RESPONSIBLE PERSON IN CHARGE (OF WORK TITLE		PHONE:	PERMIT ISSUED PERMIT ISSUED CEWITH REQUIREMENTS

COMMENTS

6/2300) - Electrica	f checked	by Mile	alline - OK	t - Flu	mbine, 2 mig	ats and
							Hiova, Tim
	-					<i>'</i>	
3-26-09	No JINA	Inspector	REQUESTED	- Expine	ED SM	A-	
	U	1					
							
					.		·
							
_							
							
						Inspection Record	l
					Type	-	Date
			•				
							_

BUILDING PERMIT REPORT
DATE: 7 June 2000 ADDRESS: 105 Edgeworth : CBL: 181-B-025 REASON FOR PERMIT: Intension renovations - Chose T To Laundry Mong
REASON FOR PERMIT: InTenior renovations - Chose T To Laundry Mon
BUILDING OWNER: Jenny Macke./
PERMIT APPLICANT: /CONTRACTOR Caron & Waltz
USE GROUP: <u>B-3</u> CONSTRUCTION TYPE: <u>5</u> ONSTRUCTION COST: <u>100.0</u> PERMIT FEES: <u>30.0</u>
The City's Adopted Building Code (The BOCA National Building code/1999 with City Amendments) The City's Adopted Mechanical Code (The BOCA National Mechanical Code/1993)
CONDITION(S) OF APPROVAL
This permit is being issued with the understanding that the following conditions are met: */ *27, *36

This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.

2. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection) "ALL LOT LINES SHALL BE CLEARLY MARKED BEFORE CALLING."

- 3. Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor elevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6" of the same material. Section 1813.5.2
- 4. Foundations anchors shall be a minimum of ½" in diameter, 7" into the foundation wall, minimum of 12" from corners of foundation and a maximum 6' O.C. between bolts. Section 2305.17
- 5. Waterproofing and dampproofing shall be done in accordance with Section 1813.0 of the building code.

6. Precaution must be taken to protect concrete from freezing. Section 1908.0

- 7. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.
- 8. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4, Section 407.0 of the BOCA/1999)
- All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993). Chapter 12 & NFPA 211
- 10. Sound transmission control in residential building shall be done in accordance with Chapter 12, Section 1214.0 of the City's Building Code.
- 11. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42". In occupancies in Use Group A,B.H-4, I-1, I-2, M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 34" but not more than 38". Exception: Handrails that form part of a guard shall have a height not less than than 36" and not more than 42". Handrail grip size shall have a circular cross section with an outside diameter of at least 1 "" and not greater than 2". (Sections 1021 & 1022.0). Handrails shall be on both sides of stairway. (Section 1014.7)
- 12. Headroom in habitable space is a minimum of 7'6". (Section 1204.0)
- 13. Stair construction in <u>Use Group R-3 & R-4 is a minimum of 10" tread and 7 %" maximum rise</u>. All other Use Group minimum 11" tread, 7" maximum rise. (Section 1014.0)
- 14. The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8") 1014.4
- 15. Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508)mm, and a minimum net clear opening of 5.7 sq. ft. (Section 1010.4)
- 16. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units. (Section 1010.1)
- 17. All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self closer's. (Over 3 stories in height requirements for fire rating is two (2) hours. (Section 710.0)
- 18. The boiler shall be protected by enclosing with (1) hour fire rated construction including fire doors and ceiling, or by providing automatic extinguishment. (Table 302.1.1)

THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

Building or Use Permit Pre-Application Additions/Alterations/Accessory Structures To Detached Single Family Dwelling

In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or Use Permit.

NOTE**If you or the property owner owes real estate or personal property taxes or user charges on any property within the City, payment arrangements must be made before permits of any kind are accepted.

Location/Address of Construction: 105 ED	CHE KKOPT H	
Tax Assessor's Chart, Block & Lot Number Chart# Block#B Lot#635	Owner: JENNA MACKELL	Telephone#:
Owner's Address:	Lessee/Buyer's Name (If Applicable)	Cost Of Work: Fee \$ 00
Proposed Project Description:(Please be as specific as possible)	aundy Room LRen	ever Passion lique
Contractor's Name, Address & Telephone CARON WALTZ 321	Grean ST S.P. 7	1By: 99-2228 P
Separate permits are required for In •All construction must be conducted in compli	ternal & External Plumbing, HVAC and	Electrical installation. s amended by Section 6-Art II.

• All Electrical Installation must comply with the 1996 National Electrical Code as amended by Section 6-Art III. •HVAC(Heating, Ventilation and Air Conditioning) installation must comply with the 1993 BOCA Mechanical Code. You must Include the following with you application:

- 1) A Copy of Your Deed or Purchase and Sale Agreement
 - 2) A Copy of your Construction Contract, if available

3) A Plot Plan (Sample Attached)

If there is expansion to the structure, a complete plot plan (Site Plan) must include:

- The shape and dimension of the lot, all existing buildings (if any), the proposed structure and the distance from the actual property lines. Structures include decks porches, a bow windows cantilever sections and roof overhangs, as well as, sheds, pools, garages and any other accessory structures.
- Scale and required zoning district setbacks

4) Building Plans (Sample Attached)

A complete set of construction drawings showing all of the following elements of construction:

- Cross Sections w/Framing details (including porches, decks w/ railings, and accessory structures)
- Floor Plans & Elevations
- Window and door schedules
- Foundation plans with required drainage and dampproofing
- Electrical and plumbing layout. Mechanical drawings for any specialized equipment such as furnaces, chimneys, gas equipment, HVAC equipment (air handling) or other types of work that may require special review must be included.

Certification

I hereby certify that I am the Owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his/her authorized agent. I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in this application is issued, I certify that the Code Official's authorized representative shall have the authority to enter all areas covered by this permit at any reasonable hour to enforce the provisions of the

codes applicable to this permit.		/		
Signature of applicant:	ty		Date: 06 -06-00	
	for the 1st \$1000.cost)	olus \$6.00 per \$1.0	000.00 construction cost thereafter.	
O:\INSP\CORRESP\MNUGENT\APADSFD.WPD				

