

Job 060876	Truss T01-2	Truss Type ATTIC	Qty 2	Ply 2	LAVENDIER Job Reference (optional)	131749498
---------------	----------------	---------------------	----------	-----------------	---------------------------------------	-----------

Mainely Trusses, Inc., Fairfield, ME

8.130 s Sep 15 2017 MiTek Industries, Inc. Tue Nov 28 07:35:43 2017 Page 2
ID:2I2aNXhs_pYzwSD577x2MWyBIJR-o8HTGLHI3NOh4POOwKupuCcDlunn7YYn?qzvxEyEjRE

NOTES- (14)

- 13) Attic room checked for L/360 deflection.
- 14) 15'-4" X 8'-0" 40 PSF ROOM, 2X10 B.C.

LOAD CASE(S) Standard

1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15

Uniform Loads (plf)

Vert: 1-2=-106, 2-3=-106, 6-19=-99, 6-7=-85, 7-8=-85, 8-9=-99, 9-11=-85, 11-12=-85, 15-17=-20, 14-15=-34, 13-14=-20, 6-8=-14
Drag: 5-15=-10, 9-14=-10

Trapezoidal Loads (plf)

Vert: 3=-291-to-4=-281, 4=-274-to-19=-264

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 10/03/2015 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 218 N. Lee Street, Suite 312, Alexandria, VA 22314.



16023 Swingley Ridge Rd
Chesterfield, MO 63017