



NOT FOR CONSTRUCTION




Roof Attachment Best Practices:

- Maximum Rail Length = 50', before expansion gap required
- Maximum Rail Span = 4' (varies, depending upon roof slope, snow load, wind speed, and exposure category at site)
- Maximum End cantilever span is 0.40 x maximum rail span
- Aluminum L-feet are fastened to structural members of the roof through pre-drilled holes, using 3" x 5/16" stainless steel lag screws.
- GeoCel applied at each attachment provides a watertight seal between, L-feet, shingles, and structural members.
- Staggering L-foot attachments allows even distribution of load on rafters.
- Typical Dimensions of one 60-cell PV Module: 64" x 40" x 1½"
- Clearance between roof and rail = 2"



Profile of Aluminum Rail Channel with Fastened End Clamp & Solar Panel



Site Specifications:

- Occupancy: Residence
- Design Wind Speed: 100 mph
- Exposure Category: C
- Ground Snow Load: 60 psf
- Roof Height: ~25' above grade to eaves
- Roof Composition: Asphalt Shingle
- Roof Pitch: 36°
- Roof Azimuth: 210° true
- Rafter Dimensions: 2x6" true
- Rafter Spacing: 24" OC



142 Presumpscot Street
 Portland, ME 04103
 (207) 221-6342

Customer Name:

John Knight
 29 Westminster Avenue
 Portland, ME 04103

System Type:

3.05DC
 Grid Tied Photovoltaic Array

Designed by: GJD
 Date: February 5, 2018
 Rev: 0

MODULE LAYOUT

A02

© Copyright ReVision Energy

This diagram is provided as a service and is based on the understanding of the information supplied. It is subject to change based on actual conditions, applicable edition of the National Electric Code, and local governmental authorities.