SILENT KNIGHT
by Honeywell

# SK-Heat, S

# SK

## Addressable Th
## Rate-of-

RESURGAM CITY OF PORTLAND, MAINE
Reviewed for Code Compliance
Inspections Division
Approved with Conditions
Date: 05/05/14

The SK-Heat, SK-Heat-HT, and SK-Heat-ROR are plug in thermal detectors, with integral communication, that provide features that surpass conventional detectors. These thermal detectors are for use with Silent Knight IntelliKnight series Fire Alarm Control Panels (FACPs).

IntelliKnight heat detectors are an essential component in virtually any IntelliKnight installation. The IntelliKnight panel recognizes each detector by its specific address, so precious seconds are not wasted in determining location of an alarm.

## Description

SK-Heat, SK-Heat-HT and SK-Heat-ROR are intelligent sensors that utilize a state-of-the art thermistor sensing circuit for fast response. Sensitivity is continuously monitored and reported to the FACP. Point ID capability allows each detector's address to be set with rotary address switches, providing exact detector locations for selective maintenance when chamber contamination reaches unacceptable levels.

SK-Heat is a fixed temperature sensor that uses a thermistor sensing circuit to produce 135ºF (57ºC) fixed temperature alarm.

SK-Heat-HT is a variable high temperature detector that provides high temperature detection at 135°F - 190ºF. (57°C - 88°C)

SK-Heat-ROR is a rate-of-rise temperature sensor with 135ºF (57ºC) fixed temperature alarm.

## Features

- Reliable analog communications for trouble-free operation
- Age resistant polymer housing
- Innovative thermistor sensing circuit
- Superior EMI resistance for reliability
- Variety of mounting options to meet any application
- Dual LED indicators for 360º visibility
- Detector transmits signal to indicate maintenance is required
- Plug-in mounting provides ease of installation
- Optional remote LED annunciator (System Sensor® PN RA100Z)
- Tamper-proof feature available on mounting bases
- Rotary address switches for fast installation
- UL Listed

## Specifications

**Physical**
Height: 2.0" (51 mm)
Diameter: 6.1" (155 mm) installed in B210LP base
Shipping Weight: 4.8 oz (137 g)

**Electrical**
Operating Voltage:
15 to 32 Volts DC Peak

Standby Current:
300µA @ 24 VDC

LED Current: 6.5 mA@ 24 VDC

## Environmental

**Operating Temperature**
SK-Heat & SK-Heat-ROR:
-4º – 100ºF (-20ºC– 38ºC)

SK-Heat-HT: -4º – 150ºF
(-20ºC – 66ºC)

Humidity: 10% – 93%
noncondensing

**Thermal Ratings**
SK-Heat: Fixed temperature alarm 135ºF (57ºC)

**SK-Heat (base included)**

SK-Heat-HT: High temperature heat sensor 135°F - 190ºF (57°C - 88ºC)

SK-Heat-ROR: Rate-of-rise detection 15ºF/min (8.3ºC/min)

## Compatibility

The SK-Heat-HT and SK-Heat-ROR are compatible with the following IntelliKnight FACP's:

5820XL
5808
5700

The SK-Heat is compatible with the following IntelliKnight FACP's:

5820XL
5808
5700
5600 (Rev 2.0 or higher)

The SK-Heat, SK-Heat-HT and SK-Heat-ROR are compatible with the following detector bases:

| | |
|---|---|
| B210LP | 6" base (included) |
| B501 | 2 wire base |
| B224BI | Isolator base |
| B224RB | Relay base |
| B200SR | Sounder base |

# Model SK-Heat, SK-Heat-HT, SK-Heat ROR Addressable Thermal and Rate-of-Rise Thermal Detectors

Reviewed for Code Compliance
Inspections Division
Approved with Conditions

Date: 05/05/14

## Engineering Specifications

The contractor shall furnish and install where indicated on the plans, Intelligent Thermal Sensor Silent Knight Model SK-Heat, SK-Heat-HT or SK-Heat-ROR. The base included shall be B210LP.

The Heat detector shall have a flashing status LED for visual supervision. When the detector is activated, the flashing LED will latch on steady at full brilliance. The detector may be reset by actuating the control panel reset switch.

The vandal-resistant, security locking feature shall be used in those areas as indicated on the drawing. The locking feature shall be field removable when not required.Voltage and RF/transient suppression techniques shall be employed to minimize false alarm potential.

Wiring SK-Series Detector Mounting Bases

### Accessories

RA100Z - Remote LED Annunciator.

RMK400 - Recessed Mounting Kit. Provides low profile for use with B501.

XR2B - Detector Removal Tool. A removal and re- placement tool for SK plug-in detectors. Includes the T55-127-000.

M02-04-01 - Replacement Test Magnet.

M02-09-00 - Test Magnet with Telescoping Handle.

XP-4 - Extension Pole for XR2B. Extends from 5 – 15 ft.

T55-127-000 - Detector Removal Head.

BCK-200B - Black Detector Kit. For SK-series detectors.

* Unless otherwise noted, specifications apply to all SK thermal detectors.

SILENT KNIGHT by Honeywell

This document is not intended to be used for installation purposes. We try to keep our product information up-to-date and accurate. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice. For more information, contact Silent Knight 12 Clintonville Road Northford, CT 06472-1610 Phone: (800) 328-0103, Fax: (203) 484-7118. For Technical Support call 800-446-6444. **www.silentknight.com**

**MADE IN AMERICA**

FORM# 350120 Rev. D1

© 2013 Honeywell International Inc.