

WALL FINISH SPECIFICATIONS

CODE	MATERIAL	MANUFACTURER	PRODUCT NO	DESCRIPTION / REMARKS
PL-1	PLASTIC LAMINATE	BY OTHERS		
PT-1	PAINT	BENJAMIN MOORE	2146-40 "PALE AVOCADO"	USE @ WALLS & SOFFITS
PT-2	PAINT	BENJAMIN MOORE	0C39 "TIMID WHITE"	USE @ SOFFITS
PT-3	PAINT	BENJAMIN MOORE	2146-50 "RAIN FOREST DEW"	USE @ SOFFITS
PT-4	PAINT (EXTERIOR)	SHERWIN WILLIAMS	METALASTIC DTM SEMI-GLOSS (FOR MTL SURFACES)	SW # 7035 AESTHETIC WHITE
PT-5	PAINT (EXTERIOR)	SHERWIN WILLIAMS	A82 SERIES/A100 SATIN FINISH (PLASTIC, CMU & WD SURFACES)	SW # 7035 AESTHETIC WHITE
PT-6	PAINT	RUST-OLEUM	"SPECIALTY MAGNETIC PRIMER"	MAGNETIC PRIMER FOR USE ABOVE ALL WALK-IN COOLER/FREEZER DOORS PRIOR TO APPLICATION OF FINISH PAINT
PT-7	PAINT (EXTERIOR)	BENJAMIN MOORE	A82 SERIES/A100 SATIN FINISH (FOR WD SURFACES) 2026-10 "LIME GREEN"	FORMULA: 32 64 128 W1 WHITE - 40 1 - G2 GREEN - 26 - 1 Y3 YELLOW - 11 - 1
SS-1	SOLID SURFACE	FORMICA	656 "RIVER ROCK MOSAIC"	
WP-1	FRP PANELS	MARLITE	#P-100 - WHITE (PEBBLE SURFACE)	
WP-2	WALL PANELS	MARLITE	STACKBOND; CUSTOM COLOR "KEY LIME"	USE AT DELFIELD AREAS COFFEE COUNTER INSTALL TILE PATTERN HORIZONTALLY
WP-3	WALL PANELS	MARLITE	PLANK - WEAVE SERIES; COLOR #209 ADARA	USE IN RESTROOMS (UPPER HALF)
WP-4	WALL PANELS	MARLITE	PLANK - WEAVE SERIES; COLOR #936 MILAN	USE IN RESTROOMS (LOWER HALF)
WP-5	WALL PANELS	MARLITE	VOLTA-FLEX	COLOR: CROSS HATCH SILVER. PATTERN: AS SELECTED BY OWNER
CG-1	16 GA STAINLESS STEEL CORNER GUARD	CUSTOM	1" x 1" S.S. CORNER GUARD, #4 SATIN FINISH W/ COUNTERSUNK S.S. SCREWS	FULL HEIGHT OF WALL FROM BASE TO CEILING
CG-2	16 GA STAINLESS STEEL CORNER END CAP	CUSTOM	S.S. END WALL CAP W/ 1" WINGS EA. SIDE X WIDTH OF WALL, #4 SATIN FINISH W/ COUNTERSUNK S.S. SCREWS	FULL HEIGHT OF WALL FROM BASE TO CEILING
CG-3	PLASTIC END CAP	CUSTOM	END WALL CAP W/ 1" WINGS EA. SIDE X WIDTH OF WALL, #4 SATIN FINISH W/ COUNTERSUNK S.S. SCREWS	FULL HEIGHT OF WALL FROM BASE TO CEILING
CG-4	PLASTIC CORNER GUARD	CUSTOM	END CORNER GUARD W/ 1" WINGS EA. SIDE X WIDTH OF WALL, #4 SATIN FINISH W/ COUNTERSUNK S.S. SCREWS	FULL HEIGHT OF WALL FROM BASE TO CEILING

CEILING FINISH SPECIFICATIONS

CODE	MATERIAL	MANUFACTURER	PRODUCT NO	DESCRIPTION / REMARKS
ACT-1	LAY-IN ACOUSTICAL CLG TILES	ARMSTRONG	ULTIMA #1910 - WHITE	24"x24"
ACT-2	LAY-IN ACOUSTICAL CLG TILES	ARMSTRONG	ULTIMA #1913 - WHITE	24"x48"
GR-1	CEILING GRID	ARMSTRONG	PRELUDE XL 15/16" - WHITE	
SWP-1	SYNTHETIC WOOD PANELS	CERTAINTEEED	TRIMBOARD SHEET (4'x8' SHEETS)	NATURAL WHITE - SMOOTH/SMOOTH
VSP-1	VINYL SOFFIT PANELS	CERTAINTEEED	VALUE TRIPLE 4" - COLONIAL WHITE	CENTER VENTED

FINISH SCHEDULE

ROOM	FLOOR		BASE		REAR WALL		RIGHT WALL		FRONT WALL		LEFT WALL		CEILING		REMARKS
	MAT	FIN	MAT	FIN	MAT	FIN	MAT	FIN	MAT	FIN	MAT	FIN	HEIGHT		
RETAIL SALES AREA	CONC	VP-1	RES-1	GB	PT-1/PT-2 WP-2	GB/GL	PT-1/PT-2 WP-2	GB/GL	PT-1/PT-2 WP-2	GB	PT-1/PT-2 WP-1	2X2 ACT	ACT-1	9'-9"	
UTILITY	CONC	VP-1 VCT-1	RES-1	PWD	WP-1	PWD	WP-1	PWD	WP-1	PWD	WP-1	2X4 ACT	ACT-2	9'-0"	*PWD WALL FINISH @ CPI PANELS TO BE PAINTED BLACK
WOMEN'S BATHROOM	CONC	VP-1	RES-1	PWD	WP-3/WP-4	PWD	WP-3/WP-4	PWD	WP-3/WP-4	PWD	WP-3/WP-4	GYP	PT-3	8'-0"	
MEN'S BATHROOM	CONC	VP-1	RES-1	PWD	WP-3/WP-4	PWD	WP-3/WP-4	PWD	WP-3/WP-4	PWD	WP-3/WP-4	GYP	PT-3	8'-0"	
CASHER AREA	CONC	VP-1	RES-1	GB	PT-1/PT-2 WP-2	GB	WP-1	-	-	GB	WP-1	GYP	PT-3	9'-0"	
WALK-IN FREEZER	CONC	SC-1	NONE	-	-	-	-	-	-	-	-	-	-	-	PRE-FAB UNIT
WALK-IN COOLER	CONC	SC-1	NONE	-	-	-	-	-	-	-	-	-	-	-	PRE-FAB UNIT
ALCOVE	CONC	VP-1	RES-1	GB	PT-1	GB	PT-1/ PT-6	-	-	GB	PT-1/ PT-6	2X2 ACT	ACT-1	9'-9"	

*NOTE: GB = GYP. BD
PWD = PLYWOOD
GL = GLAZING

FLOOR FINISH SPECIFICATIONS

CODE	MATERIAL	MANUFACTURER	PRODUCT NO	DESCRIPTION / REMARKS
RES-1	4" VINYL COVE BASE	ARMSTRONG	#64 FRESH TAUPE	
VP-1	VINYL PLANK	ALTRO	ADORE TOUCH # AT-1518 (VILLA OAK)	
VCT-1	VINYL COMPOSITION TILE	**TBD**	YELLOW	AS SELECTED BY OWNER
SC-1	SEALED CONCRETE	SHERWIN WILLIAMS	"ARMORSEAL"	COLOR, GRAY
SC-2	SEALED CONCRETE	SHERWIN WILLIAMS	DURA-PLATE 235 MULTI-PURPOSE EPOXY	COLOR: AS SELECTED BY OWNER
TS-1	TRANSITION STRIP	JOHNSONITE	REDUCER RRS-XX-C (1/8" TRANSITION)	CUT LENGTH OF OPENING COLOR AS SELECTED BY OWNER
TS-2	TRANSITION STRIP	SCHLUTER	RENO-U #AU125AT - SATIN NICKEL ANODIZED ALUM	CUT LENGTH OF OPENING

LEGEND

DOOR NUMBER SEE A2.1 FOR SCHEDULE & DETAILS
 WINDOW FRAME TYPE SEE A2.1 FOR DETAILS
 PARTITION TYPE (SEE SHEET A0.3)
 ELEVATION NUMBER/SHEET
 SECTION KEY
 BUILDING SECTION
 ENLARGED AREA/ DETAIL SYMBOL
 ELEVATION HEIGHT EL.
 COLUMN LINE
 FLOOR SINK (SEE PLUMBING DWGS)
 FLOOR DRAIN (SEE PLUMBING DWGS)
 FLOOR CLEAN OUT (SEE PLUMBING DWGS)
 INDIRECT DRAIN (SEE PLUMBING DWGS)
 PRE-FAB COOLER/FREEZER WALL PANEL
 FIRE EXTINGUISHER
 EMERGENCY WEATHER PROOF LIGHTING FIXTURE
 FIRE ALARM SYSTEM MANUAL PULL STATION
 FIRE ALARM SYSTEM AUDIO/VISUAL SIGNALING DEVICE
 EXIT LIGHT FIXTURE WITH EMERGENCY LIGHTING HEADS
 EMERGENCY BATTERY UNIT LIGHTING FIXTURE (WITH REMOTE CAPABILITIES)
 CEILING MOUNTED FIRE ALARM AUDIBLE/VISUAL SIGNALING DEVICE

SPECIFICATIONS

BUILDING FIRE EXTINGUISHER
LARSON MODEL WP10; 10 L13 MULTIPURPOSE DRY CHEMICAL UNIT FIRE EXTINGUISHER WITH WALL MOUNTING BRACKETS; UL RATING 4A-80B.C. or OTHER APPROVED EQUAL.
FIRE EXTINGUISHERS SHALL BE INSTALLED IN ACCORDANCE WITH NFPA 13 AND MANUFACTURER'S INSTRUCTIONS.
FIRE EXTINGUISHERS SHALL BE INSTALLED BY GENERAL CONTRACTOR WITH FINAL PLACEMENT IS TO BE COORDINATED IN THE FIELD BY THE CONTRACTOR WITH THE LOCAL AUTHORITY HAVING JURISDICTION.

FINISH NOTES

- SEE A6.1 FOR INTERIOR ELEVATIONS
- PROVIDE TAPE & 3 COATS JOINT COMPOUND AT WALLS SCHEDULED TO RECEIVE PAINT FINISH (LEVEL 5 FINISH)
- PROVIDE 1 PRIME COAT & 2 FINISH COATS @ ALL AREA SCHEDULED TO RECEIVE PAINT FINISH. ALL WALLS BEHIND MILLWORK CABINETS TO BE PAINTED
- ALL FINISHES TO CONTINUE TO FLOOR BEHIND AND ALONG SIDE WALLS OF DELFIELD & CHILLZONE EQUIPMENT
- SEE A1.4 FOR SOFFIT FINISH COLORS
- GYP BOARD SPECIFICATION: MANUFACTURERS: -US GYPSUM COMPANY -COLD BOND BUILDING PRODUCTS -GEORGIA PACIFIC CORPORATION MATERIALS: -MAXIMUM PERMISSIBLE LENGTH; SQUARE CUT ENDS, TAPERED EDGES; THICKNESS AS SHOWN ON DRAWINGS -STANDARD TYPE: ANSI/ASTM C36 -MOISTURE RESISTANT TYPE: ANSI/ASTM C79; WATER REPELLANT PAPER FACES ALL INTERIOR PAINT IS TO BE "REGAL" BY BENJAMIN MOORE. ALL WALLS, DOOR FRAMES & VERTICAL FACES OF SOFFITS SHALL BE PAINTED WITH AN EGG SHELL FINISH. ALL GYP BD CEILINGS & UNDERSIDE OF SOFFITS SHALL BE PAINTED WITH A FLAT FINISH.

PARTITION TYPES	TYPE	DESCRIPTION	TYPE	DESCRIPTION	TYPE	DESCRIPTION
<p>* NOTES:</p> <ol style="list-style-type: none"> 5/8" GWB TO BE TYPICAL WALL SUBSTRATE UNLESS OTHERWISE NOTED AS FOLLOWS: USE 5/8" FIRE RATED PLYWOOD BEHIND ALL ELECTRICAL PANELS UNLESS NOTED OTHERWISE USE 5/8" MOISTURE RESISTANT GYPSUM WALLBOARD AT FOLLOWING LOCATIONS: <ol style="list-style-type: none"> ALL BATHROOM WALLS SCHEDULED TO RECEIVE NEW GWB BEHIND & ADJACENT TO COFFEE BAR, CHILL ZONE & REFRIGERATED WORK TABLE WHEN INSTALLED OVER PREFAB COOLER WALL PANELS ALLOW FOR 1" ROOF DEFLECTION AT METAL STUD FRAMING EXTENDING TO METAL ROOF DECK. DO NOT ATTACH METAL STUD TOP TRACK TO METAL ROOF DECK. SECURE TO STRUCTURAL STEEL ROOF FRAMING ONLY. 	J	AS SHOWN PRE-FAB, INSULATED COOLER WALL PANELS	E	AS SHOWN 1 LAYER 5/8" GWB 6"x20 GA. METAL STUDS @ 16" O.C. SECURED TO STRUCTURE ABOVE AS REQ'D. FOR PROPER SUPPORT	A	AS SHOWN 1 LAYER 5/8" GWB 3 5/8"x20 GA. METAL STUDS @ 16" O.C. SECURED TO STRUCTURE ABOVE AS REQ'D. FOR PROPER SUPPORT
	J1	SAME AS TYPE J - ATTACH (1) LAYER 5/8" GWB	E1	SAME AS TYPE E - SUBSTITUTE 5/8" PLYWOOD IN PLACE OF 5/8" WALLBOARD	A1	SAME AS TYPE A - SUBSTITUTE 5/8" GWB WITH 5/8" PLYWOOD
	J2	SAME AS TYPE J - ATTACH (1) LAYER 5/8" PLYWOOD				
	N	AS SHOWN 1 LAYER 5/8" GWB EA. SIDE (2) 3 5/8"x20 GA. METAL STUDS @ 16" O.C. 3 1/2" SOUND ATTENUATION BATT INSULATION SECURED TO STRUCTURE ABOVE AS REQ'D. FOR PROPER SUPPORT	K	AS SHOWN PRE-FAB, INSULATED FREEZER WALL PANELS	F	AS SHOWN 1 LAYER 5/8" GWB 6"x20 GA. METAL STUDS @ 16" O.C. 3 1/2" SOUND ATTENUATION BATT INSULATION SECURED TO WALL STRUCTURE AS REQ'D. FOR PROPER SUPPORT.
	D1	SAME AS TYPE D - SUBSTITUTE 5/8" GWB WITH 5/8" PLYWOOD ONE SIDE	K1	SAME AS TYPE K - ATTACH (1) LAYER 5/8" GWB	F1	SAME AS TYPE F - SUBSTITUTE 5/8" GWB WITH 5/8" PLYWOOD
	D2	SAME AS TYPE D - SUBSTITUTE 5/8" GWB WITH 5/8" PLYWOOD BOTH SIDES	K2	SAME AS TYPE K - ATTACH (1) LAYER PLYWOOD		
	P	AS SHOWN 1 LAYER 5/8" MOISTURE RESISTANT GWB EA. SIDE 2x4 STUDS @ 16" O.C. 3 1/2" SOUND ATTENUATION BATT INSULATION SECURED TO WALL STRUCTURE AS REQ'D. FOR PROPER SUPPORT	L	AS SHOWN 1 LAYER 5/8" GWB (M.R. AT WET AREAS) 2" x 20 GA. FURRING CHANNELS @ 24" O.C.(MAX.) 2" FOIL FACED RIGID INSULATION EXISTING EXTERIOR WALL	G	AS SHOWN 1 LAYER 5/8" GWB EA. SIDE 6"x20 GA. METAL STUDS @ 16" O.C. SECURED TO STRUCTURE ABOVE AS REQ'D. FOR PROPER SUPPORT
	P1	SAME AS TYPE P - SUBSTITUTE 5/8" GWB WITH 5/8" PLYWOOD ONE SIDE	L1	SAME AS TYPE L - SUBSTITUTE 5/8" GWB WITH 5/8" PLYWOOD	G1	SAME AS TYPE G - SUBSTITUTE 5/8" PLYWOOD IN PLACE OF 5/8" WALLBOARD ONE SIDE
	P2	SAME AS TYPE P - SUBSTITUTE 5/8" GWB WITH 5/8" PLYWOOD BOTH SIDES	L2	SAME AS L - OMIT 5/8" GWB	G2	SAME AS TYPE G - SUBSTITUTE 5/8" PLYWOOD IN PLACE OF 5/8" WALLBOARD BOTH SIDES
	Q	AS SHOWN 1 LAYER 5/8" GWB (M.R. AT WET AREAS) 6" x 20 GA. METAL STUDS @ 16" O.C. 2" x 20 GA. FURRING CHANNELS @ 24" O.C.(MAX.) 2" FOIL FACED RIGID INSULATION EXISTING EXTERIOR WALL	M	AS SHOWN 5-1/4" PRE-FAB INSULATED COOLER WALL PANEL 2" CLEAR CAVITY SPACE 2" x 20 GA. METAL FURRING @ 24" O.C.(MAX.) 2" FOIL FACED RIGID INSULATION EXISTING EXTERIOR WALL	H	AS SHOWN 1 LAYER 5/8" GWB EA. SIDE 6"x20 GA. METAL STUDS @ 16" O.C. 3 1/2" SOUND ATTENUATION BATT INSULATION SECURED TO STRUCTURE ABOVE AS REQ'D. FOR PROPER SUPPORT
	Q1	SAME AS TYPE H - SUBSTITUTE 5/8" GWB WITH 5/8" PLYWOOD	M1	SAME AS TYPE M - SUBSTITUTE 5 1/4" PRE-FAB COOLER WALL PANELS WITH 6 1/2" FREEZER WALL PANELS	H1	SAME AS TYPE H - SUBSTITUTE 5/8" GWB WITH 5/8" PLYWOOD ONE SIDE
				H2	SAME AS TYPE H - SUBSTITUTE 5/8" GWB WITH 5/8" PLYWOOD BOTH SIDES	
				D	AS SHOWN 1 LAYER 5/8" GWB EA. SIDE* 3 5/8"x20 GA. METAL STUDS @ 16" O.C. 3 1/2" SOUND ATTENUATION BATT INSULATION SECURED TO STRUCTURE ABOVE AS REQ'D. FOR PROPER SUPPORT * MOPSINK PROVIDE DOUBLE STUD CONSTRUCTION TO SUPPORT WATER HEATER ABOVE	
				D1	SAME AS TYPE D - SUBSTITUTE 5/8" GWB WITH 5/8" PLYWOOD ONE SIDE	
				D2	SAME AS TYPE D - SUBSTITUTE 5/8" GWB WITH 5/8" PLYWOOD BOTH SIDES	