

Bank of America

NOTE: THE TIER 1 SIGNATURE FORMAT (ALSO FORMALLY REFERRED TO AS PRIMARY SIGNATURE) IS THE STANDARD SIGNATURE FOR THE BANK OF AMERICA. THE TIER 2 SIGNATURE IS A STANDARD SIGNATURE VARIATION. TIER 1 SIGNATURE IS FOR MAINTENANCE, REPAIR AND REPLACEMENT ONLY. IN ACCORDANCE WITH THE RESPECTIVE DECISION TREE, NO NEW TIER 1 SIGNATURE IS TO BE RECOMMENDED.

1 G-TYPE CHANNEL LETTERS / STANDARD HORIZONTAL

SIGN TYPE	DESCRIPTION CODE	X	U	Y	Z1	SOFT A	SOFT B	SOFT B	ACRYLIC THICKNESS	DEAD BOFT TRIM CAP	JEWEL LITE TRIM CAP	SCALE 1/2"=1'-0"
G6	3/4" CAP HEIGHT	3'-0"	1'-4 1/4"	39'-8 3/4"	193.76	782.76	193.76	782.76	3/64	X	X	
G5	3/8" CAP HEIGHT	2'-6"	6'-1 1/2"	25'-3 1/4"	126.06	496.41	126.06	496.41	3/64	X	X	
G4	24" CAP HEIGHT	2'-0"	4'-10 3/4"	23'-0"	106.71	463.2	106.71	463.2	3/64	X	X	
G3	18" CAP HEIGHT	1'-6"	3'-8"	17'-10 1/2"	85.83	354.84	85.83	354.84	3/64	X	X	
G2	12" CAP HEIGHT	1'-3"	3'-0 3/4"	14'-10 3/4"	69.63	285.84	69.63	285.84	3/64	X	X	
G1	9" CAP HEIGHT	1'-0"	2'-5 1/2"	11'-11"	56.43	228.84	56.43	228.84	3/64	X	X	
G0	6" CAP HEIGHT	9"	1'-0"	8'-11 1/4"	46.43	186.84	46.43	186.84	3/64	X	X	
G03	8" CAP HEIGHT	8"	1'-1 1/2"	7'-3 1/4"	52.83	212.84	52.83	212.84	3/64	X	X	
G04	6" CAP HEIGHT	6"	1'-2 3/4"	5'-1 1/2"	43.23	172.84	43.23	172.84	3/64	X	X	

* USE DEAD BOFT ONLY IF LETTERS ARE VIEWED CLOSE UP FROM STREET LEVEL, LESS THAN 0'-6" FROM GRADE.

Bank of America

3 K-TYPE CHANNEL LETTERS / SPECIAL HORIZONTAL FORMAT

SIGN TYPE	DESCRIPTION CODE	X	U	Y	Z1	SOFT A	SOFT B	SOFT B	ACRYLIC THICKNESS	DEAD BOFT TRIM CAP	JEWEL LITE TRIM CAP	SCALE 1/2"=1'-0"
K6	3/4" CAP HEIGHT	3'-0"	4'-9"	37'-0 3/4"	193.76	782.76	193.76	782.76	3/64	X	X	
K5	3/8" CAP HEIGHT	2'-6"	3'-0 1/4"	30'-0 3/4"	153.71	612.76	153.71	612.76	3/64	X	X	
K4	24" CAP HEIGHT	2'-0"	7'-11 1/4"	24'-4 1/2"	123.86	463.2	123.86	463.2	3/64	X	X	
K3	18" CAP HEIGHT	1'-6"	2'-2 1/2"	18'-4 1/2"	85.83	354.84	85.83	354.84	3/64	X	X	
K2	12" CAP HEIGHT	1'-3"	1'-5 1/4"	12'-4 1/4"	69.63	285.84	69.63	285.84	3/64	X	X	
K1	9" CAP HEIGHT	1'-0"	1'-3 3/4"	10'-4 1/4"	56.43	228.84	56.43	228.84	3/64	X	X	
K0	6" CAP HEIGHT	9"	1'-1 1/4"	9'-3 1/4"	46.43	186.84	46.43	186.84	3/64	X	X	
K03	8" CAP HEIGHT	8"	1'-3 1/4"	8'-2 1/4"	52.83	212.84	52.83	212.84	3/64	X	X	
K04	6" CAP HEIGHT	6"	1'-2 3/4"	6'-2 1/4"	43.23	172.84	43.23	172.84	3/64	X	X	

* USE DEAD BOFT ONLY IF LETTERS ARE VIEWED CLOSE UP FROM STREET LEVEL, LESS THAN 0'-6" FROM GRADE.

NOTES:

- LETTERS SYMBOL FACE TO BE WHITE TRANSLUCENT FINISH. LETTERS PER TABLE FIRST SURFACE DECORATE WITH 3M FILM BLUE.
- SYMBOL FACE TO BE WHITE TRANSLUCENT FINISH. LETTERS PER TABLE FIRST SURFACE DECORATE WITH 3M FILM RED.
- DEADBOFT ALUMINUM TRIM CAP, FORM AS SHOWN, USE WHEN LETTERS TO BE MOUNTED ON MATCH LETTER FACE.
- 1" JEWELITE TRIM CAP 1/2" INTENSE BLUE. USE ON LETTERS AND BLUE PORTION OF 3/4" WHEN LETTER SET IS MOUNTED.
- 1" JEWELITE TRIM CAP 1/2" INTENSE RED. USE ON RED PORTION OF SYMBOL WHEN LETTER SET IS MOUNTED ABOVE 12'-0".
- INTERIOR SURFACES WITH SPRAY-LAT ENHANCEMENT PAINT OR APPROVED EQUAL.

GENERAL NOTES:

- FINAL SIZES FOR ALL STRUCTURAL MEMBERS (I.E. COLLARS, MATCH PLATES, CONNECTION BOLTS, ANCHOR BOLTS, FOUNDATIONS AND ETC.) SHALL BE SIZED BY A LICENSED ENGINEER TO BE IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE, AND FEDERAL CODES.
- FABRICATOR IS RESPONSIBLE FOR THE FINISH OF THE LETTERS.
- LEADS FROM BACK OF ILLUMINATED LETTERS / SYMBOL SHALL BE A MINIMUM OF 6'-0" IN LENGTH MEASURED FROM THE BACK SURFACE OF THE LETTERS / SYMBOL.
- INTERIORS OF ALL CABINETS WITH SPRAY-LAT STAR BRITTE WHITE LIGHT ENHANCEMENT PAINT.
- ALL PAINT TO BE TWO-PART POLYURETHANE.
- COLOR FILT TO BE MATCHED IN 3M 9563Z SERIES FILT.

MATERIAL SPECIFICATIONS

- PAINT
- CHAMPAGNE METALLIC - EITHER AKZO-NOBEL # BK 250, MATTHEWS # MP 2134, MATTHEWS # 600481949P, OR MATTHEWS # 590CR728P (VOC 100%)
 - RED - MATTHEWS RED # MP 436596.
 - AKZO-NOBEL # SIGN 2073
 - BLUE - MATTHEWS BLUE # MP 21676R 6595.
 - WHITE - MATTHEWS WHITE # MP 21666R 6595.
- FILM
- BLUE - 3M # 3637-8222
 - RED - 3M # 3637-2472
 - WHITE - 3M # 3637-110
 - WHITE - 3M # 3637-26

- ACRYLIC
- CLEAR ACRYL STEEL OR APPROVED EQUAL
 - FILM DECORATION CHANNEL LETTERS ONLY, ACRYL STEEL #441 OR APPROVED EQ.
 - ALUMINUM MOUNTMENT-ACRYL STEEL #1318 OR APPROVED EQ.

Color Channel Letters

09.01/06

Rev No. 01	08.15.06
Rev No. 02	08.18.06
Rev No. 03	02.23.07
Rev No. 04	03.31.10

MONIGLE ASSOCIATES

Rev No. 05 05.02.2010

Released To:	BANK OF AMERICA
Job Number:	76173
Drawn By:	JLD
Date:	12.12.05

These documents are for design intent and shall be used only as a guide to produce the finished stage appearance and functions shown. Nothing contained in these documents shall be construed as a design for any unapproved material. The fabricator/contractor shall be responsible for all structural, electrical, mechanical and foundation requirements. See General Specifications for additional requirements. These documents were prepared under an architectural services agreement with Monigle Associates, Inc. All rights reserved. © Monigle Associates, Inc. 559 Adams Street - Denver, Colorado 80246