SECTION 10 28 00
TOILET ACCESSORIES

PART 1 - GENERAL

1.01 SUMMARY

A. This Section specifies toilet accessories for installation in the toilet rooms, janitor's closet, and break room.

1.02 SUBMITTALS

A. Product Data: For each product indicated.

B. Product Schedule: Indicating types, quantities, sizes, and installation locations by room of each accessory required. Use room and product designations indicated on Drawings.

1.03 WARRANTY

A. Special Mirror Warranty: Manufacturer's standard form in which manufacturer agrees to repair or replace mirrors that develop visible silver spoilage defects within 10 years from date of Substantial Completion.

PART 2 - PRODUCTS

2.01 MANUFACTURERS

A. Basis-of-Design: Subject to compliance with requirements, provide Bobrick; Classic series toilet accessories, in the indicated model, or comparable product by one of the following:
   1. American Specialties, Inc.
   2. McKinney/Parker Washroom Accessories Corp.

2.02 TOILET ACCESSORIES

A. Toilet Tissue Dispenser: Stainless steel unit holding single 4-1/2 or 5-inch diameter tissue roll, for recessed installation; standard spindle (non-controlled delivery); satin finish.
   1. Basis-of-Design Product: Bobrick B-6677.

B. Recessed-Mounted Paper Towel Dispenser and Waste Receptacle (Toilet Rooms): 350 C-fold or 475 multifold paper towels capacity; 2-gallon wste receptacle.
   1. Basis-of-Design Product: Bobrick B-369.

C. Surface-Mounted Paper Towel Dispenser (Break Room): 400 C-fold or 525 multifold paper towels capacity; door hung on full-length piano hinge, secured with knob latch (no key).
   1. Basis-of-Design Product: Bobrick B-2620.

D. Liquid-Soap Dispenser: Surface mounted, stainless steel container, 40 fl. oz. capacity, satin stainless finish, with tumbler type lock and refill indicator window.

1. Basis-of-Design Product: Bobrick B-2112.
2. Soap Valve: Molded plastic push button and spout designed for dispensing liquid soap.

E. Grab Bar: 1-1/4 inches to 1-1/2 inches outside diameter; 0.05 inch thick stainless steel with slip-resistant texture on the gripping surface. Formed to provide 1-1/2-inch clearance between wall surface and inside face of bar.
1. Basis-of-Design Product: Bobrick B-550 x 42.
2. Mounting: Concealed with B-2562 anchor plate for stud wall construction.

F. Framed Mirror: Stainless steel angle frame; 6mm mirror glass; concealed wall hanger.
1. Basis-of-Design Product: Bobrick B-290-2436.

G. Stainless Steel Shelf: 24 inches long.
1. Basis of Design Product: Bobrick B-295x24.

H. Mop and Broom Holder: Stainless steel, 24 inches long, with three, spring-loaded, rubber cam type holders.
1. Basis-of-Design Product: Bobrick B-223x24.

I. Medicine Cabinet: Recess-mounted steel medicine cabinet with chrome-plated framed mirror door and two shelves. Nominal size: 16 by 22 inches.
1. Basis-of-Design Product: American Pride; Horizon.

J. Keys: Provide universal keys for access to accessories for servicing and resupplying. Provide minimum of six keys to Owner's representative.

PART 3 - EXECUTION

3.01 INSTALLATION

A. Install toilet accessories using fasteners appropriate to substrate indicated and recommended by unit manufacturer. Install units level, plumb, and firmly anchored in locations and at heights indicated.

B. Install grab bars to withstand a downward load of at least 250 lbf, when tested according to method in ASTM F 446.

C. Adjust accessories for unencumbered, smooth operation and verify that mechanisms function properly. Replace damaged or defective items. Remove temporary labels and protective coatings.

END OF SECTION 10 28 00