E00.10

| | | | | | | | | | | | | | | | | T | | | | Ţ | | | |
|---|---|---|---|---|--|---|---|--|--|--|---|---|---|--|---|--|---|--|---|---|--|--------------|----------------|
| 핃 | 콧 | <u>ٿ</u> | 至 | FG | FF-3 | FF-2 | FF-1 | ŦĦ | Æ | FD-2 | FD-1 | FD | FC | FB | FA | П | Ш | D | C | В | A | TYPE | |
| DOWNLIGHT W/WHITE DECORATIVE DROP GLASS TRIM, SEMI-SPECULAR ALUMINUM REFLECTOR AND INTEGRAL ELECTRONIC BALLAST. COLOR WHITE TO BE CONFIRMED BY ARCHITECT. | 5" DIAMETER METAL HALIDE DOWNLIGHT W/SPREAD LENS AND ATTACHED ELECTRONIC BALLAST. CUSTOM COLOR TO MATCH SHERWIN WILLIAMS SW7048 URBANE. COLOR TO BE CONFIRMED BY ARCHITECT. 277V 6" DIAMETER APERTURE COMPACT FLUORESCENT | DR 2-WAY LINEA 'URE RUNS, CU' EGRAL ELECTR T LOCATION. CC MED BY ARCHIT | NNEL W/FLEXI ELECTRONIC E CONFIRMED E | 7" DIAMETER CERAMIC METAL HALIDE DOWNLIGHT W/INTEGRAL ELECTRONIC BALLAST. CUSTOM COLOR TO MATCH SHERWIN WILLIAMS SW7048 URBANE. COLOR TO BE CONFIRMED BY ARCHITECT. | 6" DIAMETER APERTURE COMPACT FLUORESCENT CORNER WASHLIGHT W/SEMI-SPECULAR ALUMINUM REFLECTOR, 45° CUT-OFF ANGLE AND INTEGRAL ELECTRONIC BALLAST. COLOR WHITE TO BE CONFIRMED BY ARCHITECT. | TER APERTURE COMPACT FLUORESCENT VASHLIGHT W/SEMI-SPECULAR M REFLECTOR, 45° CUT-OFF ANGLE AND . ELECTRONIC BALLAST. COLOR WHITE NFIRMED BY ARCHITECT. | TER APERTURE COMPACT FLUORESO VASHLIGHT W/SEMI-SPECULAR M REFLECTOR, 45° CUT-OFF ANGLE / ELECTRONIC BALLAST. COLOR WHIT NFIRMED BY ARCHITECT. | 6" DIAMETER APERTURE COMPACT FLUORESCENT DOWNLIGHT W/SEMI-SPECULAR ALUMINUM REFLECTOR AND INTEGRAL ELECTRONIC BALLAST. COLOR WHITE TO BE CONFIRMED BY ARCHITECT. | METER APERTUR LIGHT W/SEMI-SF CTOR, DECORAT JTEGRAL ELECTR TO BE CONFIRM | 4' DIAMETER 6-LAMP PROFILE LINEAR FLUORESCENT TROFFER W/CONCAVE ACRYLIC LENS AND INTEGRAL ELECTRONIC BALLAST. COLOR WHITE TO BE CONFIRMED BY ARCHITECT. 277V | 3' DIAMETER 4-LAMP PROFILE LINEAR FLUORESCENT TROFFER W/CONCAVE ACRYLIC LENS AND INTEGRAL ELECTRONIC BALLAST. COLOR WHITE TO BE CONFIRMED BY ARCHITECT. | 2' DIAMETER 4-LAMP PROFILE LINEAR FLUORESCENT TROFFER W/CONCAVE ACRYLIC LENS AND INTEGRAL ELECTRONIC BALLAST. COLOR WHITE TO BE CONFIRMED BY ARCHITECT. | 6"x8' ONE LAMP PROFILE STAGGERED LINEAR FLUORESCENT TROFFER W/MICRO-PYRAMIDAL LENS AND INTEGRAL ELECTRONIC BALLAST. COLOR WHITE TO BE CONFIRMED BY ARCHITECT. | ASYMMETRIC CERAMIC METAL HALIDE UPLIGHT W/SPECULAR EXTRUDED ALUMINUM REFLECTOR, MICRO-PRISMATIC TEMPERED GLASS LENS, SOLID CUT-OFF VISOR, INTEGRAL MAGNETIC BALLAST. CUSTOM COLOR TO MATCH SHERWIN WILLIAMS SW7048 URBANE. COLOR TO BE CONFIRMED BY ARCHITECT. | 7" CYLINDRICAL COMPACT FLUORESCENT DOWNLIGHT W/INTEGRAL ELECTRONIC BALLAST, CUSTOM COLOR TO MATCH SHERWIN WILLIAMS SW7048 URBANE. COLOR TO BE CONFIRMED BY ARCHITECT. | 6" SQUARE x 4' , DIRECT/INDIRECT FLUORESCENT ACRYLIC LENS 277V | | 2'x2', 2 LAMP, DIRECT/INDIRECT W/PERFORATED CENTER BASKET. | 2'x4' ACRYLIC LENSED W/ELECTRONIC BALLAST | 1'x4' INDUSTRIAL FIXTURE W/ELECTRONIC BALLAST AND WIRE GUARD | 2'x4', 2 LAMP, DIRECT/INDIRECT W/CENTER PERFORATED BASKET 277V | DESCRIPTION | LIGHT F |
| ZUMTOBEL CH7-1H42CFTQ8- U-X-OD7525-SF- T-702-WH-AD | BK LIGHTING SE-61-CUSTOM-10 -B-RM-H35E-MT, PM3-RM-SM-H3RE- CUSTOM-MT | ELLIPTIPAR F164-A132-X-VXX-0 MOD | STARFIRE 230-CF18HE-1-12 WH-FLX | EDISON PRICE LIGHTING AMB/ARC38/7- 100-COL-RSA | EDISON PRICE LIGHTING TRPV26/6DS- CWW-XXX-ECOL | EDISON PRICE LIGHTING TRPV26/6DS- WW-XXX-ECOL | EDISON PRICE LIGHTING TRPV26/6DS- DWW-XXX-ECOL | EDISON PRICE LIGHTING TRPH126/6- XXX-ECOL | LIGHTOLIER D6A14-8021CL-S6132B | FOCAL POINT FSD-44-D-6-T8-S- XXX-U-CR-XX-HW | FOCAL POINT FSD-33-D-4-T8-S- XXX-U-CR-XX-HW | FOCAL POINT FSD-22-D-4-T8-S- XXX-U-CR-XX-HW | ZUMTOBEL SLR6-X-3395-08- MPO-U-x | ELLIPTIPAR M408-210C-2-02- XXX-V0-0-MOD | EDISON PRICE LIGHTING AMB/TRPV-42/7- COL-RSA | ALERA F4-2UDT8-WMNA-A19- EU-MW-4 | | COLUMBIA STR22-217G-MPO-EV | COLUMBIA 4PS-232-A19-277 | COLUMBIA KL4-332-EU-KLWG4 | COLUMBIA STR24-254G-MPO-EB5 | MANUFACTURER | IXTURE SCHEDUL |
| F42TTT/830 45W | PHILLIPS CDM35/ PAR30L/M/ FL/3K/ALTO 45W | (2) F32T8/830 59W | (11) F18TT5/830 242W | PHILLIPS CDM100/ PAR38/ FL/3K/ALTO 125W | F26TTT/830 30W | F26TTT/830 30W | F26TTT/830 30W | W08 30W | F26TTT/830 30W | (6) F32T8/830 177W | (4) F25T8/830 96W | (4) F17T8/830 66W | (3) F39T5HO/830 136W | PHILLIPS CDMELITE MW210/T9/ 930/U/E 250W | F42TTT/830 46W | 2-32W T8 | | 2-17W T8 | 2-32W T8 | 3-32W T8 | 2-54W T5HO | SAMVT | DULE |
| RECESSED | SURFACE | PENDANT | SURFACE | BRACKET | RECESSED | RECESSED | RECESSED | RECESSED | RECESSED | RECESSED | RECESSED | RECESSED | RECESSED | BRACKET | BRACKET | WALL | | RECESSED | RECESSED | CHAIN HUNG | RECESSED/ SURFACE | BNILNNOW | |
| FIXTURE APPEARANCE TO MATCH "FM". | | MOUNTING HEIGHT 10'-0" AFF TO BOTTOM OF FIXTURE. | 12" SPACING AND LOCATED IN ARCHITECTRUAL TROUGH. | | | | | | | | | | | | | MOUNTING HEIGHT 7'-6" AFF | | | | PROVIDE WITH PLASTIC SLEEVE OVER LAMPS | PROVIDE WITH FLANGE KIT WHERE RECESSED IN GYPSUM CEILING | NOTES | |

| • | H ⊗ ↓ | L, | G | FAA | FZ | FY-1 | 꾸 | FX | FW | F | FS | FR | FQ-1 | FQ | ΠP | TI Z | F S | TYPE |
|---|---|--|---|---|---|--|--|---|--|--|---|---|--|---|---|--|--|--------------|
| 1000 SQ FT, DUAL TECHNOLOGY MOTION SENSOR | THERMO PLASTIC LED EXIST SIGN, WHITE WITH RED LETTERS, UNIVERSAL FACE & UNIVERSAL MOUNTING 277V | CIAL EMERGENCY ANCE FREE BATTI NICS. | VAPOR TIGHT DIE-CAST ALUMINUM, INCANDESCENT, W/GLOBE AND GUARD. | FLUORESCENT DOWNLIGHT W/INTEGRAL FLUORESCENT DOWNLIGHT W/INTEGRAL ELECTRONIC BALLAST LOCATED IN BRACKET AND ETCHED CLEAR REFLECTOR. COLOR WHITE TO BE CONFIRMED BY ARCHITECT. 277V | COLOR-CHANGING RGB LED STRIPLIGHT W/CLEAR POLYCARBONATE LENS, 10° BEAM ANGLE, 45" LONG EXTRUDED ALUMINUM HOUSING, MOUNTING BRACKET, KEY PAD AND REMOTE CONTROLLER. STANDARD BLACK FINISH. 277V | 10" DIAMETER COMPACT FLUORESCENT LIGHT W/WHITE OPAL FLAT GLASS LENS AND INTEGRAL ELECTRONIC BALLAST. COLOR WHITE TO BE CONFIRMED BY ARCHITECT. | 10" DIAMETER COMPACT FLUORESCENT LIGHT W/WHITE OPAL FLAT GLASS LENS AND INTEGRAL ELECTRONIC BALLAST. COLOR WHITE TO BE CONFIRMED BY ARCHITECT. | 6" DIAMETER APERTURE COMPACT FLUORESCENT DOWNLIGHT/WALLWASHER W/SEMI-SPECULAR REFLECTOR AND INTEGRAL ELECTRONIC BALLAST. SELF-FLANGED FINISH. | EXTERIOR 8" DIAMETER APERTURE COMPACT FLUORESCENT DOWNLIGHT W/11" DIAMETER BY 11" HIGH DIE-CAST ALUMINUM HOUSING, 2 LAMPS, CLEAR ALUMINUM REFLECTOR, INTEGRAL ELECTRONIC BALLAST AND SUITABLE FOR WET LOCATION. CUSTOM COLOR TO BE CONFIRMED BY ARCHITECT. | POLE MOUNTED EXTERIOR METAL HALIDE FLOOD LIGHTS W/2 FIXTURES, ATTACHED MAGNETIC BALLASTS, SUITABLE FOR WET LOCATION. COLOR DARK BRONZE TO BE CONFIRMED BY ARCHITECT. | CONTINUOUS T8 FLUORESCENT PERIMETER DOWNLIGHT W/9"W APERTURE, 1-1/2"H WHITE BLADE BAFFLES LOCATED 1-1/2" AND INTEGRAL ELECTRONIC BALLAST. COLOR WHITE TO BE CONFIRMED BY ARCHITECT. | CONTINUOUS T8 FLUORESCENT STAGGERED CHANNEL W/ONE LAMP PROFILE AND INTEGRAL ELECTRONIC BALLAST. COLOR WHITE TO BE CONFIRMED BY ARCHITECT. | CONTINUOUS LINEAR T8 FLUORESCENT WALL WASHER W/9"W APERTURE, PARABOLIC SPECULAR REFLECTOR AND INTEGRAL ELECTRONIC BALLAST. COLOR WHITE TO BE CONFIRMED BY ARCHITECT. | JS STAGGERED LIN MOUNT WALL METRIC DISTRIBUTI AL ELECTRONIC BE CONFIRMED BY | 5" DIAMETER APERTURE COMPACT FLUORESCENT DOWNLIGHT W/SEMI-SPECULAR ALUMINUM REFLECTOR AND INTEGRAL ELECTRONIC BALLAST. SELF-FLANGED FINISH. | CONTINUOUS LINEAR FLUORESCENT W/ASYMMETRIC UPLIGHT REFLECTOR, INTEGRAL ELECTRONIC BALLAST. COLOR WHITE TO BE CONFIRMED BY ARCHITECT. | 5" DIAMETER APERTURE CERAMIC METAL HALIDE DOWNLIGHT W/WHITE DECORATIVE DROP GLASS TRIM, SEMI-SPECULAR ALUMINUM REFLECTOR, AND INTEGRAL ELECTRONIC BALLAST. COLOR WHITE TO BE CONFIRMED BY ARCHITECT. | DESCRIPTION |
| HUBBELL | DUAL-LITE LXURWI | DUAL-LITE LSCI | LUMARK IC-VW-1-G | EPL TRPV-42/7-ECOL-PM-CPY | COLOR KINETICS COLORBLAZE 48 (#116-000016-00), MOUNTING BRACKET ¡PLAYER 3 (#103-000019-00), KEY PAD (#103-000020-00) | BEGA L8437 | BEGA L8437 | EPL TRPH126/6-WW- ECOL-XXX | H.E. WILLIAMS PHC11/85-242T- EB-CS-WET | WIDELITE A2M-1000-A-XXX-Y. FIXTURE BRACKET #PM-2-HD | LITECONTROL 85N-1-X-T8-F- BW-CWM-X- ELB-X-XXX | H.E. WILLIAMS 74-4-132-X- EBLH2-XXX | LITECONTROL 20-1-X-T8-CWM- ELB-PR-XXX | SELUX M1AJ1-1T8-AMP- PM-170'-WH-XXX | EDISON PRICE LIGHTING TRPH126/5-ECOL-XXX | LEDALITE 3808-H01-E-N- X-X-XXX-E-W | ZUMTOBEL CHD5-39T6MH- X-OD5810-SA-T-502- WH-AD | MANUFACTURER |
| | LED | 2-10W HAL | 1-200W | 42WTTT/830 45W | COLOR CHANGING LED 280W | F26TTT/830 30W | F26TTT/830 30W | F26TTT/830 30W | (2) F42TTT/830 92W | (2) PHILLIPS MH1000/U/ BT37/637 2160W | T8/830 8W/LF | T8/830 8W/LF | T8/830 8W/LF | T8/830 8W/LF | F26TTT/830 30W | F54T5HO/830 65W | PHILLIPS CDM39/ T6/830 45W | LAMPS |
| CEILING SURFACE | CEILING/END/ WALL | WALL | WALL | STEM | BRACKET | WALL | WALL | RECESSED | SURFACE | BRACKET | RECESSED | COVE | RECESSED | RECESSED | RECESSED | SURFACE | RECESSED | MOUNTING |
| | MOUNTING HEIGHT 7'-6" AFF | MOUNT ING HEIGHT 7'-6" AFF | MOUNTING HEIGHT 6'-6" AFF | | MOUNTED IN COVE, PROVIDE 2 DAYS OF APPLICATION ENGINEERING. | MOUNTING HEIGHT 6'-0" AFF TO CENTER OF FIXTURE. | MOUNTING HEIGHT 4'-0" AFF TO CENTER OF FIXTURE. | | | 10' HIGH STRAIGHT STEEL POLE, CONTRACTOR AND ARCHITECT TO CONFIRM EXACT POLE HEIGHTS. | LENGTHS AS REQUIRED, COORDINATE MOUNTING W/SELECTED CEILING TYPE. | LENGTHS AS REQUIRED. | LENGTHS AS REQUIRED, COORDINATE MOUNTING W/SELECTED CEILING TYPE. | LENGTHS AS REQUIRED. | | LOCATED WITHIN ARCHITECTURAL COVE. | FIXTURE APPEARANCE TO MATCH "FL". | NOTES |

| GENERAL NOTES A SEE SHEET E00.00 FOR LEGEND AND GENERAL NOTES. | | SHEET NOTES |
|---|---|--|
| Issue Date & Issue Description By Check 01 12/03/08 LAM BHG 75% CONSTRUCTION DOCUMENTS 02 01/23/09 LAM BHG 95% CONSTRUCTION DOCUMENTS 03 10/28/09 LAM BHG ISSUED FOR PERMIT | Sinte 200 Washington, DC 20006 Telephone 202.721.5200 Facsimile 202.872.8587 ASSOCIATES, INC. 349 Centom Read-Sum Perford, ACC4006 Figure 174.12770 Figure 174.1244 www.sell.com engineers - crichitects - surveyors - construction managers | Portland International Jetport 1001 Westbrook Street Portland, Maine 04102 |