

A09.00

 SHEET NOTES 1.HOUR SHAFT CONNECTING LESS THAN 4 STORIES 2. ATRIUM ENCLOSURE PER IBC 404.5 EXCEPTION 1 3. 1.HOUR ATRIUM ENCLOSURE PER IBC 404; (B) COMMUNICATION SPACE (MINI ATIRUM) PER NFPA 101 8.6.6 5. MECHANICAL MEZZANINE: IBC 505.3 EXCEPTION 1 ALLOWS SINGLE MEANS OF EGRESS. SIZE OF ROOM CREATES COMMON PATH OF TRAVEL OVER 75', SO TWO EXITS ARE PROVIDED 6. AUTOMATIC SLIDING ENTRANCES WITH BREAK-OUT PANELS 	<section-header><section-header><section-header></section-header></section-header></section-header>
	Date Description 09/22/08 DESIGN DEVELOPMENT 12/03/08 75% CONSTRUCTION DOCUMENTS 01/23/09 95% CONSTRUCTION DOCUMENTS 10/26/09 ISSUED FOR PERMIT 2 11/12/09 ADDENDUM #2
GENERAL NOTES A IBC 302.3.1: NON SEPARATED USE: FIRE SEPARATIONS ARE REQUIRED BY WEEN USES, EXCEPT AS REQUIRED BY OTHER PROVISIONS. B REFER TO A00.10 FOR OCCUPANT LOAD AND EGRESS REQUIREMENTS FOR DETAILED EGRESS CRITERIA C NOT IN CONTRACT (NIC) D AHOUR SPRAY-ON FIRE PROOFING ON UNDERSIDE OF SLAB ABOVE F AHOUR SPRAY-ON FIRE PROOFING ON UNDERSIDE OF SLAB ABOVE F AHR FIRE SEPARATION RATING G EXIT STAIR LOCATION H EC, FHC, DIF (DEFIBRILLATOR) AND/OR SPC (STANDPIPE CONNECTION)	<section-header><section-header><section-header><section-header><section-header><section-header><section-header><section-header></section-header></section-header></section-header></section-header></section-header></section-header></section-header></section-header>