	LIGHT FIXTURE SCHEDULE									
YPE	DESCRIPTION	MANUFACTURER	LAMPS	MOUNTING	NOTES					
A	2'x4', 2 LAMP, DIRECT/INDIRECT W/CENTER PERFORATED BASKET 277V	COLUMBIA STR24-254G-MPO-LW	2-54W T5HO	RECESSED/ SURFACE	PROVIDE WITH FLANGE KIT WHERE RECESSED IN GYPSUM CEILING					
В	1'x4' INDUSTRIAL FIXTURE W/ELECTRONIC BALLAST AND WIRE GUARD	COLUMBIA KL4-332-LW3U-KLWG4	3-32W T8	CHAIN HUNG	PROVIDE WITH PLASTIC SLEEVE OVER LAMPS. CONTRACTOR SHALL PROVIDE NECESSARY UNI-STRUT OR OTHER HANGING SYSTEM TO ALLOW LIGHTS TO HANG FROM STRUCTURE OR CONCRETE DECKING. LIGHTS SHALL NOT BE SUPPORTED FROM CATWALKS OR OTHER NON-STRUCTURAL ITEMS. WHERE ATTACHING TO OVERHEAD CONCRETE DECKING, CONTRACTOR SHALL USE FITTINGS THAT WILL ENSURE THE RADIANT TUBING EMBEDDED IN THE SLAB W NOT BE COMPROMISED.					
B1	1'x4' INDUSTRIAL FIXTURE W/ELECTRONIC BALLAST	COLUMBIA	2-32W	CHAIN						
С	277V 2'x4' ACRYLIC LENSED W/ELECTRONIC BALLAST	COLUMBIA 4PS-232-A19-LWU	2-32W T8	HUNG RECESSED	PROVIDE WITH FLANGE KIT WHERE RECESSED IN GYPSUM CEILING					
C1	277V 2'x4' 3 LAMP ACRYLIC LENSED TROFFER W/ELECTRONIC BALLAST. DAMP LOCATION RATED 277V	COLUMBIA 4PS-332F-A19-LWU	3-32W T8	RECESSED	PROVIDE WITH FLANGE OPTION FOR MOUNTING IN GYPSUM CEILING					
D	2'x2', 2 LAMP, DIRECT/INDIRECT W/PERFORATED CENTER BASKET.	COLUMBIA STR22-217G-MPO-LWU	2-17W T8	RECESSED						
F	6" SQUARE x 4' , DIRECT/INDIRECT FLUORESCENT ACRYLIC LENS	ALERA F4-2UDT8-WMNA-A19- LWU-MW-4	2-32W T8	WALL	MOUNTING HEIGHT 7'-6" AFF					
FA	8" CYLINDRICAL COMPACT FLUORESCENT DOWNLIGHT W/INTEGRAL ELECTRONIC BALLAST, CUSTOM COLOR TO MATCH SHERWIN WILLIAMS SW7048 URBANE. COLOR TO BE CONFIRMED BY ARCHITECT.	SEE PROJECT MANUAL	F42TTT/830 46W	BRACKET						
FB	ASYMMETRIC CERAMIC METAL HALIDE UPLIGHT W/SPECULAR EXTRUDED ALUMINUM REFLECTOR, MICRO-PRISMATIC TEMPERED GLASS LENS, SOLID CUT-OFF VISOR, INTEGRAL MAGNETIC BALLAST. CUSTOM COLOR TO MATCH SHERWIN WILLIAMS SW7048 URBANE. COLOR TO BE CONFIRMED BY ARCHITECT.	SEE PROJECT MANUAL	PHILLIPS CDMELITE MW210/T9/ 930/U/E 250W	BRACKET						
FC	6"x8' ONE LAMP PROFILE STAGGERED LINEAR FLUORESCENT TROFFER W/MICRO-PYRAMIDAL LENS AND INTEGRAL ELECTRONIC BALLAST. COLOR WHITE TO BE CONFIRMED BY ARCHITECT.	SEE PROJECT MANUAL	(3) F39T5HO/830 136W	RECESSED						
FD	2' DIAMETER 4-LAMP PROFILE LINEAR FLUORESCENT TROFFER W/CONCAVE ACRYLIC LENS AND INTEGRAL ELECTRONIC BALLAST. COLOR WHITE TO BE CONFIRMED BY ARCHITECT.	SEE PROJECT MANUAL	(4) F17T8/830 66W	RECESSED						
FD-1	3' DIAMETER 4-LAMP PROFILE LINEAR FLUORESCENT TROFFER W/CONCAVE ACRYLIC LENS AND INTEGRAL ELECTRONIC BALLAST. COLOR WHITE TO BE CONFIRMED BY ARCHITECT.	SEE PROJECT MANUAL	(4) F25T8/830 96W	RECESSED						
-D-2	4' DIAMETER 6-LAMP PROFILE LINEAR FLUORESCENT TROFFER W/CONCAVE ACRYLIC LENS AND INTEGRAL ELECTRONIC BALLAST. COLOR WHITE TO BE CONFIRMED BY ARCHITECT.	SEE PROJECT MANUAL	(6) F32T8/830 177W	RECESSED						
FE	NOT USED									
FF	6" DIAMETER APERTURE COMPACT FLUORESCENT DOWNLIGHT W/SEMI-SPECULAR ALUMINUM REFLECTOR AND INTEGRAL ELECTRONIC BALLAST. COLOR WHITE TO BE CONFIRMED BY ARCHITECT.	SEE PROJECT MANUAL	F26TTT/830 30W	RECESSED						
FF-1	6" DIAMETER APERTURE COMPACT FLUORESCENT DOUBLE WASHLIGHT W/SEMI-SPECULAR ALUMINUM REFLECTOR, 45° CUT-OFF ANGLE AND INTEGRAL ELECTRONIC BALLAST. COLOR WHITE TO BE CONFIRMED BY ARCHITECT.	SEE PROJECT MANUAL SEE PROJECT MANUAL	F26TTT/830 30W F26TTT/830 30W	RECESSED RECESSED						
-F-3	6" DIAMETER APERTURE COMPACT FLUORESCENT WASHLIGHT W/SEMI-SPECULAR ALUMINUM 277V BEELLEMEORRASPERITUREFCAMBRACAMDUNTESRAINT EXPENIEM WASHALIGAST WOSEMRSAFIE TO BE AND INTEGRAL ELECTRONIC BALLAST. COLOR WHITE TO BE CONFIRMED BY ARCHITECT. 277V	SEE PROJECT MANUAL	F26TTT/830 30W	RECESSED						
FG	8" DIAMETER CERAMIC METAL HALIDE DOWNLIGHT W/INTEGRAL ELECTRONIC BALLAST. CUSTOM COLOR TO MATCH SHERWIN WILLIAMS SW7048 URBANE. COLOR TO BE CONFIRMED BY ARCHITECT.	SEE PROJECT MANUAL	PHILLIPS CDM100/ PAR38/ FL/3K/ALTO 125W	BRACKET						
FH	COMPACT FLUORESCENT CHANNEL W/FLEXIBLE CONNECTORS AND INTEGRAL ELECTRONIC BALLAST. COLOR WHITE TO BE CONFIRMED BY ARCHITECT.	SEE PROJECT MANUAL	(11) F18TT5/830 242W	SURFACE	12" SPACING AND LOCATED IN ARCHITECTRUAL TROUGH.					
FJ	EXTERIOR 2-WAY LINEAR FLUORESCENT UPLIGHT W/2 FIXTURE RUNS, CUT-OFF VISOR, 2'-10" STEM AND INTEGRAL ELECTRONIC BALLASTS. SUITABLE FOR WET LOCATION. CUSTOM COLOR TO MATCH SHERWIN WILLIAMS URBANE SW7048. COLOR TO BE CONFIRMED BY ARCHITECT.	SEE PROJECT MANUAL	(2) F32T8/830 59W	PENDANT	MOUNTING HEIGHT 10'-0" AFF TO BOTTOM OF FIXTURE.					
FK	5" DIAMETER METAL HALIDE DOWNLIGHT W/SPREAD LENS AND ATTACHED ELECTRONIC BALLAST. CUSTOM COLOR TO MATCH SHERWIN WILLIAMS SW7048 URBANE. COLOR TO BE CONFIRMED BY ARCHITECT. 277V	SEE PROJECT MANUAL	PHILLIPS CDM35/ PAR30L/M/ FL/3K/ALTO 45W	SURFACE						
FL	6" DIAMETER APERTURE COMPACT FLUORESCENT DOWNLIGHT W/WHITE DECORATIVE DROP GLASS TRIM, SEMI-SPECULAR ALUMINUM REFLECTOR AND INTEGRAL ELECTRONIC BALLAST. CUSTOM COLOR TO MATCH SHERWIN WILLIAMS PORPOISE SW7047. COLOR TO BE CONFIRMED BY ARCHITECT.	SEE PROJECT MANUAL	F42TTT/830 45W	RECESSED	FIXTURE APPEARANCE TO MATCH "FM".					

TYPE	DESCRIPTION	MANUFACTURER	LAMPS	MOUNTING	NOTES
FM	5" DIAMETER APERTURE CERAMIC METAL HALIDE DOWNLIGHT W/WHITE DECORATIVE DROP GLASS TRIM, SEMI-SPECULAR ALUMINUM REFLECTOR, AND INTEGRAL ELECTRONIC BALLAST. CUSTOM COLOR TO MATCH SHERWIN WILLIAMS PORPOISE SW 7047. COLOR TO BE CONFIRMED BY ARCHITECT.	SEE PROJECT MANUAL	PHILLIPS CDM39/ T6/830 45W	RECESSED	FIXTURE APPEARANCE TO MATCH "FL".
FP	5" DIAMETER APERTURE COMPACT FLUORESCENT DOWNLIGHT W/SEMI-SPECULAR ALUMINUM REFLECTOR AND INTEGRAL ELECTRONIC BALLAST. SELF-FLANGED FINISH.	SEE PROJECT MANUAL	F26TTT/830 30W	RECESSED	
FQ	4" W APERTURE CONTINUOUS STAGGERED LINEAR FLUORESCENT PERIMETER MOUNT WALL GRAZING FIXTURE W/ASYMMETRIC DISTRIBUTION, WHITE LOUVER AND INTGRAL ELECTRONIC BALLAST. COLOR WHITE TO BE CONFIRMED BY ARCHITECT.	SEE PROJECT MANUAL	T8/830 8W/LF	RECESSED	LENGTHS AS REQUIRED
FR	CONTINUOUS T8 FLUORESCENT STAGGERED CHANNEL W/ONE LAMP PROFILE AND INTEGRAL ELECTRONIC BALLAST. COLOR WHITE.	SEE PROJECT MANUAL	T8/830 8W/LF	COVE MOUNTED	LENGTHS AS REQUIRED
FS	CONTINUOUS T8 FLUORESCENT PERIMETER DOWNLIGHT W/9"W APERTURE, 1-1/2"H WHITE BLADE BAFFLES LOCATED 1-1/2" AND INTEGRAL ELECTRONIC BALLAST. COLOR WHITE.	SEE PROJECT MANUAL	T8/830 8W/LF	RECESSED	LENGTHS AS REQUIRED COORDINATE MOUNTING W/SELECTED CEILING TYPE.
FV	POLE MOUNTED EXTERIOR METAL HALIDE FLOOD LIGHTS W/2 FIXTURES, ATTACHED MAGNETIC BALLASTS, SUITABLE FOR WET LOCATION. COLOR DARK BRONZE.	SEE PROJECT MANUAL	(2) PHILLIPS MH1000/U/ BT37/637 2160W	BRACKET	10' HIGH STRAIGHT STEE POLE, CONTRACTOR AN ARCHITECT TO CONFIRM EXACT POLE HEIGHTS.
FV-1	POLE MOUNTED EXTERIOR METAL HALIDE FLOOD LIGHTS W/3 FIXTURES, ATTACHED MAGNETIC BALLASTS, SUITABLE FOR WET LOCATION. COLOR DARK BRONZE	SEE PROJECT MANUAL	(3) PHILLIPS MH1000/U/ BT37/637 3240W	BRACKET	10' HIGH STRAIGHT STEE POLE, CONTRACTOR AN ARCHITECT TO CONFIRM EXACT POLE HEIGHTS.
FX	6" DIAMETER APERTURE COMPACT FLUORESCENT DOWNLIGHT/WALLWASHER W/SEMI-SPECULAR REFLECTOR AND INTEGRAL ELECTRONIC BALLAST. SELF-FLANGED FINISH.	SEE PROJECT MANUAL	F26TTT/830 30W	RECESSED	
FZ	COLOR-CHANGING RGB LED STRIPLIGHT W/CLEAR POLYCARBONATE LENS, 10° BEAM ANGLE, 45" LONG EXTRUDED ALUMINUM HOUSING, MOUNTING BRACKET, KEY PAD AND REMOTE CONTROLLER. STANDARD BLACK FINISH.	SEE PROJECT MANUAL	COLOR CHANGING LED 280W	BRACKET	MOUNTED IN COVE, PROVIDE 2 DAYS OF APPLICATION ENGINEERING.
FAB	3" DIAMETER CYLINDRICAL DOWNLIGHT IN ALUMINUM HOUSING W/SPREAD LENS AND HONEYCOMB BAFFLE. CUSTOM PAINT TO MATCH SHERWIN WILLIAMS PORPOISE SW7047. COLOR TO BE CONFIRMED BY ARCHITECT.	SEE PROJECT MANUAL	PAR 20/NFL 50W	WALL	MOUNTING HEIGHT 7'-6" AFF TO BOTTOM OF FIXTURE
FAC	11" SQUARE x 6"D COMPACT FLUORESCENT DOWNLIGHT IN DIE-CAST ALUMINUM HOUSING WITH INTERNAL SEMI-SPECULAR ANODIZED ALUMINUM REFLECTOR, CUT-OFF SHIELDED, ETCHED TEMPERED GLASS LENS, LOUVERED ALUMINUM FACE PLATE, AND INTEGRAL ELECTRONIC BALLAST. SUITABLE FOR WET LOCATION. CUSTOM PAINT TO MATCH SHERWIN WILLIAMS PORPOISE SW7044 ANAZING GRAX. COLOR TO BE CONFIRMED BY ARCHITECT.	SEE PROJECT MANUAL	42WTTT/830 45W	WALL	MOUNTING HEIGHT 9'-0" AFF TO CENTER OF FIXTURE
G	VAPOR TIGHT DIE-CAST ALUMINUM, INCANDESCENT, W/GLOBE AND GUARD.	LUMARK IC-VW-1-G	1-200W	WALL	MOUNTING HEIGHT 6'-6" AFF
Н	6" DIAMETER APERTURE COMPACT FLUORESCENT DOWNLIGHT W/SEMI-SPECULAR ALUMINUM REFLECTOR AND INTEGRAL ELECTRONIC BALLAST. COLOR WHITE TO BE CONFIRMED BY ARCHITECT.	SEE PROJECT MANUAL	F26TTT/830 30W	RECESSED	
J	2' x 2', 2 LAMP, ACRYLIC LENSED FIXTURE WITH ELECTRONIC BALLAST.	COLUMBIA 4PS22-231U16- FSA19-LWU	2-31W U LAMP	RECESSED	
K	100W, METAL HALIDE, FULL CUTOFF WALL PACK. BRONZE IN COLOR.	HUBBEL LMC-100P-6-1	1-100W MH	WALL	MOUNTING HEIGHT 10'-0" AFF
M	4' x 9" SURFACE MOUNTED WRAPAROUND LENSED FIXTURE WITH INTEGRAL MOTION SENSOR.	LUMINAIRE VPF84-232 ELECT-277-BK-WET	2-32W T8	SURFACE	SHALL BE WET LOCATION RATED
N	9"X4' SURFACE MOUNTED WRAP AROUND FIXTURE WITH ELECTRONIC BALLAST.	COLUMBIA AWN4-232-EU	2-32W T8	SURFACE	
0	LED ARCHITECTURAL FLOODLIGHT WITH ADJUSTABLE KNUCKLE MOUNT. PROVIDE WALL MOUNT AND BARN DOORS. ALL SHALL BE PAINTED	KIM CFL1-27L3KUV- CC-BD-CFL-JW	LED	SURFACE	MOUNTING HEIGHT AS INDICATED ON DRAWING
	"URBAN BRONZE" PER ARCHITECT COMMERCIAL EMERGENCY LIGHT WITH MAINTENANCE FREE BATTERY AND SELF TESTING ELECTRONICS.	DUAL-LITE LSCI	2-10W HAL	WALL	MOUNTING HEIGHT 7'-6" AFF
→	THERMO PLASTIC LED EXIST SIGN, WHITE WITH RED LETTERS, UNIVERSAL FACE & UNIVERSAL MOUNTING	DUAL-LITE LXURWI	LED	CEILING/END/ WALL	MOUNTING HEIGHT 7'-6". UNLESS NOTED OTHERV ON DRAWINGS.
	277V 1000 SQ FT, DUAL TECHNOLOGY MOTION SENSOR	HUBBELL		CEILING	ON DIMINUO.

SHEET NOTES

Portland International Jetport

1001 Westbrook Street Portland, Maine 04102

Gensler

2020 K Street, NW Suite 200 Washington, DC 20006 Telephone 202.721.5200 Facsimile 202.872.8587



343 Gorham Road, South Portland ME 04106 P: (207) 761-1770 F: (207) 774-1246 www.amec.com

THESE DRAWINGS ARE ISSUED FOR CONSTRUCTION AND REFLECT ALL AMEC ISSUED BULLETINS AND SKETCHES.

Issue Date & Issue Description LAM BHG 75% CONSTRUCTION DOCUMENTS 02 01/23/09 **GENERAL NOTES** 95% CONSTRUCTION DOCUMENTS 03 10/26/09 A SEE SHEET E00.00 FOR LEGEND AND ISSUED FOR PERMIT 04 11/02/09 LAM BHG ADDENDUM #1 B ALL BALLASTS SHALL MEET EFFICIENCY 02 05 11/12/09 LAM BHG MAINES REBATE PROGRAM ADDENDUM #2 REQUIREMENTS AND BE SELECTED FROM

03 06 11/20/09

ADDENDUM #3 145 07 09/01/11 LAM BHG ISSUED FOR CONSTRUCTION

LAM BHG

PWM Terminal Enhancement

, 09.6395.000 C:\AMEC\5330101\E00.10.dwg ELECTRICAL LIGHT FIXTURE SCHEDULE

E00.10

ELECTRICAL LIGHT FIXTURE SCHEDULE SCALE: NOT TO SCALE

GENERAL NOTES.

THE PRE-APPROVED LIST FOUND AT

WWW.EFFICIENCYMAINE.COM