



CITY OF PORTLAND, MAINE
Department of Building Inspection

Certificate of Occupancy

LOCATION Yellowbird Rd (199-A-001)

Issued to City of Portland/HAL Associates

Date of Issue 10 July 1998

This is to certify that the building, premises, or part thereof, at the above location, built — altered — changed as to use under Building Permit No. 980341, has had final inspection, has been found to conform substantially to requirements of Zoning Ordinance and Building Code of the City, and is hereby approved for occupancy or use, limited or otherwise, as indicated below.

PORTION OF BUILDING OR PREMISES

APPROVED OCCUPANCY

Entire

Air Cargo Apron

Limiting Conditions:

This certificate supersedes
certificate issued

Approved:

7/10/98
(Date)

Tammy Munson
Inspector

G. Samuel P. Hoffee
Inspector of Buildings

Notice: This certificate identifies lawful use of building or premises, and ought to be transferred from owner to owner when property changes hands. Copy will be furnished to owner or lessee for one dollar.

City of Portland, Maine – Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716

Location of Construction: Yellowbird Rd		Owner: HLJ Associates		Phone: 772-0943		Permit No: 980341			
Owner Address:		Lessee/Buyer's Name:		Phone:		BusinessName:			
Contractor Name: Benchmark		Address: 650 Main St		Phone: 874-2963		<div style="border: 2px solid black; padding: 5px;"> PERMIT ISSUED Permit Issued: APR 10 1998 CITY OF PORTLAND </div>			
Past Use: vacant		Proposed Use: 2000xcommercial		COST OF WORK: \$ 360,000				PERMIT FEE: \$ 1,820	
Proposed Project Description: 3000 sq. ft. air cargo apron with 20' x 10' sign office etc.				FIRE DEPT. <input type="checkbox"/> Approved <input type="checkbox"/> Denied		INSPECTION: U. Use Group: Type:			
				Signature: <i>[Signature]</i>		Signature: <i>[Signature]</i>			
Permit Taken By: Sherry Pinard				Date Applied For: April 3, 1998				Zone: CBL: 199-A-1	
				PEDESTRIAN ACTIVITIES DISTRICT (P.A.D.) Action: <input type="checkbox"/> Approved <input type="checkbox"/> Approved with Conditions <input type="checkbox"/> Denied Signature: _____ Date: _____				Zoning Approval: Special Zone or Reviews: <input type="checkbox"/> Shoreland <input type="checkbox"/> Wetland <input type="checkbox"/> Flood Zone <input type="checkbox"/> Subdivision <input type="checkbox"/> Site Plan maj <input type="checkbox"/> minor <input type="checkbox"/> mm <input type="checkbox"/>	

1. This permit application does not preclude the Applicant(s) from meeting applicable State and Federal rules.
2. Building permits do not include plumbing, septic or electrical work.
3. Building permits are void if work is not started within six (6) months of the date of issuance. False information may invalidate a building permit and stop all work..

call for p/e 874-2963 (mark woodward)

PERMIT ISSUED WITH REQUIREMENTS

CERTIFICATION

I hereby certify that I am the owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his authorized agent and I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in the application is issued, I certify that the code official's authorized representative shall have the authority to enter all areas covered by such permit at any reasonable hour to enforce the provisions of the code(s) applicable to such permit

SIGNATURE OF APPLICANT: *[Signature]* ADDRESS: _____ DATE: _____ PHONE: _____
Mark Woodward

RESPONSIBLE PERSON IN CHARGE OF WORK, TITLE: _____ PHONE: _____

CEO DISTRICT 4

COMMENTS

4-13-98 Pre construction mtg. w/ Benchmark (Mark Woodward), etc.
 Discussed Steel-10r Bldg. Re-reinforcing to be inspected prior to pour
 SS Waterwtr system installed per submitted. 14" slope on t-box piping.
 w Chambers on row - installed level. Gravel on either side as req'd. OK to b-fill.
 4-17-98 Footing inspection - layout by best & Benchmark. Dragon supplied 3,000 psi
 mix, rebar added to footing @ base of columns.

4-19-98 Roughin Plumbing - had test on - held for 15 minutes - checked
 under ground & Slab plumbing.

4/30/98 - work progressing - structure framing complete - interior walls
 framed - all roof bearing -
 * Opening in slab under shower - needs to be filled in.

4/22/98 - Need verification on roof for design because heating unit is hung off
 steel beams of roof (1/12 pitch)
 Told them they need site inspection -

All building requirements - OK -
 Want engineering verification on
 roof structural adequacy to hold
 heating system. T.M.

	Type	Inspection Record	Date
Foundation:	OK		
Framing:	OK		
Plumbing:	OK		
Final:			5/98
Other:			

BUILDING PERMIT REPORT

DATE: 9 APRIL 98 ADDRESS: Yellowbird Rd.
 REASON FOR PERMIT: 3000 SQ. FT. air cargo apron.
 BUILDING OWNER: _____
 CONTRACTOR: Benchmark
 PERMIT APPLICANT: Mark Woodward
 USE GROUP S-2 BOCA 1996 CONSTRUCTION TYPE 2-C

CONDITION(S) OF APPROVAL

This Permit is being issued with the understanding that the following conditions are met:

Approved with the following conditions: *1, *2, *6, *17, *20, *24, *25, *27, *29, *30, *31

- *1. This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.
- *2. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection)
3. Precaution must be taken to protect concrete from freezing.
4. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.
5. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996)
- *6. All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993).
7. Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214.0 of the city's building code.
8. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not be less than 30", but not more than 38".) Handrail grip size shall have a circular cross section with an outside diameter of at least 1 1/4" and not greater than 2".
9. Headroom in habitable space is a minimum of 7'6".
10. Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group minimum 11" tread 7" maximum rise.
11. The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6' 8")
12. Every sleeping room below the fourth story in buildings of use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft.
13. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units.
14. All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self closer's. (Over 3 stories in height requirements for fire rating is two (2) hours.)
15. The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by providing automatic extinguishment
16. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the

provisions of the City's Building Code Chapter 9, Section 19, 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):

- In the immediate vicinity of bedrooms
- In all bedrooms
- In each story within a dwelling unit, including basements

In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required)

A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type.

17. The Fire Alarm System shall be maintained to NFPA #72 Standard.

18. The Sprinkler System shall maintained to NFPA #13 Standard.

* 19. All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023, & 1024. Of the City's building code. (The BOCA National Building Code/1996)

20. Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".

21. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services.

22. Ventilation shall meet the requirements of Chapter 12 Sections 1210. Of the City's Building Code.

* 23. All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade.

* 24. All requirements must be met before a final Certificate of Occupancy is issued.

25. All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code. (The BOCA National Building Code/1996).

* 26. Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical Code/1993).


27. Please read and implement the attached Land Use-Zoning report requirements.

* 28. All site plan requirements as stated by The Planning Board must be met.

29. This plan must have State Fire Marshall approval

30. Permits are required from the Portland Fire Dept. for storage of flammable liquids and others.

32


P. Samuel Hoffses, Code Enforcement

cc: L.L. McDougall, PFD
Marge Schmuekel