STAGELINE® SL 320

CITY OF PORTLAND, MAINE
Reviewed for Code Compliance
Inspections Division
Approved with Conditions
Date: 07/31/17

Courtesy of: Michel Fortin

LEADING DESIGNER AND MANUFACTURER OF MOBILE STAGES AND PROMOTIONAL UNITS

vancouver 2010
Supplier

- **CONFIGURATION:**
  40' x 40' (12.19 m x 12.19 m)
  72' x 40' (21.95 m x 12.19 m)
  WITH EXTENSION PLATFORMS

- **SET UP TIME:**
  2 1/2 HOURS
  1 CERTIFIED TECHNICIAN
  3 STAGEHANDS

- **WIND RESISTANCE:**
  90 MPH (145 KM/H) WITHOUT WINDWALLS
  60 MPH (97 KM/H) WITH WINDWALLS

- FULL HEIGHT RAINPROOF WINDWALLS ON 3 SIDES

- CERTIFIED BY PROFESSIONAL ENGINEERS IN EVERY STATE AND PROVINCE

WWW.STAGELINE.COM

STAGELINE® SL 320

Reviewed for Code Compliance
Inspections Division
Approved with Conditions
Date: 07/31/17

SPECIFICATIONS:

- **Load bearing capacity:** 26,000 lb (11,793kg)
- **Roof maximum load capacity:** 18,000 lb (8,165kg)
- **Roof maximum height:** 26'-1" (7.95 m) from deck
- **Clearance:** 24'-4" to 22'-9" (7.43 m to 6.93 m) from deck
- **Lateral rigging beams:**
  For rigging sound including line arrays
  Capacity: 4,000 lb at 6' (907 kg at 1.83 m) per side
  Height: 31'-0" (9.45 m) from ground
- **Overall height from ground:** 32'-4" (9.86 m)
- **Floor:**
  Size: 40' x 40' (12.19 m x 12.19 m)
  Capacity: Rated at 100 lb / sq. ft (500 kg/m^2)
  Height: 3'-6" to 6' (1.07 m to1.83 m)
- **Roof:** fiberglass bonded to steel
- **24 rigging points**
- **1 stairway with handrails**
- **Storage capacity:** 5,000 lb (2,268 kg)

OPTIONAL:

- **Fire retardant windwalls on 3 sides:**
  Vinyl or mesh
  Full color graphic printing
- **Skirting**
- **Sound wing extensions:**
  16' x 12' (4.87 m x 3.65 m) with guardrails
- **Additional decks :** up to 72' x 44' (21.95 m x 13.41 m) with 4' x 8' (1.22 m x 2.44 m) extension platforms
- **2 Lateral banner supports:**
  up to 16' x 26'-4" (4.87 m x 8.03 m)
- **Publicity space:**
  Rolling billboard to maximize visibility during transportation
  Multiple banners of various sizes attach to structure for optimum visibility
- **Guardrails**
- **Sound wing covers**
- **2 Bi-Directional Rigging Beams:** 4,000 lb (1,814 kg)

Set up Time: 2 1/2 hours

Manpower: 4 x

Why the industry chooses Stageline® products :

- **Manufacturing:** Stageline has built over 500 units.
- **Expertise:** Stageline has been designing mobile stages for over 25 years.
- **100% fail proof history:** Best safety record in the industry.
- **Reliability in engineering:** Highest wind resistance, with or without windwalls.
- **Wide range of models:** SL50, SL100, SL100-Mix, SL260, SL320, SAM555, Promobile, Covered wings & Backstage.
- **Rain or shine:** Complete rainproofing with full height windwalls and downstage canopies.
- **Single trailer:** All stage components travel in one stage trailer unit.
- **Quality:** Designed and built to last over 25 years.
  All units built to date are still in operation.
  Quality controlled with a 600-point inspection.
- **Standards:** All units are engineered to withstand 2 times the permitted load.

Tel: +1 450-589-1063
Fax: +1 450-589-1711
North America: 1 800-267-8243
www.stageline.com

Tough, safe and economical, STAGELINE mobile stages are built and field-tested by production professionals to meet the needs of your most demanding and varied outdoor projects. With over ten thousand successful events in more than 35 countries each year, these innovative products are considered by many to be the industry standard.

Due to Stageline's product improvement policy, technical specifications may change without notice.