

2nd FLOOR FRAMING PLAN
S2.1 SCALE: 1/8" = 1'-0"

## **FLOOR FRAMING NOTES:**

- 1. FLOOR FRAMING SHALL BE AS FOLLOWS:
  - A. TENANT, & UTILITY ROOM FLOOR FRAMING SHALL BE 22" DEEP PRE-ENGINEERED OPEN WEB TRUSSES @ 24" O.C.
  - CORRIDOR FRAMING SHALL BE 2X8 NO. 2 SYP JOISTS @ 24" O.C. TYPICAL.
- C. STAIR MID-LANDING FRAMING SHALL BE 2X10 @ 16" O.C.
- INDICATES WOOD BEAM/HEADER DESIGNATION. SEE BEAM/HEADER SCHEDULE ON S2.0 FOR ADD'L INFO.
- 3. "C2" INDICATES BUILT-UP COLUMN DESIGNATION. BUILT-UP COL DESIGNATIONS ON S2.1A AND S2.1B APPLY TO ALL FLOORS U.N.O. SEE COL SCHEDULE ON S2.0 FOR ADD'L INFO.
- 4. SEE S5 SERIES DWGS FOR ALL SHEAR WALL AND ANCHORAGE LOCATIONS.
- 5. SEE S7 SERIES DWGS FOR TYP FRAMING DETAILS AND INFO.
- 6. SEE ARCH DWGS FOR EXACT FINISHED FLOOR ELEVATIONS.
- 7. SEE GENERAL NOTES FOR LUMBER SPECIES AND GRADE REQ'S.
- 8. ALL COL'S, INCLUDING STUD PACKS, MUST ALIGN FLOOR—TO—FLOOR WITH SOLID BLOCKING OF THE SAME SIZE AND DIMENSION AS THE COL ABOVE, AT FLOOR CAVITY LOCATIONS. CONTINUE TO FDN OR BEAM SUPPORT BELOW.
- 9. ALL CONNECTOR TYPES REFER TO SIMPSON STRONG-TIE SPECIFICATIONS. SEE GEN NOTES FOR ADD'L INFO.
- 10. EXXXXXX DENOTES CMU WALL. SEE GENERAL NOTES AND S9.1 FOR ADD'L INF & DESIGNATIONS.
- FLOOR DIAPHRAGM THIS AREA TO BE BLOCKED SOLID @ ALL PANEL EDGES USING Z2 CLIPS AND ALL PANEL EDGES FASTENED W/ 10d NAILS @ 6"

## PORTLAND HILTON GARDEN INN ADDITION


LOCATION

PORTLAND

145 JETPORT BLVD PORTLAND, MAINE 04102







ISSUED FOR: REVIEW PRICING JULY 20, 2012 ■ PERMITTING JAN 30, 2013

CONSTRUCTION

REVISIONS

IS NOT TO BE REPRODUCED OR COPIED IN WHOLE OR IN PART. IT IS ONLY TO BE USED FOR THE PROJECT SPECIFICALLY IDENTIFIED HEREIN AND IS NOT TO BE USED ON ANY OTHER PROJECT. IT IS TO BE RETURNED UPON REQUEST. SCALES AS STATED HEREIN ARE VALID ON THE ORIGINAL DRAWING, THE DIMENSIONS OF WHICH ARE 30x42 INCHES.

□JOBNO.

0479.000 DRAWING TITLE

2nd FLOOR FRAMING PLAN