City of Portland, Maine - Building or Use Permit Application, 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716 Phone: 761-9240 Location of Construction: Permit No: 1020 Owner: Thomas & Cypthia Dykes *** 18 Tide Mill Rd. Lessee/Buyer's Name: Owner Address: Phone: BusinessName: 18 Tide Mill Rd. Permit Issued: Contractor Name: Address: Phone: Sheds USA COST OF WORK: PERMIT FEE: Past Use: Proposed Use: \$1,329.00 \$ 36,00 Same Single Family FIRE DEPT. Approved INSPECTION: Use Group: 4 Type ☐ Denied Zone: CBL: BOCAGG 212-A-060 Signature: Proposed Project Description: Zoning Approval PEDESTRIAN ACTIVITIES DISTRICT Action: Approved Special Zone or Reviews: Storage shed Approved with Conditions: ☐ Shoreland Denied □Wetland ☐ Flood Zone Signature: □ Subdivision Date: ☐ Site Plan maj ☐minor ☐mm ☐ Permit Taken By: Date Applied For: Gayle September 12, 2000 GG Zoning Appeal □ Variance This permit application does not preclude the Applicant(s) from meeting applicable State and Federal rules. ☐ Miscellaneous Building permits do not include plumbing, septic or electrical work. ☐ Conditional Use ☐ Interpretation 3. Building permits are void if work is not started within six (6) months of the date of issuance. False informa-☐ Approved tion may invalidate a building permit and stop all work... □ Denied Historic Preservation □ Not in District or Landmark ☐ Does Not Require Review ☐ Requires Review Action: CERTIFICATION ☐ Appoved I hereby certify that I am the owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been ☐ Approved with Conditions ☐ Denied authorized by the owner to make this application as his authorized agent and I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in the application is issued, I certify that the code official's authorized representative shall have the authority to enter all Date: areas covered by such permit at any reasonable hour to enforce the provisions of the code(s) applicable to such permit September 12, 2000 SIGNATURE OF APPLICANT ADDRESS: DATE: PHONE:

White-Permit Desk Green-Assessor's Canary-D.P.W. Pink-Public File Ivory Card-Inspector

PHONE:

RESPONSIBLE PERSON IN CHARGE OF WORK, TITLE

Insp Type Foundation: Framing: Plumbing: Final:			THE Did he Construction Women of Austin for &
Inspection Record			A
Date			

	(R2)
	BUILDING PERMIT REPORT
D	ATE: 12 Sept. 2660 ADDRESS: 18 Tide Mill Rd CBL: 212-13-660
RI	EASON FOR PERMIT: TO CONSTAUCT a 8'X 10 Storage shed.
в	JILDINGOWNER: The Dykess
PE	RMIT APPLICANT:
US	E GROUP: \mathcal{M} CONSTRUCTION TYPE: 58 CONSTRUCTION COST: $9/390$ PERMIT FEES: $9/360$
	e City's Adopted Building Code (The BOCA National Building code/1999 with City Amendments) e City's Adopted Mechanical Code (The BOCA National Mechanical Code/1993)
	CONDITION(S) OF APPROVAL
Th	is permit is being issued with the understanding that the following conditions Shall be met: $\frac{\mathcal{K}}{\mathcal{K}}$
1. 2. 3.	This permit does not excuse the applicant from meeting applicable State and Federal rules and laws. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection) "ALL LOT LINES SHALL BE CLEARLY MARKED BEFORE CALLING." Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor elevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6" of the same material. Section 1813.5.2
	Foundations anchors shall be a minimum of 1/2" in diameter, T' into the foundation wall, minimum of 12" from corners of foundation and a maximum 6' O.C. between bolts. Section 2305.17
	Waterproofing and dampproofing shall be done in accordance with Section 1813.0 of the building code.
	Precaution must be taken to protect concrete from freezing. <u>Section 1908.0</u> It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the
	TER OTOHOUT TECOHIMENOED HALA TECHNISCH IZHIL MILVEVOLEHELL XII TOHHUZHOH IDUM DEHDE CONCERT IN DIZCELL THIS IS GODE TO VEHIV MIZE UIC

proper setbacks are maintained.

Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the artic area by means of 1/2 inch gypsum board or the equivalent applied to the garage side. (Chapter 4, Section 407.0 of the BOCA/1999)

9. All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical

Code/1993). Chapter 12 & NFPA 211

10. Sound transmission control in residential building shall be done in accordance with Chapter 12, Section 1214.0 of the City's Building Code.

11. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", In occupancies in Use Group A, B.H-4, I-1, I-2, M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not be less than 30", but not more than 38"). Handrail grip size shall have a circular cross section with an outside diameter of at least 1 1/1" and not greater than 2". (Sections 1021 & 1022.0). Handrails shall be on both sides of stairway. (Section 1014.7)

12. Headroom in habitable space is a minimum of 7.6". (Section 1204.0)

13. Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 "maximum rise. All other Use Group minimum 11" tread, 7" maximum rise. (Section 1014.0)

14. The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8") 1014.4

15. Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508)mm, and a minimum net clear opening of 5.7 sq. ft. (Section 1010.4)

16. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly

from the apartment to the building exterior with no communications to other apartment units. (Section 1010.1)

All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self closer's. (Over 3 stories in height requirements for fire rating is two (2) hours. (Section 710.0)

18. The boiler shall be protected by enclosing with (1) hour fire rated construction including fire doors and ceiling, or by providing automatic

extinguishment. (Table 302.1.1)

- 19. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1999), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):
 - In the immediate vicinity of bedrooms
 - In all bedrooms

In each story within a dwelling unit, including basements

20. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. (Section 921.0)

21. The Fire Alarm System shall maintained to NFPA #72 Standard.

22. The Sprinkler System shall installed and maintained to NFPA #13 Standard.

23. All exit signs, lights and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023.0 & 1024.0 of the City's Building Code. (The BOCA National Building Code/1999)

24. Section 25 – 135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".

25. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification the Division of Inspection Services.

26. Ventilation shall meet the requirements of Chapter 12 Sections 1210.0 of the City's Building Code. (Crawl spaces & artics).

27. All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade. No closing in of walls until all electrical (min. 72 hours notice) and plumbing inspections have been done.

28. All requirements must be met before a final Certificate of Occupancy is issued.

- (29. All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code (The BOCA National Building Code/1999).
 - 30. Ventilation of spaces within a building shall be done in accordance with the City's Mechanical code (The BOCA National Mechanical Code/1993). (Chapter M-16)

31. Please read and implement the attached Land Use Zoning report requirements.

232. Boring, cutting and notching shall be done in accordance with Sections 2305.3, 2305.3.1, 2305.4.4 and 2305.5.1 of the City's Building Code.

33. Bridging shall comply with Section 2305.16.

34. Glass and glazing shall meet the requirements of Chapter 24 of the building code. (Safety Glazing Section 2405.0)

35. All signage, shall be done in accordance with Section 3102.0 signs of the City's Building Code, (The BOCA National Building Code/1999).

P. Sacruci Dictises, Building Inspector

1.1. McDougall, PFD

Marge Schmuckal, Zoning Administrator

PSH ILIZS99

**This Permit is berewith issued,on the basis of plans submitted and cooditions placed the plans, any deviations shall require a separate approval.

...THIS PERMIT HAS BEEN ISSUED WITH THE UNDERSTANDING THAT ALL THE CONDITIONS OF THE APPROVAL SHALL BE COMPLETED. THEREFORE, BEFORE THE WORK IS COMPLETED A REVISED PLAN OR STATEMENT FROM THE PERMIT HOLDER SHALL BE SUBMITTED TO THIS OFFICE SHOWING OR EXPLAINING THAT THE CONDITIONS HAVE BEEN MET. IF THIS REQUIREMENT IS NOT RECEIVED YOUR CERTIFICATE OF OCCUPANCY SHALL BE WITHHELD.

**** Certificate of Occupancy Fees: \$50.00 each

***** All PLANS THAT REQUIRE A PROFESSIONAL DESIGN'S SEAL,(AS PER SECTION 114.0 OF THE BUILDING CODE) SHALL ALSO BE PRESENTED TO THIS DIVISION ON AUTO CAD LT. 2000 OR REQUIVALENT.

THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

Building or Use Permit Pre-Application Additions/Alterations/Accessory Structures

To Detached Single Family Dwelling

In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or Use Permit.

NOTE ** If you or the property owner owes real estate or personal property taxes or user charges on any property within the City, payment arrangements must be made before permits of any kind are accepted. Location/Address of Construction: Tax Assessor's Chart, Block & Lot Number Telephone#: Campuici Diskes 7101-9840 Chart# Block# Owner's Address: Lessee/Buyer's Name (If Applicable) Cost Of Work: 1329.00 \$ 36.0 Proposed Project Description:(Please be as specific as possible) Contractor's Name, Address & Telephone Rec'd By: Separate permits are required for Internal & External Plumbing, HVAC and Electrical installation. • All construction must be conducted in compliance with the 1996 B.O.C.A. Building Code as amended by Section 6-Art II. ·All plumbing must be conducted in compliance with the State of Maine Plumbing Code. •All Electrical Installation must comply with the 1996 National Electrical Code as amended by Section 6-Art III. •HVAC(Heating, Ventilation and Air Conditioning) installation must comply with the 1993 BOCA Mechanical Code. You must Include the following with you application: SP / 1200 1) A Copy of Your Deed or Purchase and Sale Agreement 2) A Copy of your Construction Contract, if available -3) A Plot Plan (Sample Attached) If there is expansion to the structure, a complete plot plan (Site Plan) must include: The shape and dimension of the lot, all existing buildings (if any), the proposed structure and the distance from the actual property lines. Structures include decks porches, a bow windows cantilever sections and roof overhangs, as well as, sheds, pools, garages and any other accessory structures. Scale and required zoning district setbacks - 4) Building Plans (Sample Attached) A complete set of construction drawings showing all of the following elements of construction: Cross Sections w/Framing details (including porches, decks w/ railings, and accessory structures) Floor Plans & Elevations Window and door schedules Foundation plans with required drainage and dampproofing Electrical and plumbing layout. Mechanical drawings for any specialized equipment such as furnaces, chimneys, gas equipment, HVAC equipment (air handling) or other types of work that may require special review must be included. Certification tereby certify that I am the Owner of record of the named property, or that the proposed work is authorized by the owner of record and it I have been authorized by the owner to make this application as his/her authorized agent. I agree to conform to all applicable laws this jurisdiction. In addition, if a permit for work described in this application is issued, I certify that the Code Official's authorized resentative shall have the authority to enter all areas covered by this permit at any reasonable hour to enforce the provisions of the les applicable to this permit.

Building Permit Fee: \$30.00 for the 1st \$1000.cost plus \$6.00 per \$1,000.00 construction cost thereafter.

ignature of applicant:

Date: 4

88/85/1997 16:32

THIS IS NOT A BOUNDARY SURVEY

PAGE COUNTY MORTGAGE INSPECTION OF: DEED BOOK ___11768 PAGE PLAN BOOK _ 150 43 LOT


ADDRESS: 18 Tide Mill Road, Portland, Maine

Job Number: 144-48

Buyers: Thomas & Cindy Dykes

Inspection Date: 7-17-97

Sellers: LeAnne Mark



[HEREBY CERTIFY TO: Hopkmann & Abbondanza: The Mortgage Office and its title iconer.

Monuments found did not conflict with the deed description.

The dwelling actbacks do not violate town zoning requirements.

As delinested on the Federal Emergency Management agency Community Pened: 230051-0012 B

The electure does not fall within the special flood hexard zone. The land does not fall within the special flood hazard zone,

APPARENT EASTMENTS AND ENGINE OF TAY ARE SHOWN OTHER ENCUMERANCES, RECORDED OR NOT. MAY EXIST. THIS SKETCH WILL NOT REVEAL ABUTTING DEED CONVICTS. IF ARY.

Livingston - Hughes Professional Land Surveyors ss Cuines Roed Kennebunkport - Mains 04048 207-967-9761 phone/inx


THIS SKETCH IS FOR MORTGAGE PURPOSES ONLY

<u>10</u> YEAR WARRANTY!!

THE HOME DEPOT & SHEDS USA

Finest Quality Sheds "Delivered, Built, Guaranteed"

Sku # 335-406 Sku # 335-969(MD)



"The New Yorker"

Shown as 8x10, vertical T-111 with a peak roof

The New Yorker includes:


2×4/24"0C

- 40" double door
 One window w/shutters & flower box
- Free pressure treated floor joists, free gable vents

NEW YORKER PRICING			
*Sizes Avail.	<u>T-111</u>	Pine	<u>Cedar</u>
8x8	\$995.00	\$1075.00	\$1375.00
8x10	\$1225.00	(\$1325.00)	\$1525.00
10x10	\$1475.00	\$1665.00	\$1905.00

Options for All Sheds	
4' Pressure treated ramp	\$44.00
Window screen (each)	\$13.00
4' Storage loft for 8' wide sheds	\$65.00
4' Storage loft for 10' wide sheds	\$80.00
(loft storage space will vary with roof style)	
<u>UPGRADES</u>	
5	

١	(lott storage space will vary with roof style)				
	<u>UPGRADES</u>				
Pressure treated plywood floor\$1.2					
2"x6" Floor joists for 8' wide sheds \$.92/sq.f					
	(2"x6" floor joists are standard on all 10' wide sheds)				
١	*From 40" to 54" Double Door\$44.00				
	*From 40" to 66" Double Door\$84.00				
	*From 40" to 78" Double Door\$114.00				
	*54" Double Doors not available on 8x8 New Yorker. 66" & 78"				
	Double Doors not available on any New Yorker or 8x12 and 10x12				
	Bostonian due to space restrictions.				




"The Bostonian"

Shown as 8x12, horizontal tongue & groove pine with an extended front peak roof

The Bostonian includes:

- 40" double door
- Two windows w/shutters & flower boxes
- <u>Free</u> pressure treated floor joists, <u>free</u> gable vents

BOSTONIAN PRICING					
*Sizes Avail.	<u> 111-T</u>	<u>Pine</u>	Cedar		
8x12	\$1445.00	\$1525.00	\$1815.00		
8x14	\$1675.00	\$1865.00	\$2085.00		
8x16	\$1885.00	\$2135.00	\$2335.00		
10x12	\$1735.00	\$2135.00	\$2275.00		
10x14	\$1995.00	\$2295.00	\$2555.00		
10x16	\$2225.00	\$2575.00	\$2925.00		



"The Portsmouth"

Shown as 8x14, vertical tongue & groove cedar with a gambrel roof

The Portsmouth includes:

- 40" double door and 26" single door
- Two windows w/shutters & flower boxes
- <u>Free</u> pressure treated floor joists, <u>free</u> gable vents

PORTSMOUTH PRICING					
*Sizes Avail.	<u>T -111</u>	<u>Ріпе</u>	<u>Cedar</u>		
8x12	\$1515.00	\$1585.00	\$1875.00		
8x14	\$1735.00	\$1925.00	\$2145.00		
8x16	\$1955.00	\$2205.00	\$2395.00		
10x12	\$1805.00	\$2195.00	\$2335.00		
10x14	\$2065.00	\$2355.00	\$2615.00		
10x16	\$2285.00	\$2635.00	\$2985.00		
I					

FREE DELIVERY (to most areas) AND BUILT ON YOUR SITE!!

Please check with your local Home Depot to see if you qualify for free delivery.

Your choice of roof style and shingle color... <u>FREE!!</u>

All sheds come complete from shingled roof to concrete block supports!

Skilled craftsmen completely assemble your shed on site. Any questions? Contact your local Home Depot.

*All dimensions are approximate.

MA/NH/ME/RI/VT

2/00