

Tilt Sash Replacement Kits

Weather Shield® Premium Windows



Heavy Duty Protection You Can Count On

Sash exteriors feature low-maintenance, heavy-duty extruded aluminum cladding that resists denting, dimpling, fading and chalking far better than thinner roll-formed aluminum exteriors found on many other brands of windows.

Weather Stripping

Both sash feature double weather stripping that provides a strong, positive seal for greater resistance to air and water infiltration.

Everything You Need To Get Started

Tilt sash replacement kits include two sash with sash lock and keeper, two jamb liners with calibrated balances, eight jamb liner brackets with stainless steel screws, two vinyl sash stops and a head parting stop and weather strip.



Tilt Sash Replacement Kits

Tilt Sash Replacement Kits from Weather Shield® can breathe new life into older windows with standard and custom sizes that precisely fit existing window frames. These sash replacement kits are easy to install with minimal disturbance to the surrounding wall trim, wallpaper or paint. Plus, their unique tilt-in sash design allows for easier cleaning of both glass surfaces from inside your home. That's something that's not often seen on sash replacement kits offered by other manufacturers.

INSTALLATION INSTRUCTIONS



STEP 1: Remove the old sash by taking out the inside stop mouldings from the side jambs using a pry bar or putty knife.



STEP 2: Cut out all cords and weights. Remove the bottom sash first, then the top sash.



STEP 3: Prepare the frame by positioning the brackets for the vinyl jamb liner about 4" from the top and bottom. Secure in place.



STEP 4: Install the vinyl jamb liner by placing the foam gasket at the top of each liner, place against brackets and snap in.



STEP 5: Install the sash by holding the top sash at 90 degrees and level with the cams in the vinyl jamb liner. Engage the corner pins and tilt the sash upright in the vinyl track while sliding the sash down. Repeat with the bottom sash.